



ADR Touch Control PRO 250 Cement Machine (jig only without platens)

Code: 39-7170/02

Product Group: [ADR 250 Cement Machines](#),
[Automatic Compression Machines](#)

- 250 kN capacity
- Meets requirements of EN 1354-4, EN 196-1, ISO 679, EN 459-2, EN 1015-11, EN 13454-2, ASTM C109/C109M
- Cement specimens
- Tests 100, 70.7, 50 and 40 mm cubes
- Calibration accuracy and repeatability conforms to BS EN ISO 7500-1; ASTM E4
- Supplied with Windows(R) download software as standard
- When used for cube testing distance pieces (EN) of the appropriate size must be ordered separately.

Designed to provide comprehensive test facilities, this compression machine is controlled by the automatic console.

The control port is connected to the 250 kN load frame, attachment of a flexural frame is not included. The 250 kN frame is supplied complete with compression jig and meets the requirements of EN 196-1. The 40 mm, 50 mm/2.0 inch square platens are sold separately.

Further Information

The ADR Touch Control PRO will deliver all the features and quality of the established ADR-Auto range, with its 20 year history, but with a new sleek design and additional capabilities. The console assembly consists of an ADR Touch Control PRO and power base which can be used with all existing concrete and cement frames

User interface

The new ADR Touch Control PRO has an improved user interface providing a high quality platform for testing that will enhance the performance of our compression machines. It now has a larger 7-inch colour touch screen with a higher definition display, allowing easier observation of test progress. A favourites option is also available, allowing users to save the most common set-ups for immediate access, without the need for navigating through selection menus.

User flexibility

The ADR Touch Control PRO has a unique flexible head with rotation capabilities of 75-degrees and a 45-degree tilt, improving usability and comfort for individual users. It is available with four languages English, Spanish, Portuguese and French, making it even more user-friendly and accessible to a wider audience. The new LAN connectivity feature lets the operator use the PC based APP (ELE Logger) to download test results away from the test area. User flexibility has also increased with the new ADR Touch Control PRO as it can now be operated remotely, so tests can

be initiated away from the test area. Many issues can be resolved quickly by our service team through the new remote diagnostics feature and updating to the latest version of software has never been easier.

Compatibility

The all new dual sensor capabilities allow users to test both concrete and cement samples on one frame. The ADR Touch Control PRO is compatible with all existing compression frames and upgrade kits are also available. The upgrade kits can be used to convert existing ADR-Auto consoles to the new Automatic Digital Control Readout.

Testing times

The new generation ADR Compression Machines have an increased control over the pace rate, which allows users to run the pace rate higher than average, but still within standard. This produces an average time saving of 10% for a typical 150mm cube sample.

Electrical

Reduced component count and no wire design results in increased reliability and serviceability. New low voltage interlocks and e-stop has increased safety. The ADR Touch Control PRO has the latest Arm Core Processor technology which has improved the processing power and speed.

Specification

Voltage Supply	110 V 60 Hz 1 Ph
Overall Frame Dimensions	355 x 455 x 1230 mm (14" x 18" x 48.4")
Console Dimensions	760 x 520 x 1500 mm (30" x 20.5" x 59")
Standards	EN 1354-4, EN 196-1, ISO 679, EN 459-2, EN 1015-11, EN 13454-2, ASTM C109/C109M

Accessories



100 kN Flexural Fitting Kit ADR Auto for 220 - 240 V AC, 50 Hz, 1 ph

Code: [37-6135/01](#)



100 kN Flexural Fitting Kit ADR Auto for 220 - 240 V AC, 60 Hz, 1 ph

Code: [37-6135/06](#)



2000 kN Load Calibration Device complete with Handheld Readout Unit & Calibration Certificate ISO376

Code: [37-8315](#)



40mm Square Platen Set

Code: [39-5600/10](#)



BS/EN Standard Rectangular Platen

Code: [37-4860](#)



EN 12390-3/4 Distance Piece - 100 mm Depth

Code: [37-5180](#)




EN 12390-3/4 Distance Piece - 20 mm Depth

Code: [37-5110](#)



EN 12390-3/4 Distance Piece - 50 mm Depth

Code: [37-5120](#)



EN 12390-3/4 Distance Piece - 60 mm Depth

Code: [37-5140](#)



Extended Front Safety Gate for Use with 2000kN BS/EN Load Frames Fitted with Rectangular Platens.

Code: [37-4835](#)



Flexible Hose

Code: [5038B0027](#)



Impact Printer Rs232 Serial Connection. Supplied Complete with 1 Paper Roll.

Code: [37-4859/01](#)



Pair of Square Platens 2"

Code: [39-5600/11](#)



Set of Distance Pieces

Code: [39-6220](#)

Spares/Consumables



Pressure transducer, 0-700bar, 0.05 to 10v DC Output

Code: [6014A0062](#)



Pressure transducer, 0-70bar, 0.05 to 10v DC Output

Code: [6014A0065](#)

Alternatives



ADR Touch Control PRO 2000/250kN Auto BS EN Compression Machine

Code: [36-5155/06](#)



ADR Touch Control PRO 3000/250kN Auto BS EN Compression Machine

Code: [36-5170/06](#)



ADR Touch Control PRO 3000/250kN Auto BS EN Compression Machine

Code: [36-5170/01](#)