



ADR Touch Control PRO 3000/250kN Auto BS EN Compression Machine

Code: 36-5170/06

Product Group: Dual Frame Compression Machines

- 3000/250 kN capacity
- Meets requirements of EN 12390-3, -4, -12504-1, 1354, 1521, 13161, 1338 772- 1, -6, 13286-41 196- 1 459-2. BS 3892-3, 187
- Concrete and cement specimens
- Tests 200, 150, 100, 70.7, 50 and 40 mm cubes and cylinders up to 320 x 160 mm diameter
- Calibration accuracy and repeatability conforms to BS EN ISO 7500-1; ASTM E4
- Supplied with Windows(R) download software as standard

Designed to provide comprehensive test facilities, this twin-frame compression machine is controlled by the automatic console. The 3000 kN capacity frame meets the requirements of EN Standards and accepts the range of on-board accessories.

As the second outlet control port is connected to the 250 kN load frame, attachment of a flexural frame is not possible. The 250 kN frame is supplied complete with compression jig, 40 mm, 50 mm/2.0 inch square platens and meets the requirements of EN 196-1.

When selecting the frame to be used for testing the automatic changeover valve incorporated in the system delivers the hydraulic fluid to that frame.

Standards

EN 12350-6, EN 196-1

Further Information

The ADR Touch Control PRO will deliver all the features and quality of the established ADR-Auto range, with its 20 year history, but with a new sleek design and additional capabilities. The console assembly consists of an ADR Touch Control PRO and power base which can be used with all existing concrete and cement frames

User interface

The new ADR Touch Control PRO has an improved user interface providing a high quality platform for testing that will enhance the performance of our compression machines. It now has a larger 7-inch colour touch screen with a higher definition display, allowing easier observation of test progress. A favourites option is also available, allowing users to save the most common set-ups for immediate access, without the need for navigating through selection menus.

User flexibility

The ADR Touch Control PRO has a unique flexible head with rotation capabilities of 75-degrees

and a 45-degree tilt, improving usability and comfort for individual users. It is available with four languages English, Spanish, Portuguese and French, making it even more user-friendly and accessible to a wider audience. The new LAN connectivity feature lets the operator use the PC based APP (ELE Logger) to download test results away from the test area. User flexibility has also increased with the new ADR Touch Control PRO as it can now be operated remotely, so tests can be initiated away from the test area. Many issues can be resolved quickly by our service team through the new remote diagnostics feature and updating to the latest version of software has never been easier.

Compatibility

The all new dual sensor capabilities allow users to test both concrete and cement samples on one frame. The ADR Touch Control PRO is compatible with all existing compression frames and upgrade kits are also available. The upgrade kits can be used to convert existing ADR-Auto consoles to the new Automatic Digital Control Readout.

Testing times

The new generation ADR Compression Machines have an increased control over the pace rate, which allows users to run the pace rate higher than average, but still within standard. This produces an average time saving of 10% for a typical 150mm cube sample.

Electrical

Reduced component count and no wire design results in increased reliability and serviceability. New low voltage interlocks and e-stop has increased safety. The ADR Touch Control PRO has the latest Arm Core Processor technology which has improved the processing power and speed.

Accessories




100 kN Flexural Fitting Kit ADR Auto for 220 - 240 V AC, 60 Hz, 1 ph

Code: [37-6135/06](#)




Change over valve assembly kit for 230V, 50/60Hz

Code: [37-0011/01](#)




EN 12390-3/4 Distance Piece - 100 mm Depth

Code: [37-5180](#)




EN 12390-3/4 Distance Piece - 20 mm Depth

Code: [37-5110](#)



EN 12390-3/4 Distance Piece - 50 mm Depth

Code: [37-5120](#)



EN 12390-3/4 Distance Piece - 60 mm Depth

Code: [37-5140](#)



Flexible Hose

Code: [5038B0027](#)



Impact Printer Rs232 Serial Connection. Supplied Complete with 1 Paper Roll.

Code: [37-4859/01](#)

Spares/Consumables



Pressure transducer, 0-700bar, 0.05 to 10v DC Output

Code: [6014A0062](#)



Pressure transducer, 0-70bar, 0.05 to 10v DC Output

Code: [6014A0065](#)

Alternatives



ADR Touch Control PRO 2000/250kN Auto BS EN Compression Machine

Code: [36-5155/01](#)



ADR Touch Control PRO 250 Cement Machine (jig only without platens)

Code: [39-7170/06](#)



ADR Touch Control PRO 250 Cement Machine (jig only without platens)

Code: [39-7170/01](#)



ADR Touch Control PRO 250 Cement Machine (jig only without platens)

Code: [39-7170/02](#)