## **Product Sheet**



## **Paqualab** photometer

Code: 430-550

Product Group: Paqualab Test Meters

Lightweight and portable for laboratory or field use.

Accurate results using tablet reagents which have a long shelf-life.

Over 40 different water tests available for use with the photometer.

Ideal for use with ELE's Paqualab systems.

This Paqualab photometer is simple to use, robust in construction and designed for on-site analysis. The photometer provides dependable results to enable decisions on water quality to be made instantly and with confidence.

Simple operation with automatic set-up for each test. Designed for reagent systems in tablet form.

Rapid access to frequently used tests from a choice of over 100 parameters/methods.

With dilution tube, 8 glass curvettes, operating instructions and hard carrying case.

## **Further Information**

Test reagent tablets are not supplied. Available separately under Photometer Reagents.

| Specification          |  |
|------------------------|--|
| Instrument type        | Dual light source photometer<br>offering direct-reading of<br>pre-programmed test<br>calibrations, absorbance and<br>transmittance |
| Wavelengths            | 450 nm, 500 nm, 550 nm, 570<br>nm, 600 nm, 650 nm  |
| Accuracy               | ± 1.0% T   |
| Display                | 320 x 240 pixel LCD with<br>backlight and contrast<br>adjustment   |
| User interface         | On-screen prompts available in<br>English, French, Spanish,<br>German, Italian, Turkish and<br>Mandarin (Chinese)                  |
| Dimensions (w x l x h) | 150 x 250 x 70 mm  |
| Weight                 | 975g   |
| IP rating              | IP67   |



www.ele.com +44 (0) 01525 249 200



Power supply

Test cuvettes

3x 1.5V AA batteries (typically 40 hours) Automatic centring for cylindrical cuvettes from 13 to 20 mm OD

