



Automatic Soil Compactor BS CE Compliant

Code: 24-8080/01

Product Group: BS CE Automatic Compactors

- With NEW CE Compliant guarding as an extra safety measure for users
- Five models meeting requirements of BS/EN and ASTM available
- Complies to BS 1377-4, BS 1924-2, EN 13286-2, EN 13286-47, ASTM D558, ASTM D698, ASTM D1557, AASHTO T99, AASHTO T134, AASHTO T180 standards
- Automatic re-setting of counter after completion of blow pattern

The time and effort required to prepare specimens for compaction studies and other test methods can often be costly and time-consuming. The use of an automatic, mechanical compactor will show considerable cost benefits over hand compaction methods.

These machines automatically compact specimens eliminating the laborious hand compaction method. The height and weight of the rammer are adjustable to suit test requirements.

An automatic blow pattern ensures optimum compaction for each layer of soil in compliance with the standards. The rammer travels across the mould and the table rotates the mould in equal steps on a base that is extremely stable. The number of blows per layer can be set at the beginning of the test.

Preset blow pattern ensures an even compaction, includes solid state controls for reliability and maintenance. An automatic digital counter resets to zero on the completion of a test. The selectable rammer has a drop height of 300-450mm, a selectable rammer weight of 2.5 or 4-5kg. A preset number of blows per layer can be set by thumb wheel control. A compaction rate of approximately 26 blows per minute. Accepts BS Standard Compaction and CBR moulds; also meets the requirements of BS 1377-4, BS 1924-2, EN 13286-2, EN 13286-47, ASTM D558, ASTM D698, ASTM D1557, AASHTO T99, AASHTO T134, AASHTO T180.

Specification

Standards

BS 1377-4, BS 1924-2, EN 13286-2, EN 13286-47, ASTM D558, ASTM D698, ASTM D1557, AASHTO T99, AASHTO T134,


| | |
|--------------|--|
| Rammer BS/EN | AASHTO T180 Circular faced, 50 mm dia, selectable to 2.5 kg or 4.5 kg weight |
| Rammer ASTM | Circular faced, 2 in (50.8 mm) dia, selectable to 5.5 lb (2.5 kg) or 10 lb (4.5 kg) weight |
| Drop BS/EN | Adjustable to 300 mm or 450 mm |
| Drop ASTM | Adjustable to 12 in (305 mm) or 18 in (457 mm) |
| Weight (kg) | 165 |

Accessories




BS Cbr Mould Body.

Code: [24-9198](#)



BS Extension Collar

Code: [24-9200](#)



BS Solid Base or Top Plate

Code: [24-9204](#)



BS Standard Compaction Mould 1000Cm Capacity.

Code: [24-9000](#)