



Double Wall Laboratory Oven - 0.7 cu. Ft. Capacity - 115vAC

Code: [88-0200/02](#)

Product Group: [Double Wall Laboratory Ovens](#)

- Sturdy, double wall welded steel construction.
- Thermostatically controlled.
- All components UL/CSA approved.
- Includes two plated shelves.

Designed for general laboratory tasks, Double Wall Laboratory Ovens are ideal for drying, baking, annealing, conditioning, sterilizing, evaporating, dehydrating and other general laboratory work. Available in a variety of sizes, this series of ovens is fully equipped with a thermometer and adjustable shelves. The double wall welded steel construction, baked enamel exterior, and corrosion resistant interior make this a sturdy, all-purpose laboratory oven.

115vAC, 50/60 Hz, 1Ø.

Specification

Capacity	0.7 cu. ft. (19.8 liter).
Chamber Size	12 " w. x 10" d. x 10" h. (305 x 254 x 254 mm).
Temperature Range	225 °C (43 7°F) maximum.
Shelves	Two included.
Thermometer	One included.
Overall Dimensions	14 " w. x 12 " d. x 17" h. (35 6 x 305 x 432 mm).
Amps	5.2
Watts	600
Weights	41 lbs. (18.6 kg).

Alternatives



Bench Oven - Digital PID Controller - 7 cu. ft. capacity - 115V

Code: [88-0140/02](#)



Bench Oven - Digital PID Controller - 7 cu. ft. capacity - 230V

Code: [88-0140/01](#)



Bench Oven - Hydraulic Thermostat - 7 cu. ft. capacity - 115vAC

Code: [88-0130/02](#)



Bench Oven - Hydraulic Thermostat - 7 cu. ft. capacity - 230vAC

Code: [88-0130/01](#)



Double Wall Laboratory - 3.0 cu. Ft. Capacity - 115vAC

Code: [88-0220/02](#)



Double Wall Laboratory - 3.0 cu. Ft. Capacity - 230vAC

Code: [88-0220/01](#)



Double Wall Laboratory Oven - 2.0 cu. Ft. Capacity - 115vAC

Code: [88-0210/02](#)



Forced Convected Oven - 18 cu. ft. capacity - 240V

Code: [88-0161/01](#)



Forced Convected Oven - 27 cu. ft. capacity - 240v

Code: [88-0166/01](#)



Forced Convected Oven - 6.9 cu. ft. capacity - 120V

Code: [88-0156/02](#)