
Product Sheet





Los Angeles Abrasion Machine with CE Safety Cabinet W/ Microswitches. 220-240V 60Hz 1Ph.

Code: 42-5310/06 Product Group: Los Angeles Abrasion Machine

The machine consists of a closed hollow cylindrical steel drum rotating around its horizontal axis on ball bearing units mounted on a sturdy base framework. Also the full enclosure ensures noise is minimized.

The drum is driven at a speed of between 30 - 33 rpm via an enclosed belt drive arrangement from an electric motor/gearbox unit situated on the base frame. Inside the drum a full length steel shelf is attached, accessed by a dust-proof opening.

The cylinder incorporates a removable internal shelf, one shelf position is provided to meet the requirements of both the ASTM and EN test standards.

Controls are located easily on the right-hand side of the machine at convenient operator height.

Start and stop push buttons and a subtracting revolution counter allows the user to preset the number of revolutions before an automatic stop.

Further Information


NOT AVAILABLE FOR SALE IN THE USA

Specification

Description

Power Supply EN 1097-2 ASTM C131 ASTM C535 NF P18-573 Los Angeles Abrasion Machine with CE Safety Cabinet 220 -240 V 60Hz 220 - 240 V AC, 60 Hz, 1 ph Yes Yes Yes Yes

Accessories







Set of 12 Abrasive Charges (ASTM).

Code: 42-5300/10



Set of 12 Abrasive Charges EN)

Code: 42-5305/10



Alternatives



Los Angeles Abrasion Machine Meets ASTM and European Standards. 220-240V 50Hz 1Ph.

Code: 42-5315/01



Los Angeles Abrasion Machine Meets ASTM and European Standards. 220-240V 60Hz 1Ph.

Code: 42-5315/06

