Product Sheet





Soil moisture meter.

Code: 514-126 Product Group: Soil Moisture

This instrument is rugged, hand-held for field derivation of soil moisture.

Buriable soil moisture blocks allow moisture levels to be measured throughout the soil profile.

It is easy to use and battery operated.

This instrument is the ideal companion for the new, slim design moisture blocks, which are placed in the soil and leads connected in turn, to the meter. The measured resistance of the block, in ohms, is converted to a corresponding reading between 0 and 100 on an empirical scale. In practical terms this empirical range covers the soil suction range 0.2 to 15 bar and using the calibration graphs of soil moisture content (dry weight percentage) against soil suction in bars, the soil moisture content may be determined.

In practical situations, resistance blocks are often placed at various depths in the soil to monitor soil moisture content profiles across the root zone. Experience will determine the optimum depth of placement depending on the particular soil type.

The soil moisture blocks are designed for use with this particular meter and give a uniform and quick response, made possible by their slim design (20mm diameter).

Further Information

Specification

Measuring range

Power requirements Weight 0-100 empirical range corresponds to 0.2-15 bar 1 x 9 V battery (supplied) 0.90

Accessories







Soil Moisture Block 0.9 m Lead

Code: 514-128



Soil Moisture Block 2.7 m Lead

Code: 514-130



Soil Moisture Block 4.5 m Lead

Code: 514-132

