# **Product Sheet**



## **Los Angeles Abrasion Machine**

Code: 42-5305/02

Product Group: Los Angeles Abrasion Machine

The machine consists of a closed hollow cylindrical steel drum rotating around its horizontal axis on ball bearing units mounted on a sturdy base framework.

The drum is driven at a speed of between 30 - 33 rpm via an enclosed belt drive arrangement from an electric motor/gearbox unit situated on the base frame. Inside the drum a full length steel shelf is attached, accessed by a dust-proof opening.

The cylinder incorporates a removable internal shelf, one shelf position is provided to meet the requirements of both the ASTM and EN test standards.

Controls are located easily on the right-hand side of the machine at convenient operator height.

Start and stop push buttons and a subtracting revolution counter allows the user to preset the number of revolutions before an automatic stop.

### Standards

ASTM C131, ASTM C535, AASHTO T96, NF P18-573

#### **Further Information**

110-120vAC, 60 Hz, 1ø.

### **Specification**

5,000 g each of aggregate and Capacity

charge.

Drum Speed 30-33 rpm.

Frame Welded structural steel.

Adjustable; automatic shut-off; Counter

push-button

reset and adjustment.

Controls Magnetic motor starter with

> overload protection and integral On-Off switches.

38.6" w. x 36.2" d. x 38.6" h. **Dimensions** 

(980 x 920 x 980 mm).

Net 882 lbs. (400 kg). Weight

1 HP Motor

+44 (0)1525 249 200

**=** +1 (800) 323 1242