



## Speedy Moisture Tester D2 Small 0-20% Moisture Range. Supplied Less Calcium Carbide

Code: [23-7502](#)

Product Group: [Rapid method by Speedy Moisture Tester](#), [Rapid method by Speedy Moisture Tester](#)

Uses a technique based on the fact that water will react with calcium carbide to form a gas and that the quantity of gas formed is directly proportional to the water present. The gas pressure is indicated on a built-in pressure gauge. The pressure gauge calibrated in percentage of moisture. Has a moisture range of 0-20% with gauge divisions every 0.2%. Holds a sample size of 6 g. Includes an electronic balance of 200 g capacity x 0.1 g readability and is supplied in plastic carrying case.

### Standards

ASTM D4944, AASHTO T217

### Further Information

**\*\*NOT AVAILABLE FOR SALE IN THE USA\*\***

### Specification

|                    |          |
|--------------------|----------|
| Model              | D2 Small |
| Moisture Range     | 0 to 20% |
| Gauge divisions    | 0.20%    |
| Sample weight g    | 6        |
| Weight complete kg | 5.5      |

### Accessories



#### Calcium Carbide Powder 500G.

Code: [23-7700](#)



## Reagent for Speedy Moisture Testers. Pack of 12 Cans 500 G Each. (Calcium Carbide)

Code: [23-7702](#)



## Speedy Calibration Unit Self Contained Unit.

Code: [23-7600](#)

### Alternatives



## Speedy Moisture Tester D2 Large 0-20% Moisture Range. Supplied Less Calcium Carbide

Code: [23-7452](#)



## Speedy Moisture Tester G2 Large 0-50% Moisture Range. Supplied Less Calcium Carbide

Code: [23-7462](#)