Product Sheet







ADR Touch Pro

Code: 1939C0030 Product Group: N/A

ELE International is pleased to announce the release of a new Automatic Digital Control Readout, the ADR Touch Pro.

It will deliver all the features and quality of the established ADR-Auto V2.0, with its 20-year design history as well as a new sleek design and additional capabilities.

1939C0030 consists of a Touch Pro and a power base which can be used with all existing compression frames.

The new ADR Touch Pro has an improved user interface providing a high-quality platform for testing that will enhance the performance of our compression machines. It includes a 7", high-resolution, colour display which improves the visibility of key test data and makes it simple to operate. It now has favourites options on the home screen for custom configuration making it quicker to access common types of tests.

The ADR Touch Pro is currently one of the only flexible heads in the market with rotation capabilities of 75-degrees and a 45-degree tilt, improving usability and comfort to individual users. It is available in four languages: English, Spanish, Portuguese and French, making it even more user-friendly and accessible to a wider audience in their native language. The new LAN connectivity feature lets the operator use the PC based APP (ELE Logger) to download test results away from the test area. User flexibility has also increased with the new ADR Touch Pro because it can now be operated remotely. The design increases ELE International's Any issues and updates can be resolved quickly by our service team through the new remote diagnostics feature.

The all new dual sensor capabilities allow users to test both concrete and cement samples on one frame. The ADR Touch Pro is compatible with all existing Compression Frames and upgrade kits are also available. The upgrade kits can be used to convert existing ADR-Auto V2.0 consoles to the new Automatic Digital Control Readout.

Specification

Screen resolution

7" 800 x 480 TFT LED touch screen, scratch proof and splash proof (IP31) Rotate up to 75 degrees

ADR Touch Head movement

= +1 (800) 323 1242

Product Sheet

www.ele.com +44 (0) 01525 249 200



horizontally and 45 degrees

vertically

Connection LAN + USB

Remote control: external PC Yes, using custom PC App
Remote control: download test Yes, using custom PC App

data

Memory storage Over 100 test profiles and 6

customised test profiles (favourites) per frame in flash. 4GB = millions of test storage

+ SD card

Printer Optional external printer + print

from PC

Calibration and accuracy 0.5% across range and 1% to

full load range

Multiple language support

Yes, available in English, Spanish, Portuguese and

French

Pace rate indicator

Yes

Load v time, goodness of test

Yes

Analysis of trend data

Yes