

## Rapid Moisture Testers



### Speedy Calibration Unit Self Contained Unit.

Code: [23-7600](#)

Attributes: [Description](#) = Speedy Calibration Unit, [Weight](#), lbs = 13

Standards: [ASTM D4944](#), [AASHTO T217](#)



### Speedy Moisture Tester D2 Large 0-20% Moisture Range. Supplied Less Calcium Carbide

Code: [23-7452](#)

Attributes: [Model/type](#) = D2 Large, [Moisture range %](#) = 0 to 20, [Gauge divisions %](#) = 0.2, [Sample weight g](#) = 20, [Dimensions w x d x h, "](#) = 518x382x212 mm, [Description](#) = Speedy Moisture Tester

Standards: [BS 812](#), [ASTM D4944](#), [AASHTO T217](#)



### Reagent for Speedy Moisture Testers. Pack of 12 Cans 500 G Each. (Calcium Carbide)

Code: [23-7702](#)

Attributes: [Description](#) = Calcium carbide powder - 12 x 500 g, [Stock Solution](#) = Calcium Carbide

Standards: [ASTM D4944](#), [AASHTO T217](#)



### Portable Electronic Balance

Code: [23-7452/12](#)

Attributes: [Scale](#) = 0-200 g, [Description](#) = Portable Electronic Balance

Standards: [ASTM D4944](#), [AASHTO T217](#)