

Rapid method by Speedy Moisture Tester



Speedy Moisture Tester G2 Large 0-50% Moisture Range. Supplied Less Calcium Carbide

Code: [23-7462](#)

Attributes: [Model/type](#) = G2 Large, [Moisture range %](#) = 0 to 50, [Gauge divisions %](#) = 0.5, [Sample weight g](#) = 8

Standards: [ASTM D4944](#), [AASHTO T217](#)



Speedy Moisture Tester D2 Small 0-20% Moisture Range. Supplied Less Calcium Carbide

Code: [23-7502](#)

Attributes: [Model/type](#) = D2 Small, [Moisture range %](#) = 0 to 20, [Gauge divisions %](#) = 0.2, [Sample weight g](#) = 6

Standards: [ASTM D4944](#), [AASHTO T217](#)



Speedy Moisture Tester D2 Large 0-20% Moisture Range. Supplied Less Calcium Carbide

Code: [23-7452](#)

Attributes: [Model/type](#) = D2 Large, [Moisture range %](#) = 0 to 20, [Gauge divisions %](#) = 0.2, [Sample weight g](#) = 20, [Dimensions w x d x h, "](#) = 518x382x212 mm, [Description](#) = Speedy Moisture Tester

Standards: [BS 812](#), [ASTM D4944](#), [AASHTO T217](#)
