

Penetration Test




Standard Penetrometer

Code: 46-5290

Attributes: Description = Standard Penetrometer

Standards: BS 2000-49, EN 1426, EN 13179-2, IP 49, ASTM D5, AASHTO T49



Semi-Automatic Penetrometer

Code: 46-5295/01

Attributes: Description = Semi-Automatic Penetrometer, Power Supply = 220 - 240 V AC, 50 - 60 Hz, 1ph

Standards: BS 2000-49, EN 1426, EN 13179-2, ASTM D5, AASHTO T49, IP 49



Penetration Needle

Code: 46-5360/10

Attributes: Description = Penetration Needle

Standards: BS 2000-49, EN 1426, EN 13179-2, ASTM D5, AASHTO T49, IP 49



Penetration Needle

Code: 46-5340/C

Attributes: Description = Penetration Needle - NPL verified, Weight, kg = 0.0025

Standards: BS 2000-49, EN 1426, EN 13179-2, ASTM D5, AASHTO T49, IP 49



Transfer Dish

Code: 46-5800

Attributes: Description = Transfer Dish

Standards: BS 2000-49, EN 1426, EN 13179-2, ASTM D5, AASHTO T49, IP 49



Penetration Tin

Code: 46-5860

Attributes: Description = Penetration Tin for 200 to 350 mm depths, Weight, kg = 0.03

Standards: BS 2000-49, EN 1426, EN 13179-2, ASTM D5, AASHTO T49, IP 49



Penetration Tin

Code: 46-5861

Attributes: Description = Penetration Tin for less than 200 mm depths,
Weight, kg = 0.025

Standards: BS 2000-49, EN 1426, EN 13179-2, ASTM D5, AASHTO T49, IP
49



Automatic Penetrometer

Code: 46-5380/01

Attributes: Description = Automatic Penetrometer

Standards:



Constant Temperature Bath 21 - 56°C

Code: 46-5500/01

Attributes: Description = Constant Temperature Bath

Standards: