

Accessories for the Marshall Test



Asphalt Flow Indicator with Brake - English

Code: [45-6892](#)

Attributes: [Weight, oz. = 12](#), [Description = Asphalt Flow Indicator with Brake - English](#)

Standards: [ASTM D6927](#), [AASHTO T245](#)




Asphalt Flow Indicator with Brake - Metric

Code: [45-6894](#)

Attributes: [Weight, oz. = 12](#), [Description = Asphalt Flow Indicator with Brake - Metric](#)

Standards: [ASTM D6927](#), [AASHTO T245](#)



Digital Proving Ring, 6,000 lbs (28.0 kN)

Code: [78-0764](#)

Attributes: [Overall Height, mm = 248](#), [Description = Digital Proving Ring, 6,000 lbs \(28.0 kN\)](#)

Standards:



Digital Proving Ring, 11,200 lbs (50.0 kN)

Code: [78-0864](#)

Attributes: [Overall Height, mm = 248](#), [Description = Digital Proving Ring, 11,200 lbs \(50.0 kN\)](#)

Standards:



Proving Ring 10,000 lbf Capacity

Code: [PR-100](#)

Attributes: [Description = Proving Ring 10,000 lbf Capacity](#)

Standards:



Digital Proving Ring, 10,000 lbs

Code: [PRD-100](#)

Attributes: [Description = Digital Proving Ring, 10,000 lbs](#)

Standards:



Digital Proving Ring, 6,000 lbs

Code: [PRD-60](#)

Attributes: [Description = Digital Proving Ring, 6,000 lbs](#)

Standards:



4" Lottman Breaking Head

Code: [45-6860](#)

Attributes: [Strips = 3" l. x 1/2" w. x 3/4" h. \(76.2 x 12.7 x 19 mm\) with 2" \(50.8 mm\) radius on contact end.](#), [Description = 4" Lottman Breaking Head](#)

Standards: [ASTM D6931](#), [AASHTO T283](#)



4" Marshall Breaking Head

Code: [45-6855](#)

Attributes: [Description = 4" Marshall Breaking Head, Base diameter, " = 6](#), [ASTM D6927-15 = Yes](#)

Standards: [EN 12697-34](#)



50kN Clamped Boss Load Ring

Code: [78-0860](#)

Attributes: [Description = Clamped Boss Load ring - 50 kN](#), [Value of CBR % = Above 40%](#), [Overall Height, mm = 248](#), [Force Capacity, kN = 50](#), [Load device type = Load ring](#)

Standards: [EN 12697-34](#)