

Digital Tritest 50 Load Frame



Clamped Boss Load Ring - 3.0 kN

Code: 78-0160

Attributes: Description = Load ring - 3 kN, Force Capacity, kN = 3, Weight, lbs = 9.25

Standards: BS 1377, ASTM D3080



Electronic Digital Indicator, 1.0"/>" data-bbox="284 257 740 275"/>

Code: 88-4220

Attributes: Scale Divisions, tons/sq. Ft. = 0.0001" (0.002 mm), Description = Electronic Digital Indicator, 1.0"/>" data-bbox="284 296 851 326"/>

Standards:



Clamped Boss Load Ring - 2.0 kN

Code: 78-0060

Attributes: Description = Load ring - 2 kN, Force Capacity, kN = 2, Value of CBR % = Up to 8%, Capacity, lbf = 450, Capacity kN = 2.0

Standards: BS 1377, ASTM D3080



Clamped Boss Load Ring - 10.0 kN

Code: 78-0460

Attributes: Description = Load ring - 10 kN, Value of CBR % = 8% to 40%, Weight, lbs = 10.54, Force Capacity, kN = 10

Standards:



Clamped Boss Load Ring - 4.5 kN

Code: 78-0260

Attributes: Description = Load ring - 4.5 kN, Load device type = Load ring, Force Capacity, kN = 4.5, Weight, lbs = 9.25

Standards:



50kN Clamped Boss Load Ring

Code: 78-0860

Attributes: Description = Clamped Boss Load ring - 50 kN, Value of CBR % = Above 40%, Overall Height, mm = 248, Force Capacity, kN = 50, Load device type = Load ring

Standards: EN 12697-34



Clamped Boss Load Ring - 28.0 kN

Code: 78-0760

Attributes: Description = Load ring - 28 kN, Value of CBR % = Average range of CBR, Load device type = Load ring, Force Capacity, kN = 28, Overall Height, mm = 248, ASTM D4429 = Yes

Standards: BS 1377, BS 1924



Digital Tritest 50 Load Frame

Code: 25-3518/01

Attributes: Voltage Supply = 220-240V 50/60Hz, CBR Penetration = Yes, Unconfined Compression = Yes, Unconfined Compression = Yes, Description = Digital Tritest 50 Load Frame, Consolidated Undrained = Yes, Consolidated Drained = Yes, Capacity, lbf = 11,200

Standards: BS 1377-7, BS 1377-8, BS 1924-2, ASTM D1883, ASTM D2166, ASTM D2850, ASTM D4767, ASTM D7181, AASHTO T99, AASHTO T134, AASHTO T135, AASHTO T136, AASHTO T180, AASHTO T193, AASHTO T208, AASHTO T296, AASHTO T297



Digital Tritest 50 Load Frame

Code: 25-3518/02

Attributes: Voltage Supply = 110-20V 50/60 Hz, CBR Penetration = Yes, Unconfined Compression = Yes, Unconfined Compression = Yes, Description = Digital Tritest 50 Load Frame, Capacity, lbf = 11,200

Standards: ASTM D1883, ASTM D2166, ASTM D2850, ASTM D4767, ASTM D7181, AASHTO T99, AASHTO T134, AASHTO T135, AASHTO T136, AASHTO T180, AASHTO T193, AASHTO T208, AASHTO T296, AASHTO T297



Dial Gauge 25mm Travel X 0.01mm Divisions

Code: 25-4210

Attributes: Description = Dial gauge 25mm travel x 0.01mm divisions, Dial Indicator = 25 mm Range

Standards: BS 1377



Dial Indicator - 1.0" Range

Code: 88-4100

Attributes: Description = Mechanical Dial Indicator - 1.0" Range, Dial Indicator = 1.0" Range

Standards:



2 Channel Digital Readout, English

Code: [27-1108/02](#)

Attributes: [Rated Power = 110vAC, 50/60Hz, 1Ø.](#), [Description = 2 Channel Digital Readout, English](#)

Standards:



2 Channel Digital Readout, Metric

Code: [27-1109/02](#)

Attributes: [Rated Power = 110vAC, 50/60Hz, 1Ø.](#), [Description = 2 Channel Digital Readout, Metric](#)

Standards: