

Loss-on-Ignition



Controller, for use in 83-4170/01

Code: [83-4170/11](#)

Attributes: [Description](#) = Controller, for use in 83-4170/01

Standards:



Thermostat, KGrade, 370 long, dia 2.5, for 83-4170/01

Code: [83-4170/10](#)

Attributes: [Description](#) = Thermostat, KGrade, 370 long, dia 2.5, for 83-4170/01

Standards:



Element/Chamber complete, heating, for use in 83-4170/01

Code: [83-4170/12](#)

Attributes: [Description](#) = Element/Chamber complete, heating, for use in 83-4170/01

Standards:



Element heating for use in 83-4170

Code: [83-4170/14](#)

Attributes: [Description](#) = Element heating for use in 83-4170

Standards:



Refractory brick for 83-4170/01

Code: [83-4170/13](#)

Attributes: [Description](#) = Refractory brick for 83-4170/01

Standards:



Muffle Furnace

Code: [83-4170/01](#)

Attributes: [Description](#) = Muffle Furnace, Voltage Supply = 220 – 240 V AC, 50/60 Hz, 1 ph

Standards: EN 196-2, EN 459-2, EN 13454-2, BS 1016-4, ISO 344, ISO 1171, ASTM D2361, ASTM D2795, ASTM D3714