


Tri-Flex 2 Permeability Test Cell




1.4" Porous Stones

Code: 25-4461

Attributes: Description = Porous disc 1.4", Diameter, " = 1.4"

Standards: ASTM D2850, ASTM D4767, ASTM D5084, AASHTO T296, AASHTO T297, ASTM D7181



Porous Stones 2.8"

Code: 25-6721

Attributes: Description = Porous disc 2.8", Diameter, " = 2.8"

Standards: ASTM D2850, ASTM D4767, ASTM D5084, AASHTO T296, AASHTO T297, ASTM D7181



4.0" Porous Stones

Code: 25-7761

Attributes: Description = Porous disc 4.0", Diameter, " = 4.0"

Standards: ASTM D2850, ASTM D4767, ASTM D5084, AASHTO T296, AASHTO T297, ASTM D7181



Porous Disc 70mm Diameter Pack of 2.

Code: 25-6561

Attributes: Description = Porous disc 70 mm, Diameter, " = 70 mm

Standards: ASTM D2850, ASTM D4767, ASTM D5084, AASHTO T296, AASHTO T297, ASTM D7181



Porous Disc 100mm Diameter Pack of 2.

Code: 25-7661

Attributes: Description = Porous disc 100 mm, Diameter, " = 100 mm

Standards: ASTM D2850, ASTM D4767, ASTM D5084, AASHTO T296, AASHTO T297, ASTM D7181



Rubber Membrane 100mm/4 Inch Diameter. Pack of 10

Code: 25-7621

Attributes: Description = Rubber Membrane 4", Sample diameter = 100 mm, Thickness, " = 0.012

Standards: ASTM D2850, ASTM D4767, ASTM D5084, AASHTO T296, AASHTO T297, ASTM D7181



Acrylic Cap and Base Set 2.8"

Code: 25-0690/15

Attributes: Diameter, " = 2.8", Description = Acrylic Cap and Base Set 2.8"

Standards: ASTM D5084



Tri-Flex 2 Permeability Test Cell

Code: 25-0690

Attributes: Maximum Pressure, psi = 150, Description = Tri-Flex 2 Permeability Test Cell

Standards: ASTM D5084



2.416" Porous Stones

Code: 25-5661

Attributes: Diameter, " = 2.416", Description = 2.416" Porous Stones

Standards: ASTM D2850, ASTM D4767, ASTM D5084, AASHTO T296, AASHTO T297



Membrane Sealing Rings 2.8"

Code: 25-6641

Attributes: Diameter, " = 2.8", Description = Membrane Sealing Rings 2.8"

Standards: ASTM D2850, ASTM D4767, ASTM D5084, AASHTO T296, AASHTO T297



1.4" (35 mm) Sealing Rings

Code: 25-4281

Attributes: Description = Membrane Sealing Ring 1.4", Diameter, " = 1.4"

Standards: ASTM D2850, ASTM D4767, ASTM D5084, AASHTO T296, AASHTO T297



2.416" Sealing Rings

Code: 25-5663

Attributes: Weight, lbs = 0.25, Description = 2.416" Sealing Rings

Standards: ASTM D2850, ASTM D4767, ASTM D5084, AASHTO T296, AASHTO T297



1.4" Cap & Base Set

Code: [25-0690/13](#)

Attributes: [Diameter, " = 1.4"](#), [Description = 1.4" Cap & Base Set](#)

Standards: [ASTM D5084](#)



2.416" Cap & Base Set

Code: [25-0690/14](#)

Attributes: [Diameter, " = 2.416"](#), [Description = 2.416" Cap & Base Set](#)

Standards: [ASTM D5084](#)



70 mm Cap & Base Set

Code: [25-0690/10](#)

Attributes: [Diameter, " = 70mm](#), [Description = 70 mm Cap & Base Set](#)

Standards: [ASTM D5084](#)



4.0" Cap & Base Set

Code: [25-0690/17](#)

Attributes: [Diameter, " = 4.0"](#), [Description = 4.0" Cap & Base Set](#)

Standards: [ASTM D5084](#)



1.4" (35 mm) Rubber Membranes

Code: [25-4261](#)

Attributes: [Description = Rubber Membrane 1.4"](#), [Thickness, " = 0.012](#)

Standards: [ASTM D2850](#), [ASTM D4767](#), [ASTM D5084](#), [AASHTO T296](#),
[AASHTO T297](#), [ASTM D7181](#)



2.416" Rubber Membranes

Code: [25-5665](#)

Attributes: [Overall Height, mm = 9.8"](#), [Description = 2.416" Rubber Membranes](#)

Standards: [ASTM D2850](#), [ASTM D4767](#), [ASTM D5084](#), [AASHTO T296](#),
[AASHTO T297](#)



Rubber Membrane 70mm/2.8 Inch Diameter. Pack of 10.

Code: 25-6441

Attributes: Description = Rubber Membrane 2.8", Sample diameter = 70 mm, Thickness, " = 0.012

Standards: ASTM D2850, ASTM D4767, ASTM D5084, AASHTO T296, AASHTO T297, ASTM D7181



Membrane Sealing Ring 70mm Diameter Pack of 10.

Code: 25-6461

Attributes: Description = Membrane Sealing Ring 70 mm, Sample diameter = 70 mm, Diameter, " = 70 mm

Standards: ASTM D2850, ASTM D4767, ASTM D5084, AASHTO T296, AASHTO T297



Membrane Sealing Ring 100mm Diameter. Pack of 10.

Code: 25-7631

Attributes: Description = Membrane Sealing Ring 100 mm, Sample diameter = 100 mm, Diameter, " = 4.0"

Standards: ASTM D2850, ASTM D4767, ASTM D5084, AASHTO T296, AASHTO T297