



IF IT'S WORTH BUILDING, IT'S WORTH TESTING

Contents

www.ele.com
+44 (0) 01525 249 200



This wishlist was generated on 04/03/2016, and contains the following Products:

45-3845

Biodegradable Solvent

45-3820/02

Centrifuge Extractor 1,500 g

45-3825/02

Centrifuge Extractor 3,000 g

88-1104/02

Ohaus Electronic Balance - 35,000 g Capacity



Biodegradable Solvent

Code: [45-3845](#)

Product Group: [Asphalt Centrifuge Extractors](#)

5 gal. can.



Centrifuge Extractor 1,500 g

Code: 45-3820/02

Product Group: Asphalt Centrifuge Extractors,
Bitumen Extraction Test

Standards

ASTM D2172, AASHTO T164

Further Information

120vAC, 60 Hz, 1Ø.

Specification

Control	Variable speed, 0-3,600 rpm; brake for fast stopping.
Motor	1/6 h.p.
Cover	Aluminum; removable, with integral cup for adding solvent.
Housing	Aluminum; removable, sealed.
Bowl	Aluminum; removable.
Filter Discs	10 included.
Dimensions	17" w. x 17" d. x 18" h. (432 x 432 x 457 mm).
Weight	Net 85 lbs. (38.6 kg).



Centrifuge Extractor 3,000 g

Code: [45-3825/02](#)

Product Group: [Asphalt Centrifuge Extractors](#)

Standards

ASTM D2172, AASHTO T164

Further Information

120vAC, 60 Hz, 1Ø.

Specification

Control	Variable speed, 0-3,600 rpm; brake for fast stopping.
Motor	1/6 h.p.
Cover	Aluminum; removable, with integral cup for adding solvent.
Housing	Aluminum; removable, sealed.
Bowl	Aluminum; removable.
Filter Discs	10 included.
Dimensions	18" w. x 18" d. x 19" h. (457 x 457 x 483 mm).
Weight	Net 140 lbs. (63.5 kg).



Ohaus Electronic Balance - 35,000 g Capacity

Code: [88-1104/02](#)

Product Group: [Ohaus Series Electronic Balances](#)

Further Information

100-240V, 50/60 Hz.

Specification

Maximum Capacity	35000 g
Readability	0.5 g
Internal Calibration	NO
Pan Size (in/cm)	11.0 x 14.9 in / 28.0 x 37.7 cm
Dimensions w x h x d (in/cm)	14.9 x 18.4 x 5.0 in / 37 x 46.7 x 12.8 cm
Shipping Wt. (lb/kg)	24 lb / 10.6 kg