



IF IT'S WORTH BUILDING, IT'S WORTH TESTING

Contents

www.ele.com
+44 (0) 01525 249 200



This wishlist was generated on 27/05/2016, and contains the following Products:

24-4936

Stock Solution 8 oz.

36-0690/02

Accu-Tek Touch 250 Series 110V/60Hz

24-9095/01

Automatic Soils Compactor ASTM 220-240V 50Hz 1Ph.



Stock Solution 8 oz.

Code: [24-4936](#)

Product Group: [Sand Equivalent Test Set](#)

Standards

ASTM D2419, AASHTO T176



Accu-Tek Touch 250 Series 110V/60Hz

Code: 36-0690/02

Product Group: Accu-Tek Touch 250 Series

Standards

ASTM C39, AASHTO T22

Further Information

110vAC, 60 Hz, 1Ø.

Specification

Capacity	250,000 lbf (1,112 kN)
Frame	Upper and lower steel plate sections with four steel uprights, threaded and welded into place; 14 .75" w. x 12 " d. x 37" h. (375 x 305 x 940 mm).
Ram	6-1/8" (155 mm) diameter; 3" (76 mm) travel.
Upper Platen	Swivel seat type; 6-1/4" (159 mm) diameter.
Lower Platen	7" (178 mm) diameter.
Vertical Clearance	12 -1/2" (318 mm); or 14 -1/2" (368 mm) with lower spacer removed - (Upper and Lower platens installed).
Horizontal Clearance	9" (229 mm) between uprights.
Pump	1 h.p. (0.7kw) electro-hydraulic pump mounted within reservoir with overload protection.
Controls	Pump-mounted pressure compensated flow control

	valve with 4-position control lever and adjustable flow valve. Pump On/Off switch.
Display	5.7" (145 mm) touch screen display, incorporating full key pad (QWERTY type); pace deviation bargraph; automatic stress calculation; 2 GB of internal memory for storing thousands of test results; download data to PC via USB or to printer via RS-232 interface.
Range	2,500 to 25 0,000 lbf. (11 .2 to 1,112 kN).
Accuracy	Factory calibrated to within 0.5% of reading - from 1% to 100% of machine capacity.
Overall Dimensions	25 .5" w. x 12 " d. x 45 " h. (648 x 305 x 1,143 mm).
Weight	Net 535 lbs. (243 kg).

Spares/Consumables




Accutek Oil

Code: [9806-0016](#)



Ram Seal

Code: [4699-1316](#)



Automatic Soils Compactor ASTM 220-240V 50Hz 1Ph.

Code: [24-9095/01](#)

Product Group: [Automatic Compactors](#), [Automatic Soil Compactor](#)

Standards

ASTM D558, ASTM D559, ASTM D560, ASTM D698, ASTM D1557, AASHTO T99, AASHTO T134, AASHTO T135, AASHTO T136, AASHTO T180

Specification

Hammer	Circular faced, 2.0" (50.8 mm) dia. foot; selectable to either 5.5 lb.(2.5 kg) or 10 lb. (4.5 kg) weight.
Drop	Adjustable to either 12 " (305 mm) or 18" (457 mm)
Controls	Digital counter system, selector switch for either standard proctor test or modified proctor/CBR testing.
Dimensions	10" w. x 17" d. x 55 " h. (250 x 430 x 1,400 mm).
Weight	Net 41.9 lbs. (190 kg).

Spares/Consumables



Lead Cylinders

Code: [24-9095/13](#)



Modified Compaction Mould

Code: [24-9098](#)



Standard Compaction Mould

Code: [24-9097](#)