



IF IT'S WORTH BUILDING, IT'S WORTH TESTING

Contents

www.ele.com
+44 (0) 01525 249 200



This wishlist was generated on 08/07/2016, and contains the following Products:

34-6134/12

6" Compression Pads 70 Durometer

34-6132/12

4" Compression Pads 70 Durometer

34-6132/10

4" Compression Pads 60 Durometer



6" Compression Pads 70 Durometer

Code: [34-6134/12](#)

Product Group: [Concrete Capping Pads and Retainers](#)

Set of 2.

Standards

ASTM C1231, AASHTO T22

Further Information

Capping Pads with Retainers can only be used on compression testers with a vertical daylight opening of 14-1/2" (368 mm) between platens

Specification

Capping Pads.

Tough elastometric material; 60 durometer pads may be used on any strength concrete; however, the longevity is lowered when used on cylinders in excess of 5,500 psi. 70 durometer pads should be used only on cylinders where concrete is 4,500 psi or higher.

Retainers.

Machined, high alloy steel

Weights.

Pads: Net 8 oz. (227 g) ea.

Retainers:

4" (102 mm) Net 4 lbs. (1.8 kg) ea.

6" (152 mm) Net 8 lbs. (3.6 kg) ea.



4" Compression Pads 70 Durometer

Code: [34-6132/12](#)

Product Group: [Concrete Capping Pads and Retainers](#)

Set of 2.

Standards

ASTM C1231, AASHTO T22

Further Information

Capping Pads with Retainers can only be used on compression testers with a vertical daylight opening of 14-1/2" (368 mm) between platens

Specification

Capping Pads.

Tough elastometric material; 60 durometer pads may be used on any strength concrete; however, the longevity is lowered when used on cylinders in excess of 5,500 psi. 70 durometer pads should be used only on cylinders where concrete is 4,500 psi or higher.

Retainers.

Machined, high alloy steel

Weights.

Pads: Net 8 oz. (227 g) ea.

Retainers:

4" (102 mm) Net 4 lbs. (1.8 kg) ea.

6" (152 mm) Net 8 lbs. (3.6 kg) ea.



4" Compression Pads 60 Durometer

Code: [34-6132/10](#)

Product Group: [Concrete Capping Pads and Retainers](#)

Set of 2.

Standards

ASTM C1231, AASHTO T22

Further Information

Capping Pads with Retainers can only be used on compression testers with a vertical daylight opening of 14-1/2" (368 mm) between platens

Specification

Capping Pads.

Tough elastometric material; 60 durometer pads may be used on any strength concrete; however, the longevity is lowered when used on cylinders in excess of 5,500 psi. 70 durometer pads should be used only on cylinders where concrete is 4,500 psi or higher.

Retainers.

Machined, high alloy steel

Weights.

Pads: Net 8 oz. (227 g) ea.

Retainers:

4" (102 mm) Net 4 lbs. (1.8 kg) ea.

6" (152 mm) Net 8 lbs. (3.6 kg) ea.