



IF IT'S WORTH BUILDING, IT'S WORTH TESTING

Contents

www.ele.com
+44 (0) 01525 249 200



This wishlist was generated on 04/08/2016, and contains the following Products:

25-0623

Combination Permeameter



Combination Permeameter

Code: 25-0623

Product Group: Combination Permeameter,
Combination Permeameter Constant or Falling Head

- Plated steel chamber head assembly
- Corrosion-resistant cast aluminum base assembly
- Includes accessories for conducting both constant and falling head permeability studies

This combination permeameter has a transparent plastic chamber for soil specimens of either fine-grained or coarse-grained soils. Generally, soils containing 10 percent or more particles passing a 75 μm sieve are tested using the falling head assembly. More granular soils, containing 90 percent or more particles retained on the 75 μm sieve, are tested using the constant head assembly.

The cell is sealed at the top so that a vacuum may be used to saturate the specimen. Porous stones located at the top and bottom of the cell prevent sample flaking or washout. For constant head tests, a plastic funnel reservoir is mounted on an upright attached to the cell, providing a maximum head of 550 mm. Falling head tests are performed using the graduated pipette falling head reservoir, which gives a maximum head of 1000 mm and is graduated 0.2 ml.

Specification

Specimen size	63.5 x 63.5 mm (dia x l max) when using lower chamber only, 63.5 x 140 mm (dia x l max) when using both lower and extension chambers
Chamber	Transparent plastic, two sections
Base	Cast aluminium
Top seal	Plated steel with gaskets
Porous Stones	62.7 x 12.7 mm (diameter x thickness)
Constant head	Plastic, funnel reservoir, 550 mm maximum head
Falling head	Graduated pipette, 100 ml x 0.2 ml, 1000 mm maximum head

Product Sheet

www.ele.com
+44 (0) 01525 249 200



Weight kg	5
Specimen Size	2-1/2" diam. x 2-1/2" l. max. (63.5 x 63.5 mm) when using lower chamber only; 2-1/2" diam. x 5-1/2" l. max. (63.5 x 140 mm) when using both lower and extension chambers.
Capacity	Clear lucite; 1/4" (6.3 mm) wall; two sections.
Base	Cast aluminum.
Top Seal	Plated steel with gaskets.
Porous Stones	Mounts at top and bottom; 2.47" diam. x 1/2" thick (62.7 x 12.7 mm); 105-120 permeability rating; 300 micron, average pore size.
Constant Head	Plastic; funnel reservoir; 55 cm maximum head.
Falling Head	Graduated pipette; 100 mm x 0.2 mm; 100 cm. maximum head.
Weight	Net 11 lbs. (5 kg).

Spares/Consumables



Porous Stone 2.47" x .50"

Code: [T-308](#)