



IF IT'S WORTH BUILDING, IT'S WORTH TESTING

Contents

www.ele.com
+44 (0) 01525 249 200



This wishlist was generated on 13/09/2016, and contains the following Products:

25-0609

Standpipe Panel.

25-0607

Compaction Permeameter.

25-0611

De-Airing Tank.

25-0613

Soaking Tank.



Standpipe Panel.

Code: [25-0609](#)

Product Group: [Compaction Permeameter](#)

Complete with three glass tubes of 1.5, 3 and 5 mm diameter bore, approximately 1.4 metres long. Supplied with metre scale and thick walled flexible tubing. The glass tubes are fitted to a panel for wall mounting and connected to a 3-way outlet valve. Complete with three glass tubes of 1.5, 3 and 5 mm diameter bore, approximately 1.4 metres long. Supplied with metre scale and thick walled flexible tubing. The glass tubes are fitted to a panel for wall mounting and connected to a 3-way outlet valve.



Compaction Permeameter.

Code: 25-0607

Product Group: Compaction Permeameter

101.6 mm

Specification

Mould	Machined seamless steel tubing, plated
Capacity	101.6 x 116.4 mm (inside dia x h) 1/30 ft ³
Collar	50.8 mm high, machined
Top	Overflow valve assembly and water connection
Base	Cast aluminum, with inlet/outlet fitting
Porous stone	(4") 101.6 x 12.7 mm (diameter x thickness)
Weights	5.4 kg



De-Airing Tank.

Code: [25-0611](#)

Product Group: [Compaction Permeameter](#)

Manufactured from transparent plastic with de-airing jet inlet and a flow outlet connection with flexible tubing. The tank is manufactured to withstand a reduced pressure and is suitable for direct wall mounting.



Soaking Tank.

Code: [25-0613](#)

Product Group: [Compaction Permeameter](#)

With fixed overflow. Used for containing permeability cell during test.