



IF IT'S WORTH BUILDING, IT'S WORTH TESTING

Contents

www.ele.com
+44 (0) 01525 249 200



This wishlist was generated on 31/10/2016, and contains the following Products:

34-6775/02

Master Humidifier

39-1510/01

Laboratory Humidifier/vapouriser 220-240V 50/60 Hz



Master Humidifier

Code: [34-6775/02](#)

Product Group: [Master Humidifier](#)

Ultrasonic humidifiers produce a mist created by a piezo-electric device which produces an extremely fine, smoke-like fog. The vapor is dispensed by a small internal fan through an opening in the front or top of the unit. This fog travels just a few feet before evaporating into the surrounding atmosphere. Inside there is a small float valve and the p/e device which creates the fog by means of ultrasonic vibration of the water.

Further Information

120vAC, 60 Hz, 1Ø. 340 Watts.

Specification

Discharge	Horizontal Discharge
Output	7.5 lbs. vapor/hr. (3.4 kg/hr.); up to 6 ft. (2 m) horizontally.
Particle Size	4-7 microns
Motor	Sealed, ball-bearing type.
Sound Level	Approx. 48dB
Water Supply	1/4" push-in fitting (on left rear).
Operating Water Pressure	10-70 psi
Dimensions	18 -1/4" W x 7-1/4" D x 11-3/4" H
Weight	Net 38 lbs. (17.3 kg).



Laboratory Humidifier/vapouriser 220-240V 50/60 Hz

Code: [39-1510/01](#)

Product Group: [N/A](#)

- Used to humidify curing rooms for concrete and mortar specimens.
- Max room capacity 500 cubic meters
- Supplied complete with level regulator with anti-overflow that allows direct connection to the water network for continuous use.

Specification

Capacity	500 m3
Water source	Water mains
Use	Continuos when used with level regulator
Dimensions	350 mm x 350 mm x 420 mm
Voltage Supply	220-240 V 50/60 Hz
Weight	7 lbs (3.2kg)