



IF IT'S WORTH BUILDING, IT'S WORTH TESTING

This wishlist was generated on 23/11/2016, and contains the following Products:

83-4170/01

Muffle Furnace

38-0200/01

ELE Flame Photometer

38-1000

Blaine Air Permeability Apparatus

38-1200

Le Chatelier Flask

38-2695

Pocket Concrete Penetrometer

38-6000

Flow Table

38-2010

Vicat Frame

38-2015/01

Automatic Vicat Apparatus

38-3005

Le Chatelier Mould

38-3800/01

Autoclave

38-3420/01

Le Chatelier Water Bath

38-4600/01

Heat of Hydration Apparatus

38-4600/12

Beckman Thermometer and Reader Glass

38-7087

Air Entrainment Meter

39-6160/01

ADR-Auto V2.0 250/25 Cement Machine C/W Compression and Flexural Jigs and Platen Sets

38-7600

Spray Nozzle Apparatus

39-0035/01

Automatic/Manual 5 litre nominal capacity Mortar Mixer

39-1100

Three-gang Mould

39-1150/01

Jolting Table 220 - 240 V 50 Hz

39-0410

Three-gang Mould

39-1300/01

Humidity Cabinet to En196 320 Litre Capacity

39-7100/01

10kN Flexural/Tensile Testing Machine

39-6160

Flexural Jig Assembly



Muffle Furnace

Code: 83-4170/01

Product Group: Furnaces, Loss-on-Ignition,
Loss-on-Ignition

Standards

EN 196-2, EN 459-2, EN 13454-2, BS 1016-4, ISO 344, ISO 1171, ASTM D2361, ASTM D2795, ASTM D3714

Specification

External Dimensions (l x w x h)	545 x 385 x 400 mm
Work chamber dimensions (l x w x h)	300 x 200 x 120 mm
Internal volume	6.9 litres
Maximum temperature	1200 °C
Electrical supply	220 – 240 V AC, 50 - 60 Hz, 1 ph
Power supply	3500 W
Weight	130 kg



ELE Flame Photometer

Code: [38-0200/01](#)

Product Group: [ELE Flame Photometer](#)

Special Note: The Flame Photometer requires a source of moisture-free air at 6 litres/minute at a pressure of 1 kg/cm². It also requires a fuel source for the flame and a regulator (see accessories).

Standards

EN 196-21, ASTM C114, TEST 17

Further Information

****NOT AVAILABLE FOR SALE IN THE USA****

For 220-240 V AC, 50-60 Hz, 1 ph

Specification

Dimensions (l x w x h)	420 x 360 x 300 mm
Readout	LED three 12.5 mm digits
Sensitivity Na	3 to 100 ppm
K	3 to 100 ppm
Ca	5 to 100 ppm (optional filter)
Reproducibility	1% CV for 20 consecutive samples using 10 ppm, set to read 100
Recorder Output	Nominal 1.00 V for a reading of 100.0
Weight	8 kg



Blaine Air Permeability Apparatus

Code: 38-1000

Product Group: Blaine Fineness Apparatus,
Determination of Fineness Blaine Apparatus

Standards

EN 196-6, EN 459-2, EN 13286-44, BS 4359-2, ASTM C204, AASHTO T153

Specification


Cell	Stainless steel; 12.70 $\pm$ 0.10 mm i.d.
Disk	0.9 $\pm$ 0.1 mm thick with 30-40 one mm diam. holes.
Plunger	Stainless steel.
Manometer	U-tube glass with ground joint, stop cock and rubber bulb assembly.
Filter Paper	12.70 mm diam.
Fluid	Pure Mineral Oil.
Weight	Net 7 lbs. (3.2 kg).

Spares/Consumables



Blaine Air Permeability Cell

Code: [38-1000/15](#)



Filter Paper

Code: [38-0652](#)



Manometer U-tube

Code: [38-1000/10](#)



Le Chatelier Flask

Code: 38-1200

Product Group: Specific Gravity (relative density) of Hydration Cement, Le Chatelier Flask

For determining the density of hydraulic cement and lime, supplied complete with calibration certificate. Capacity 250ml. Graduated from 0 to 1ml and from 18 to 24ml graduations. Accurate to 0.05ml.

Standards

EN 196-6, ASTM C128, ASTM C188, E 694, AASHTO T133

Specification

Graduations

Zero mark represents 250 ml, the capacity of the large bulb; neck graduations from 0-1 ml in 0.1 ml divisions with two extra 0.1 ml graduations above the 1.0 and below the 0 marks; bulb portion of neck holds 17 ml; top portion of neck graduated from 18-24 ml in 0.1 ml divisions; 24 ml capacity.

Stopper

Ground glass.

Weight

Net 8 oz. (227 g).



Pocket Concrete Penetrometer

Code: 38-2695

Product Group: Concrete Mortar Penetrometer,
Concrete Mortar Penetrometer, Setting Time by
Penetration Resistance

Supplied complete with belt-loop, canvas carrying
case.

Standards

ASTM C187, ASTM C191, ASTM C780

Specification

Needle	Steel shaft; 1/20 sq. in. surface area.
Range	0 to 700 psi.
Scale	Direct-reading; indicator sleeve holds reading until released.
Dimensions	3/4" (19 mm) diam. x 7" (178 mm) long.
Carrying Case	Canvas, with belt-loop.
Weight	Net 8 oz. (227 g).



Flow Table

Code: [38-6000](#)

Product Group: [Flow and Workability of Mortar Lime](#)

Manufactured from cast bronze as specified in BS and ASTM C230. Complete with Tripod and Baseplate.

Standards

BS 4551-1, BS 3892-1, ASTM C230

Further Information

NOT AVAILABLE FOR SALE IN THE USA



Vicat Frame

Code: [38-2010](#)

Product Group: [Vicat Method](#)

Complete with consistency plunger, 10 mm diameter.
Requires one initial or final set needle to make up test weight to 300g.

Standards

EN 196-3, EN 13454-2, ASTM C187, ASTM C191

Further Information


NOT AVAILABLE FOR SALE IN THE USA

Spares/Consumables



Consistency Plunger

Code: [38-2010/10](#)



Automatic Vicat Apparatus

Code: [38-2015/01](#)

Product Group: [Automatic Vicat](#)

Complete with EN and ASTM Initial and Final needles, Consistency Plunger, Windows(R) software and RS232 cable, 1 x EN and ASTM Mould and Glass Plate. Suitable for continuous use in saturated humidity, at a controlled temperature of $20^{\circ}\text{C} \pm 1^{\circ}\text{C}$.

Standards

ASTM C187, ASTM C191

Further Information

****NOT AVAILABLE FOR SALE IN THE USA****

For 220 - 240 V AC, 50 - 60 Hz, 1 ph.

Spares/Consumables




ASTM Initial and Final Set Needle

Code: [38-2023](#)



Consistency Plunger

Code: [38-2015/16](#)



EN Initial and Final Set Needle

Code: 38-2021



Le Chatelier Mould

Code: 38-3005

Product Group: General Expansion of Dry Hydrated Lime by the Le Chatelier Method, Soundness of Cement Paste by the Le Chatelier Method, Soundness

Comprising a split cylinder fitted with two indicator stems. The mould is supplied complete with two glass plates and a weight 100 g $\pm$ 10 g. Three moulds required for each test.

Standards

BS 6463, EN 196-3, EN 459-2

Further Information

****NOT AVAILABLE FOR SALE IN THE USA****



Autoclave

Code: [38-3800/01](#)

Product Group: [Soundness of Portland Cement by the Autoclave Method](#)

The autoclave provides high pressure steam curing of the specimens and is supplied with a safety valve pressure gauge and controlled heater unit. The pressure vessel is independently certified and certificated. A specimen rack with capacity for 12 specimens included. The unit conforms to the requirements of ASTM C151.

220-240 V 50/60 Hz 1ph

Standards

ASTM C151

Further Information

****NOT AVAILABLE FOR SALE IN THE USA****

Spares/Consumables



Lid Sealing Gasket

Code: [38-3800/13](#)



Le Chatelier Water Bath

Code: [38-3420/01](#)

Product Group: [Soundness of Cement Paste by the Le Chatelier Method, Soundness](#)

Manufactured from corrosion resistant material, complete with a removable rack to hold up to twelve moulds and timer unit.

Further Information

****NOT AVAILABLE FOR SALE IN THE USA****



Heat of Hydration Apparatus

Code: [38-4600/01](#)

Product Group: [Heat of Hydration Cement](#)

For 220 - 240 V AC, 50 Hz, 1 ph.

Standards

BS 4550

Further Information

****NOT AVAILABLE FOR SALE IN THE USA****

Spares/Consumables



Beckman Thermometer and Reader Glass

Code: [38-4600/12](#)



Dewar Flask

Code: [38-4600/10](#)



Glass Paddle for Stirrer

Code: [38-4600/13](#)



Beckman Thermometer and Reader Glass

Code: [38-4600/12](#)

Product Group: [Heat of Hydration Cement](#)

Spare: range 6°C ± 0.01°C

Standards

BS 4550

Further Information

****NOT AVAILABLE FOR SALE IN THE USA****



Air Entrainment Meter

Code: [38-7087](#)

Product Group: [Air Content of Mortar, Masonry Cement and Lime by the Pressure Method](#)

0.75 litre capacity, complete with integral pump.

Standards

EN 413-2, BS 459-2

Further Information

****NOT AVAILABLE FOR SALE IN THE USA****



ADR-Auto V2.0 250/25 Cement Machine C/W Compression and Flexural Jigs and Platen Sets

Code: [39-6160/01](#)

Product Group: [ADR-Auto V2.0 250/25 Compression Machine, Activity Index](#)

- 250 kN maximum capacity
- Calibration accuracy to BS EN ISO 7500-1; ASTM E4
- Automatic loading cycle
- 25 kN low capacity frame supplied as standard
- Tests a wide variety of specimen sizes
- Tests mortar, lime, cement and Fly Ash
- Complete with compression/flexural jigs and platen sets
- Supplied with Windows(R) download software as standard

The ADR-Auto 250/25 Machine provides consistent automatic testing of a wide range of specimens. The machine comprises a standard ELE 250/25 kN load frame and ADR-Auto console and incorporates all the features included in the ADR-Auto series concrete testing machines.

As standard the machine is supplied with platens fitted to the load frame, compression jig with 40 mm and 50mm/2 inch square platen sets and flexural jig for testing 40.1 x 40 x 160 mm prisms.

The availability of the 25 kN low capacity load frame as standard extends the test capability of the machine for low strength compression or flexural testing. The automatic loading cycle is controlled by a closed loop microprocessor hydraulic system incorporated with the display in the ADR-Auto console attached to the load frame. A serial output port is built into the system, enabling test data to be stored in memory (up to 500 test results) for subsequent downloading to PC or suitable printer.

Standards

EN 196-1, EN 459-2, EN 1744, EN 1015-11, EN 13454-2, BS 3892-1, BS 4551-1, ASTM C109

Further Information

****NOT AVAILABLE FOR SALE IN THE USA****

For 220 - 240 V AC, 50 Hz, 1 ph.



Spray Nozzle Apparatus

Code: [38-7600](#)

Product Group: [Fineness of Fly Ash \(Wet Sieving\)](#)

Comprising a spray nozzle 17.5 mm ID with 17 holes as specified in EN451, a vacuum pressure gauge, 160 kPa graduated at 5 kPa divisions and fittings to attach the apparatus to a standard domestic water supply. Supplied without sieve.

Standards

BS 3892-1, EN 451-2, ASTM C430

Further Information

****NOT AVAILABLE FOR SALE IN THE USA****



Automatic/Manual 5 litre nominal capacity Mortar Mixer

Code: 39-0035/01

Product Group: Automatic/Manual 5 Litre Nominal Capacity Mortar Mixer

- New Microprocessor control
- New mix program selector
- Complies with latest EN Standards update
- Choice of automatic mixing cycles
- Sand and water dispenser supplied as standard

This mixer is designed to mix mortars and cement pastes to the requirements of the above Standards. The mixing paddle has a planetary motion and is driven by a motor with a microprocessor based speed and program controller. The mixer can be operated either in an automatic or manual mode. When the mixer is used in the manual mode, the two mixing speeds can be changed by means of a rocker switch, without switching off the motor. In the automatic mode any one of the preset mixing programs may be selected.

Standards

EN 196-1, EN 196-3, EN 413-2, EN 459-2, EN 1744-1, EN 13279-2, EN 1015-2, EN 13395-1, EN 13454-2, ISO 679, BS 3892-1, BS 3892-3, BS 6463-103, BS 4551-1

Further Information


****NOT AVAILABLE FOR SALE IN THE USA****

Complete with bowl and paddle, sand and Water dispensers. For 220 - 240 V AC, 50 - 60 Hz, 1 ph.

Specification


Dimensions (l x w x h)	530 x 350 x 580 mm
Speeds (rpm) Low, High	Paddle: 140 ± 5, 285 ± 10 Mixing Head: 62 ± 5, 125 ± 10
Rated Power	180 W
Bowl Capacity	5 litres approx.
Weight	54 kg

Spares/Consumables




Bowl

Code: [39-0031/11](#)



Paddle

Code: [39-0031/10](#)



Three-gang Mould

Code: [39-1100](#)

Product Group: [Moulding of Prisms](#)

For 40.1 x 40 x 160 mm mortar prisms. This mould is manufactured to a very high specification. Supplied with glass plate.

Standards

EN 196-1, EN 413-2, EN 459-2, EN 1015-10, EN 13454-2, ISO 679, BS 3892-1, BS 4551-1

Further Information

****NOT AVAILABLE FOR SALE IN THE USA****

Spares/Consumables



Glass Plate

Code: [39-1100/10](#)



Mortar Sand

Code: [39-1170](#)



Jolting Table 220 - 240 V 50 Hz

Code: [39-1150/01](#)

Product Group: [Jolting Table](#)

Supplied without moulds.

Standards

EN 196-1, EN 413-2, EN 459-2, EN 1744-1, EN 1015-10, EN 1015-11, EN 13454-2, ISO 679, BS 3892-1, BS 4551-1

Further Information

****NOT AVAILABLE FOR SALE IN THE USA****

Spares/Consumables



Mortar Sand

Code: [39-1170](#)



Scraper

Code: [39-1130](#)



Three-gang Mould

Code: 39-0410

Product Group: Moulding of 50 mm and 100 mm Specimens

For 50mm mortar cubes. Manufactured from cast iron with simple cube release mechanism.

Standards

BS 1881-131, ASTM C109

Further Information

NOT AVAILABLE FOR SALE IN THE USA



Humidity Cabinet to En196 320 Litre Capacity

Code: 39-1300/01

Product Group: Humidity Cabinet BS EN, Prism
Moulds and Inserts

For 220 - 240 V AC, 50 Hz, 1 ph.

Standards

EN 196-1, EN 459-2, BS 3892-1

Further Information

****NOT AVAILABLE FOR SALE IN THE USA****

10 Reinforced Shelves and Circular Chart Recorder

Specification

Capacity	320 litres
Dimensions External, Internal	660 x 635 x 1745 mm, 490 x 510 x 1275 mm
Temperature Range	+5.0°C to +60°C
Fluctuation (better than)	± 0.2°C
Variation (better than)	± 0.5°C
Recorder:	7 day,
Circular chart type,	0 – 50°C,
Temperature,	0 – 100% RH
Humidity	
Rated power	850 Watt
Number of shelves	10

Product Sheet

www.ele.com
+44 (0) 01525 249 200




Weight 200 kg

Spares/Consumables



Replacement Circular Charts

Code: [39-1300/10](#)



10kN Flexural/Tensile Testing Machine

Code: 39-7100/01

Product Group: 10 kN Flexural/ Tensile Testing Machine

This single lever machine is designed for flexural tests on 40.1 x 40 x 160 mm mortar prisms and tensile tests on mortar briquettes. The rate of applied loading for flexural testing is to EN196-1. Load is applied by a weight travelling along the beam at a constant rate, driven by a motor/gearbox. Readings are made by means of a cursor visible through a window in the moving weight. Failure of a specimen triggers a switch mechanism and brings the weight to a halt immediately. To prevent overloading, a sensor is incorporated in the weight and automatically stops the machine at its maximum capacity of 10 kN. Supplied complete with flexural and tensile jaws.

Standards

EN 196-1

Further Information

NOT AVAILABLE FOR SALE IN THE USA

For 220 - 240 V AC, 50 Hz, 1 ph.



Flexural Jig Assembly

Code: [39-6160](#)

Product Group: [Cement Testing Accessories](#)

Does come as standard with 39-6160/01 and 39-6160/06.

Jig Is Designed For The Flexural Testing Of 40 X 40 X 160 Mm When Fitted In To ELE Range Of Compression Machines.

Fitted With One Upper And Two Lower Roller Bearers.