



IF IT'S WORTH BUILDING, IT'S WORTH TESTING

Contents

www.ele.com
+44 (0) 01525 249 200



This wishlist was generated on 09/12/2016, and contains the following Products:

88-4100

Dial Indicator - 1.0" Range

24-9262

Swell Stand



Dial Indicator - 1.0" Range

Code: [88-4100](#)

Product Group: [Digital Tritest 50 Load Frame](#), [Hveem Stabilometer](#), [CBR-Test 50 Machine](#), [CBR Loading Press](#), [Hand-Operated](#), [Tripod Attachment](#), [Mechanical Dial Indicators](#), [Direct/Residual Shear Apparatus](#)

1.0" x 0.001" divisions.

Specification

Range	1.0"
Divisions	0.001"
Movement	Clockwise
Face Diameter	2-1/4"
Contact Point	Immediate response, up or down; tip movement magnified to indicator hand with minimal friction; 3/16" (5 mm) radius x 1/4" (6 mm) l.
Dials	With continuous graduations and revolution counters.
Measure Movement	Measure movement towards dial case; pointer at zero with stem extended.
Weight	Net 12 oz. (340 g).

Spares/Consumables



Electronic Digital Indicator, 0.600"/15 mm range

Code: [88-4210](#)



Swell Stand

Code: [24-9262](#)

Product Group: [Expansion \(swell\) Test Equipment, Tripod Attachment](#)

For mounting Swell Dial Gauge in position on CBR mould collar.

Standards

ASTM D1883, AASHTO T193

Further Information

Requires dial indicator; not included, order separately

Specification

Construction	Machined, one-piece cast aluminum.
Contact Head	Integral part of ssembly; holds dial indicator.
Construction	2" I. (50.8 mm) included.
Weight	Net 1 lb. (0.4 kg).

Spares/Consumables



Dial Indicator - 1.0" Range

Code: [88-4100](#)