



IF IT'S WORTH BUILDING, IT'S WORTH TESTING

Contents

www.ele.com
+44 (0) 01525 249 200



This wishlist was generated on 03/01/2017, and contains the following Products:

23-7462

Speedy Moisture Tester G2 Large 0-50% Moisture Range. Supplied Less Calcium Carbide



Speedy Moisture Tester G2 Large 0-50% Moisture Range. Supplied Less Calcium Carbide

Code: [23-7462](#)

Product Group: [Rapid method by Speedy Moisture Tester](#), [Rapid method by Speedy Moisture Tester](#)

Uses a technique based on the fact that water will react with calcium carbide to form a gas and that the quantity of gas formed is directly proportional to the water present. The gas pressure is indicated on a built-in pressure gauge. The pressure gauge calibrated in percentage of moisture. Has a moisture range of 0-50% with gauge divisions every 0.5%. Holds a sample size of 8 g. Includes an electronic balance of 200 g capacity x 0.1 g readability and is supplied in plastic carrying case.

Standards

ASTM D4944, AASHTO T217

Further Information

****NOT AVAILABLE FOR SALE IN THE USA****

Specification

Model	G2 Large
Moisture Range	0 to 50%
Gauge divisions	0.50%
Sample weight g	8
Weight complete kg	7.5

Accessories



Calcium Carbide Powder 500G.

Code: [23-7700](#)



Reagent for Speedy Moisture Testers. Pack of 12 Cans 500 G Each. (Calcium Carbide)

Code: [23-7702](#)



Speedy Calibration Unit Self Contained Unit.

Code: [23-7600](#)

Alternatives



Speedy Moisture Tester D2 Large 0-20% Moisture Range. Supplied Less Calcium Carbide

Code: [23-7452](#)



Speedy Moisture Tester D2 Small 0-20% Moisture Range. Supplied Less Calcium Carbide

Code: [23-7502](#)