



IF IT'S WORTH BUILDING, IT'S WORTH TESTING

Contents

www.ele.com
+44 (0) 01525 249 200



This wishlist was generated on 27/02/2017, and contains the following Products:

34-0810

Set of Needle Points 1 1/2 1/4 1/10 1/20 1/40 Inch Sq.

29-3925

Proctor Penetrometer Spring Type with Adaptor Stem.

82-2820

Syringe with Rubber Bulb.

38-2695

Pocket Concrete Penetrometer



Set of Needle Points 1 1/2 1/4 1/10 1/20 1/40 Inch Sq.

Code: 34-0810

Product Group: [Setting Time by Penetration Resistance](#)

Stainless steel, 1, 1/2, 1/4, 1/10, 1/20 and 1/40 in² area (645, 323, 161, 65, 32 and 16 mm²) with stainless steel adaptor for the smaller needles.

Further Information

NOT AVAILABLE FOR SALE IN THE USA



Proctor Penetrometer Spring Type with Adaptor Stem.

Code: [29-3925](#)

Product Group: [Proctor Penetrometer, Setting Time by Penetration Resistance](#)

Supplied without needle points

Standards

ASTM D1558

Further Information

****NOT AVAILABLE FOR SALE IN THE USA****

Accessories




Case for Proctor Penetrometer.

Code: [29-3933](#)



Set of Needle Points 1 1/2 1/4 1/10 1/20 1/40 Inch Sq.

Code: [34-0810](#)



Syringe with Rubber Bulb.

Code: [82-2820](#)





Syringe with Rubber Bulb.

Code: [82-2820](#)

Product Group: [Setting Time by Penetration Resistance, Syringe and Stirring Rod](#)

Further Information

****Not available for sale in the USA****



Pocket Concrete Penetrometer

Code: 38-2695

Product Group: Concrete Mortar Penetrometer,
Concrete Mortar Penetrometer, Setting Time by
Penetration Resistance

Supplied complete with belt-loop, canvas carrying
case.

Standards

ASTM C187, ASTM C191, ASTM C780

Specification

Needle	Steel shaft; 1/20 sq. in. surface area.
Range	0 to 700 psi.
Scale	Direct-reading; indicator sleeve holds reading until released.
Dimensions	3/4" (19 mm) diam. x 7" (178 mm) long.
Carrying Case	Canvas, with belt-loop.
Weight	Net 8 oz. (227 g).