



IF IT'S WORTH BUILDING, IT'S WORTH TESTING

This wishlist was generated on 01/03/2017, and contains the following Products:

45-9315/10

Attachment Required for 6000 g

45-9315/01

Rice Test Vibrator

81-0518

Timer Clock

45-9305/01

Vacuum Pyknometer Apparatus

45-9300

Vacuum Pyknometer, 6000 g

45-6600/01

AutoComp 100-A

42-1005

Wire Basket Brass with Handle Nominal 6000Cm³ Capacity with 1.7mm Wire Mesh.

42-1000/01

Buoyancy Balance 6Kg X 0.1G. Supplied with Support Frame Water Tank & Suspension Hook.

82-5442

Digital Thermometer

46-5340/C

Penetration Needle

46-5360/10

Penetration Needle

46-5860

Penetration Tin

46-5861

Penetration Tin

46-5800

Transfer Dish

46-5500/01

Constant Temperature Bath 21 - 56°C

45-6490/01

Water Bath

45-6463

Steel Block

45-6462

Paper Discs



Attachment Required for 6000 g

Code: [45-9315/10](#)

Product Group: [Rice Test Vibrator](#), [Rice Test Vibrator](#),
[Specific Gravity \(Rice\) Test with 6,000 gram Vacuum](#)
[Pyknometer](#)

Accessory

Standards

EN 12697-5



Rice Test Vibrator

Code: [45-9315/01](#)

Product Group: [Rice Test Vibrator](#), [Rice Test Vibrator](#)

The Rice Test Vibrator is used with the 45-9300 6000 g Vacuum Pyknometer. Adjustable clamps hold the pyknometer securely to the base during vibration.

Standards

EN 12697-5, ASTM D2041, AASHTO T209

Further Information

For 220 - 240 V AC, 50 Hz, 1ph.

Specification

| | |
|------------|--|
| Dimensions | 495 x 30 mm (height x base diameter) |
| Motor | 1/20 hp, 1.6 amp |
| Weight | 5.5 kg |
| Motor | 1/20 h.p.; 3000 vpm; 1.6 amp. |
| Dimensions | 19-1/2" (495 mm) h.; 12 " (30 mm) base diameter. |
| Weight | Net 14.3 lbs. (6.5 kg). |

Accessories



Attachment Required for 6000 g

Code: [45-9315/10](#)

Alternatives



Rice Test Vibrator 115vAC, 50/60 Hz

Code: [45-9315/02](#)



Timer Clock

Code: [81-0518](#)

Product Group: [Rice Test Vibrator](#), [Watches and Clocks](#)

Accessory

Standards

EN 12697-5

Further Information

****NOT AVAILABLE FOR SALE IN THE USA****



Vacuum Pyknometer Apparatus

Code: 45-9305/01

Product Group: Vacuum Pyknometer

- Large capacity design minimises segregation effects
- Lightweight polycarbonate construction
- Transparent top for visual observations

The Vacuum Pyknometer is a large capacity unit used in the Rice Test for determining the maximum specific gravity of bituminous paving mixtures.

The Pyknometer has a total volume of approximately 10 litres and will conveniently accept samples of 6000 grams to minimise segregation effects. The unit is constructed of lightweight polycarbonate, with the upper half being transparent for visual observation of the effects of the vacuum.

The Vacuum Pyknometer Apparatus consists of a 6000 g pyknometer, vacuum pump with control valves/gauges, water trap and connection tubing.

Standards

EN 12697-5

Further Information

****NOT AVAILABLE FOR SALE IN THE USA****

Supplied complete with 6000 g pyknometer, vacuum pump with control valves/gauges, water trap and connection tubing. For 220 - 240 V AC, 50 Hz, 1ph.

Specification

| | |
|-------------|---|
| Dimensions | 273 x 406 mm (outside diameter x height) |
| Capacity | Approx. 10 litres, 6000 g sample weight |
| Connections | Water inlet valve; quick disconnect for vacuum gauge and hose |
| Weight | 3.6 kg |

Alternatives

Product Sheet

www.ele.com
+44 (0) 01525 249 200



Vacuum Pyknometer, 6000 g

Code: [45-9300](#)



Vacuum Pyknometer, 6000 g

Code: 45-9300

Product Group: Vacuum Pyknometer, Vacuum Pyknometer (6,000 Gram), Specific Gravity (Rice) Test with 6,000 gram Vacuum Pyknometer

The Vacuum Pyknometer is a large capacity unit used in the rice test for determining the maximum specific gravity of bituminous paving mixtures. The Pyknometer has a transparent top for observation and a lightweight polycarbonate construction.

The Pyknometer has a total volume of 10 litres and will conveniently accept samples of 6000 grams to minimise segregation effects.

Standards

EN 12697-5, ASTM D2041, AASHTO T209, AASHTO T283

Specification

| | |
|--------------|--|
| Capacity | Approximately 10 liters; 6,000 g (13 .2 lbs.) sample weight. |
| Construction | Lightweight polycarbonate with transparent upper half. |
| Gauge | 2" (50.8 mm) diam., 30" x 0.5" Hg. |
| Aspirator | Plastic; 3/8" pipe thread (included). |
| Connections | Water inlet valve; quick disconnect for vacuum gauge and hose. |
| Dimensions | 10-3/4" (273 mm) o.d. x 16" (406 mm) h. |
| Weight | Net 8 lbs. (3.6 kg). |

Accessories



1/4" O.D Plastic Tubing

Code: 45-9301/14



Drierite Desiccant

Code: [45-9315/14](#)



Filtering Kit

Code: [45-9301](#)

Alternatives



Vacuum Pyknometer (2,000 gram)

Code: [45-9310](#)



Vacuum Pyknometer Apparatus

Code: [45-9305/01](#)



AutoComp 100-A

Code: 45-6600/01

Product Group: Automatic Compaction

- Fully automatic, simple to operate
- Built-in safety features
- Uniform compaction
- Automatic blow counter

This ruggedly constructed automatic compactor provides a consistent and even degree of compaction. The unit incorporates a compaction pedestal comprising a laminated hardwood block secured to a concrete base by a 300 mm square x 25 mm thick steel plate. The mechanism lifts the 4535 g hammer and automatically releases it at the specified height of 457 mm. The conveniently positioned control fascia panel comprises of a mains light, start and stop buttons and a direct-reading counter used to set the required number of blows.

During operation the AutoComp 100-A automatically counts down to zero. Dual rammer pick-ups have been incorporated, reducing stress on the machine's internal mechanism.

Particular attention has been paid to operator safety by the inclusion of various in-built safety features.

Standards

EN 12697-10, EN 12697-30, BS 598

Further Information

****NOT AVAILABLE FOR SALE IN THE USA****

Specification

| | |
|--------------------------|---------------------|
| Dimensions (l x w x h) | 535 x 535 x 1880 mm |
| Compaction foot diameter | 98.52 mm |

Product Sheet

www.ele.com
+44 (0) 01525 249 200



| | |
|----------------|--------|
| Sliding weight | 4535 g |
| Height of drop | 457 mm |
| Weight | 278 kg |

Accessories



Digital Hotplate

Code: [78-3104/01](#)



Paper Discs

Code: [45-6462](#)



Sample Tray - 306 x 306 x 38 mm

Code: [81-4020](#)

Alternatives



Compaction Mould

Code: [45-6310](#)



Wire Basket Brass with Handle Nominal 6000Cm³ Capacity with 1.7mm Wire Mesh.

Code: 42-1005

Product Group: Particle Density (specific gravity) and
Water Absorption for Coarse Aggregates

For BS 812 Relative Density. 200 mm diameter x 190
mm deep, 1.70 mm wire mesh.

Standards

EN 1097-6, EN 12697-6, BS 812, ASTM C127, AASHTO T85

Further Information

NOT AVAILABLE FOR SALE IN THE USA



Buoyancy Balance 6Kg X 0.1G. Supplied with Support Frame Water Tank & Suspension Hook.

Code: [42-1000/01](#)

Product Group: [Particle Density \(specific gravity\) and Water Absorption for Coarse Aggregates](#)

The buoyancy balance system developed by ELE consists of a rigid support frame, incorporating a water tank mounted on a platform. A mechanical lifting device is used to raise the water tank through the frame height immersing the specimen suspended below the balance. The balance supplied may also be used as a standard weighing device, thus providing a versatile and comprehensive weighing system in the laboratory. 6000 g x 0.1 g supplied with frame, water tank and suspension hook.

Standards

EN 1097-6, EN 12697-6, BS 812, ASTM C127, AASHTO T85

Further Information

****NOT AVAILABLE FOR SALE IN THE USA****

For 220 - 240 V AC, 50 - 60 Hz, 1 ph.

Accessories



200 mm Diameter Lid

Code: [79-0010](#)



200 mm Diameter Receiver

Code: [79-0020](#)



200mm Dia BS Sieve 31.5mm Perforated Plate.

Code: [79-1630](#)



200mm Dia BS Sieve 4.00mm Stainless Steel Mesh.

Code: [79-0310](#)



200mm Dia BS Sieve 63 Mic Stainless Steel Mesh.

Code: [79-0070](#)



200mm Dia BS Sieve 63.0mm Perforated Plate.

Code: [79-1670](#)



Digital Pocket Thermometer

Code: [82-5420](#)



Sample Container - Tinned Steel 10 litres

Code: [81-3060](#)



Sample Tray - 406 x 406 x 50 mm

Code: [81-4030](#)



Wire Basket Brass with Handle Nominal 6000Cm³ Capacity with 1.7mm Wire Mesh.

Code: [42-1005](#)



Digital Thermometer

Code: [82-5442](#)

Product Group: [Hand-held Digital Thermometers](#)

Range -75 - 1200°C

Further Information

****NOT AVAILABLE FOR SALE IN THE USA****

Specification

| | |
|---------------------------|---|
| Range | -75 to +1200°C or -30 to +199.9°C or -75 to +1999°F |
| Resolution and accuracy | 1°C (-75 to +1200°C), 0.2% ± 0.1°C, 0.1°C (-30 to +199.9°C) 0.2% ± 1.0°C, 1°F (-75 to +1999°F), 0.2% ± 2.0°F |
| Cold junction (automatic) | 0 to 45°C |
| Weight | 500 g |



Penetration Needle

Code: [46-5340/C](#)

Product Group: [Penetration Test](#)

Hardened steel, supplied with an UKAS verification certificate. For testing to BS 2000-49 and ASTM D5. (Pack contains 1 needle only).

Standards

BS 2000-49, EN 1426, EN 13179-2, ASTM D5, AASHTO T49, IP 49

Further Information

****NOT AVAILABLE FOR SALE IN THE USA****



Penetration Needle

Code: [46-5360/10](#)

Product Group: [Penetration Test](#)

Hardened steel.

Standards

BS 2000-49, EN 1426, EN 13179-2, ASTM D5, AASHTO T49, IP 49

Further Information

****NOT AVAILABLE FOR SALE IN THE USA****



Penetration Tin

Code: [46-5860](#)

Product Group: [Penetration Test](#)

For penetrations between 200 and 350,
approximately 70 mm diameter x 45 mm deep.

Standards

BS 2000-49, EN 1426, EN 13179-2, ASTM D5, AASHTO T49, IP 49

Further Information

****NOT AVAILABLE FOR SALE IN THE USA****



Penetration Tin

Code: [46-5861](#)

Product Group: [Penetration Test](#)

For penetrations below 200, approximately 55 mm diameter x 35 mm deep.

Standards

BS 2000-49, EN 1426, EN 13179-2, ASTM D5, AASHTO T49, IP 49

Further Information

****NOT AVAILABLE FOR SALE IN THE USA****



Transfer Dish

Code: [46-5800](#)

Product Group: [Bitumen Penetration Test](#), [Asphalt Penetrometer](#), [Penetration Test](#)

For use with ELE Penetrometer 46-5295.

Standards

BS 2000-49, EN 1426, EN 13179-2, ASTM D5, AASHTO T49, IP 49



Constant Temperature Bath 21 - 56°C

Code: [46-5500/01](#)

Product Group: [Penetration Test](#)

A bench mounting bath specially designed for the conditioning of bitumen samples prior to penetration tests. Incorporating a highly accurate thermostat, the bath maintains a temperature between 21 and 56°C \pm 0.1°C (at ambient). An integral cover and deep tray for penetration testing are supplied as standard.

Further Information

****Not available for sale in the USA****



Water Bath

Code: [45-6490/01](#)

Product Group: [N/A](#)

60 litre water bath with stainless steel tank and outer case suitable for marshall test specimens and fitted with a digital thermostat and electric circulation unit. Complete with bath cover and perforated specimen tray.

Inner dimensions: 700 x 550 x 165 mm.

Outer dimensions : 900 x 640 x 340 mm.

Standards

EN 12697-30

Further Information

****NOT AVAILABLE FOR SALE IN THE USA****

Temperature range ambient to 95°C \pm 1°C. For 220 - 240 V AC, 50 - 60 Hz 1ph.

Accessories

Steel Block

Code: [45-6463](#)



Alternatives

Steel Block

Code: [45-6463](#)







Steel Block

Code: [45-6463](#)

Product Group: [Accessories for manual and automatic compaction](#)

100 mm diameter x 50 mm height. For heating the compaction hammer foot.

Standards

EN 12697-30

Further Information

****NOT AVAILABLE FOR SALE IN THE USA****

Accessories



Water Bath

Code: [45-6490/01](#)

Spares/Consumables



Baseplate

Code: [45-6310/11](#)



Compaction Mould Body

Code: [45-6310/10](#)

Alternatives



Water Bath

Code: [45-6490/01](#)



Paper Discs

Code: [45-6462](#)

Product Group: [Filter Paper Discs, Accessories for manual and automatic compaction](#)

Non-absorbent, 99 mm diameter, pack of 100.

Standards

EN 12697-30

Specification

Weight

Net 2.9 oz. (82 g).