



IF IT'S WORTH BUILDING, IT'S WORTH TESTING

Contents

www.ele.com
+44 (0) 01525 249 200



This wishlist was generated on 03/04/2017, and contains the following Products:

88-4100

Dial Indicator - 1.0" Range

45-7580

Expansion Pressure Device

45-7520

Hveem Diaphragm Replacement Tool

45-7580/14

Lever Type Calibration Device



Dial Indicator - 1.0" Range

Code: [88-4100](#)

Product Group: [Digital Tritest 50 Load Frame](#), [Hveem Stabilometer](#), [CBR-Test 50 Machine](#), [CBR Loading Press](#), [Hand-Operated](#), [Tripod Attachment](#), [Mechanical Dial Indicators](#), [Direct/Residual Shear Apparatus](#)

1.0" x 0.001" divisions.

Specification

Range	1.0"
Divisions	0.001"
Movement	Clockwise
Face Diameter	2-1/4"
Contact Point	Immediate response, up or down; tip movement magnified to indicator hand with minimal friction; 3/16" (5 mm) radius x 1/4" (6 mm) l.
Dials	With continuous graduations and revolution counters.
Measure Movement	Measure movement towards dial case; pointer at zero with stem extended.
Weight	Net 12 oz. (340 g).

Accessories



1" Extension Point

Code: [88-4154](#)



1/2" Extension Point

Code: [88-4152](#)



1/4" Extension Point

Code: [88-4150](#)



3" Extension Point

Code: [88-4156](#)



Dial Indicator Holder

Code: [88-4194](#)



Mechanical Dial Indicator - 25 mm Range Clockwise Movement

Code: [88-4110](#)



Unconfined Compression Assembly Only

Code: [25-3999](#)

Spares/Consumables



Electronic Digital Indicator, 0.600\"/>

Code: [88-4210](#)

Alternatives



Electronic Digital Indicator, 0.600\"/>

Code: [88-4210](#)



Expansion Pressure Device

Code: 45-7580

Product Group: Expansion Pressure Device


Standards

ASTM D2844, AASHTO T190, CA 301

Specification

Frame Stand	Includes adjustable turntable, height gauge and head
Height Gauge	Scribed; sliding.
Head	Adjustable, drilled; includes deflection bar and dial indicator adjustment screw.
Plate	Perforated brass; circular, with perpendicular stem.
Dial Indicator Holder	Triangular, drilled; with dial indicator support and 3 feet.
Dial Indicator	0.2" (7.6 mm) range x 0.0001" (0.002 mm) divisions.
Mold	0.2" (7.6 mm) range x 0.0001" (0.002 mm) divisions.
Calibrating Device	Lever-type.
Overall Dimensions	12" w. x 12" d. x 16" h. (305 x 305 x 406 mm).
Weight	Net 35 lbs. (15.9 kg).

Accessories



R-Value Rough Hveem Test Mold

Code: 45-7505/10

Spares/Consumables



Dial Indicator and Holder Assembly

Code: [45-7580/12](#)



Expansion Pressure Frame

Code: [45-7580/10](#)



Lever Type Calibration Device

Code: [45-7580/14](#)



Hveem Diaphragm Replacement Tool

Code: [45-7520](#)

Product Group: [Hveem Stabilometer](#)

Used to replace diaphragms in Hveem stabilometer.
Pre-stressing Type.



Lever Type Calibration Device

Code: [45-7580/14](#)

Product Group: [Expansion Pressure Device](#)