



IF IT'S WORTH BUILDING, IT'S WORTH TESTING

Contents

www.ele.com
+44 (0) 01525 249 200



This wishlist was generated on 10/04/2017, and contains the following Products:

25-0618

Compaction Permeameter 4"

25-0619

Compaction Permeameter 6"



Compaction Permeameter 4"

Code: [25-0618](#)

Product Group: [Compaction Permeameters](#)

Standards

ASTM D5856

Specification

Mould	Machined seamless steel tubing; plated.
Capacity	1/30 cu. ft.; 4" i.d. x 4.584" h. (101.6 x 116.4 mm).
Collar	2" h. (50.8 mm); machined seamless steel tubing; fits either end of mold; plated.
Top	Cast aluminum; with overflow valve assembly and water connection.
Base	Cast aluminum; with inlet/outlet fitting.
Porous Stone	4" diam. x 1/2" thick (101.6 x 12.7 mm). 50-70 permeability rating; 225 micron, average pore size.
Weights	Net 12 lbs. (5.4 kg).


Accessories



Constant and Falling Head Accessory Kit

Code: [25-0620](#)

Spares/Consumables



Porous Stone for 25-0618

Code: [T-319](#)

Alternatives



Compaction Permeameter 6"

Code: [25-0619](#)



Compaction Permeameter 6"

Code: [25-0619](#)

Product Group: [Compaction Permeameters](#)

Standards

ASTM D5856

Specification

Mould	Machined seamless steel tubing; plated.
Capacity	0.1145 cu. ft.; 6" i.d. x 7" h. (152 .4 x 177.8 mm).
Collar	2" h. (50.8 mm); machined seamless steel tubing; fits either end of mold; plated.
Top	Cast aluminum; with overflow valve assembly and water connection.
Base	Cast aluminum; with inlet/outlet fitting.
Porous Stone	5-15 /16" diam. x 1/2" thick (15 0.8 x 12 .7 mm). 50-70 permeability rating; 225 micron, average pore size.
Weights	Net 24 lbs. (10.9 kg).

Accessories



Constant and Falling Head Accessory Kit

Code: [25-0620](#)

Spares/Consumables



Porous Stone for 25-0619

Code: [T-324](#)

Alternatives



Compaction Permeameter 4"

Code: [25-0618](#)