



IF IT'S WORTH BUILDING, IT'S WORTH TESTING

This wishlist was generated on 23/04/2017, and contains the following Products:

---

25-0580

**Constant Head Permeability Cell 75mm Diameter Specimen.**

---

25-0591

**Manometer Tubes & Stand.**

---

25-0593

**Constant Level Tank.**

---

81-0200

**Aluminium Scoop Small**

---

81-0518

**Timer Clock**

---

82-7720/01

**Vacuum Pump**

---

81-0375

**Rubber Tubing**

---

25-0605

**Falling Head Permeability Cell.**

---

25-0609

**Standpipe Panel.**

---

25-0611

**De-Airing Tank.**

---

25-0613

**Soaking Tank.**

---



## Constant Head Permeability Cell 75mm Diameter Specimen.

Code: [25-0580](#)

Product Group: [Constant Head Apparatus](#)

75 mm Diameter

## Standards

BS 1377-5

## Specification

Nominal Cell inside diameter	75 mm
Cell wall	Transparent plastic
Take-off points	3
End plates	Anodised aluminium
Weight kg	2.6



## Manometer Tubes & Stand.

Code: [25-0591](#)

Product Group: [Constant Head Apparatus](#)

Comprising three glass tubes of constant bore, metre scale and connecting tubing for cell pressure take-off points, all mounted on a free-standing panel. Comprising three glass tubes of constant bore, metre scale and connecting tubing for cell pressure take-off points, all mounted on a free-standing panel.

## Standards

BS 1377-5



## Constant Level Tank.

Code: [25-0593](#)

Product Group: [Constant Head Apparatus](#)

Manufactured from transparent plastic with attachment for wall mounting. The inlet, outlet and overflow pipes are fitted to the base of the tank and can be adjusted for height within the tank. Supplied complete with connecting tubing.

## Standards

BS 1377-5



## Aluminium Scoop Small

Code: [81-0200](#)

Product Group: [Scoops and Shovels](#)

82 x 127 x 50 mm, cast aluminium with handle

## Further Information

**\*\*NOT AVAILABLE FOR SALE IN THE USA\*\***



## Timer Clock

Code: [81-0518](#)

Product Group: [Rice Test Vibrator](#), [Watches and Clocks](#)

Accessory

## Standards

EN 12697-5

## Further Information

**\*\*NOT AVAILABLE FOR SALE IN THE USA\*\***



## Vacuum Pump

Code: [82-7720/01](#)

Product Group: [Vacuum Pumps](#)

## Further Information

**\*\*NOT AVAILABLE FOR SALE IN THE USA\*\***

## Specification

Type	Single stage
Pump	Oil filled rotary
Ultimate vacuum	Better than 0.1 mbar
Displacement	42 litres per minute (2.4 m <sup>3</sup> /hour)
Electrical supply	220 – 240 V AC, 50 - 60 Hz, 1 ph
Weight	12.7 kg



## Rubber Tubing

Code: [81-0375](#)

Product Group: [Vacuum Pumps, Rubber Tubing](#)

## Further Information

**\*\*NOT AVAILABLE FOR SALE IN THE USA\*\***

## Specification

Bore	6.5 mm
Wall thickness	5.0 mm
Sold by	Metre



## Falling Head Permeability Cell.

Code: [25-0605](#)

Product Group: [Falling Head Apparatus](#)

## Specification

Cell	Plated seamless tube 100 mm diameter x 130 mm height
Base	Porous plate with three tie rods
Top plate	Machined to accept smaller tubes
Weight kg	3.4



## Standpipe Panel.

Code: [25-0609](#)

Product Group: [Compaction Permeameter](#)

Complete with three glass tubes of 1.5, 3 and 5 mm diameter bore, approximately 1.4 metres long. Supplied with metre scale and thick walled flexible tubing. The glass tubes are fitted to a panel for wall mounting and connected to a 3-way outlet valve. Complete with three glass tubes of 1.5, 3 and 5 mm diameter bore, approximately 1.4 metres long. Supplied with metre scale and thick walled flexible tubing. The glass tubes are fitted to a panel for wall mounting and connected to a 3-way outlet valve.



## De-Airing Tank.

Code: [25-0611](#)

Product Group: [Compaction Permeameter](#)

Manufactured from transparent plastic with de-airing jet inlet and a flow outlet connection with flexible tubing. The tank is manufactured to withstand a reduced pressure and is suitable for direct wall mounting.



## Soaking Tank.

Code: [25-0613](#)

Product Group: [Compaction Permeameter](#)

With fixed overflow. Used for containing permeability cell during test.