



IF IT'S WORTH BUILDING, IT'S WORTH TESTING

Contents

www.ele.com
+44 (0) 01525 249 200



This wishlist was generated on 03/05/2017, and contains the following Products:

88-0156/02

Forced Convected Oven - 6.9 cu. ft. capacity - 120V

88-0161/01

Forced Convected Oven - 18 cu. ft. capacity - 240V

24-9220

Filter Papers 150mm Dia Equivalent to Whatman No 1. Box of 100.

88-4434

Digital Pocket Thermometer

37-6130

100kN Flexural (Beams) Frame. Supplied Without Specimen Bearers and Fitting Kit.

47-0202

Digital Asphalt Thermometer

88-4100

Dial Indicator - 1.0" Range

24-4938

Stock Solution 1 gallon



Forced Convected Oven - 6.9 cu. ft. capacity - 120V

Code: [88-0156/02](#)

Product Group: [Forced Convected Ovens](#)

120vAC, 60 Hz, 1Ø, 21.6 amps.

Specification

Chamber Size	30" w. x 18" d. x 22" h. (76 x 46 x 56 cm); 6.9 ft ³ (196 liters).
Overall Size	36" w. x 24.5" d. x 36.5" h. (92 x 63 x 93 cm).
Operating Range	35 °C - 204 °C (95 °F - 400 °F).
Weights	245 lbs. (112 kg).

Alternatives



Bench Oven - Digital PID Controller - 7 cu. ft. capacity - 115V

Code: [88-0140/02](#)



Bench Oven - Digital PID Controller - 7 cu. ft. capacity - 230V

Code: [88-0140/01](#)



Bench Oven - Hydraulic Thermostat - 7 cu. ft. capacity - 115vAC

Code: [88-0130/02](#)



Bench Oven - Hydraulic Thermostat - 7 cu. ft. capacity - 230vAC

Code: [88-0130/01](#)



Double Wall Laboratory - 3.0 cu. Ft. Capacity - 115vAC

Code: [88-0220/02](#)



Double Wall Laboratory - 3.0 cu. Ft. Capacity - 230vAC

Code: [88-0220/01](#)



Double Wall Laboratory Oven - 0.7 cu. Ft. Capacity - 115vAC

Code: [88-0200/02](#)



Double Wall Laboratory Oven - 2.0 cu. Ft. Capacity - 115vAC

Code: [88-0210/02](#)



Forced Convected Oven - 18 cu. ft. capacity - 240V

Code: [88-0161/01](#)



Forced Convected Oven - 27 cu. ft. capacity - 240v

Code: [88-0166/01](#)



Forced Convected Oven - 18 cu. ft. capacity - 240V

Code: [88-0161/01](#)

Product Group: [Forced Convected Ovens](#)

240vAC, 50/60 Hz, 1Ø, 16.4 amps.

Alternatives



Bench Oven - Digital PID Controller - 7 cu. ft. capacity - 115V

Code: [88-0140/02](#)



Bench Oven - Digital PID Controller - 7 cu. ft. capacity - 230V

Code: [88-0140/01](#)



Bench Oven - Hydraulic Thermostat - 7 cu. ft. capacity - 115vAC

Code: [88-0130/02](#)



Bench Oven - Hydraulic Thermostat - 7 cu. ft. capacity - 230vAC

Code: [88-0130/01](#)



Double Wall Laboratory - 3.0 cu. Ft. Capacity - 115vAC

Code: [88-0220/02](#)



Double Wall Laboratory - 3.0 cu. Ft. Capacity - 230vAC

Code: [88-0220/01](#)



Double Wall Laboratory Oven - 0.7 cu. Ft. Capacity - 115vAC

Code: [88-0200/02](#)



Double Wall Laboratory Oven - 2.0 cu. Ft. Capacity - 115vAC

Code: [88-0210/02](#)



Forced Convected Oven - 27 cu. ft. capacity - 240v

Code: [88-0166/01](#)

Product Sheet

www.ele.com
+44 (0) 01525 249 200



Forced Convection Oven - 6.9 cu. ft. capacity - 120V

Code: [88-0156/02](#)



Filter Papers 150mm Dia Equivalent to Whatman No 1. Box of 100.

Code: [24-9220](#)

Product Group: [BS EN CBR mould accessories](#)

Box of 100.

Standards

EN 13286-4, BS 1377-4, BS 1924-2

Accessories



BS Solid Base or Top Plate

Code: [24-9204](#)

Alternatives



BS Solid Base or Top Plate

Code: [24-9204](#)



Digital Pocket Thermometer

Code: [88-4434](#)

Product Group: [Digital Pocket Thermometers](#)

Fahrenheit scale and Celsius scale.

Standards

ASTM D854

Specification

Range	-58Â° to +392Â°F or -50Â° to 200Â°C.
Resolution	0.1Â°F or 0. 1Â°C.
Weight	5 oz. (142 g).

Alternatives



Digital Thermometer

Code: [88-4420](#)



Pistol-Grip Infrared Thermometer

Code: [88-4400](#)



100kN Flexural (Beams) Frame. Supplied Without Specimen Bearers and Fitting Kit.

Code: [37-6130](#)

Product Group: [Flexural Testing for Beams](#)

- Open sided for ease of specimen loading
- Meets EN 12390-5, 1521, 13161, 772-6 and ASTM C78 for standard section beams
- Optional ball seating assembly

This rigidly constructed, open sided frame is suitable for testing 100 mm and 150 mm square-section beams. The frame supports a hydraulic ram and upper sub-platen assembly incorporating a spherical seating. The upper and lower sub-platens will accept various specimen loading bearers, which are supplied separately.

Standards

BS 1881-118, EN 12390-5

Further Information

Not available for sale in the USA

Accessories



100 kN Flexural Fitting Kit ADR Auto for 110 - 120 V AC, 60 Hz, 1 ph

Code: [37-6135/02](#)



100 kN Flexural Fitting Kit ADR Auto for 220 - 240 V AC, 50 Hz, 1 ph

Code: [37-6135/01](#)



100 kN Flexural Fitting Kit ADR Auto for 220 - 240 V AC, 60 Hz, 1 ph

Code: [37-6135/06](#)



100kN Flexural Fitting Kit (ADR) Used for Connecting Flexural Frames to ADR Compression Machines.

Code: [37-6138](#)



ASTM C78 Specimen Bearer Assembly Case-Hardened 38mm Dia X 160mm Length.

Code: [37-6132](#)



Ball Seating Assembly 150mm Dia Platens.

Code: [37-6133](#)



BS 1881 Specimen Bearer Assembly 38mm Dia X 160mm Length.

Code: [37-6131](#)



Standard Distance Piece - 100 mm Depth

Code: [37-5100](#)



Standard Distance Piece - 20 mm Depth

Code: [37-4980](#)



Standard Distance Piece - 50 mm Depth

Code: [37-5000](#)



Standard Distance Piece - 60 mm Depth

Code: [37-5020](#)



Standard Distance Piece - 80 mm Depth

Code: [37-5050](#)

Alternatives



Accu-Tek Touch 250 Automatic Compression Machine 110V/60Hz

Code: [36-1690/02](#)



Digital Asphalt Thermometer

Code: [47-0202](#)

Product Group: [Digital Asphalt Thermometer](#)

Comprises a hand-held digital thermometer with an operating range of -99 to +1372 °C with a switchable resolution between 0.1 and 1.0 °C. Operates on a 9V battery and utilises K-type thermocouple sensors.

Standards

BS 2000-49, EN 1426, EN 13179-2, ASTM D5, AASHTO T49, IP 49

Further Information

****NOT AVAILABLE FOR SALE IN THE USA****

Specification

Range	-50 to 1000°C
Resolution	Switchable 0.1 or 1.0°C
Weight	300 g

Accessories



250 Asphalt Probe

Code: [47-0202/10](#)



Breaking Head (Marshall)

Code: [45-6850](#)



Vibrating Hammer

Code: [47-0455/01](#)

Alternatives



Marshall Test 50

Code: [45-6810/01](#)



Marshall Test 50

Code: [45-6810/06](#)



Dial Indicator - 1.0" Range

Code: [88-4100](#)

Product Group: [Digital Tritest 50 Load Frame](#), [Hveem Stabilometer](#), [CBR-Test 50 Machine](#), [CBR Loading Press](#), [Hand-Operated](#), [Tripod Attachment](#), [Mechanical Dial Indicators](#), [Direct/Residual Shear Apparatus](#)

1.0" x 0.001" divisions.

Specification

Range	1.0"
Divisions	0.001"
Movement	Clockwise
Face Diameter	2-1/4"
Contact Point	Immediate response, up or down; tip movement magnified to indicator hand with minimal friction; 3/16" (5 mm) radius x 1/4" (6 mm) l.
Dials	With continuous graduations and revolution counters.
Measure Movement	Measure movement towards dial case; pointer at zero with stem extended.
Weight	Net 12 oz. (340 g).

Accessories



1" Extension Point

Code: [88-4154](#)



1/2" Extension Point

Code: [88-4152](#)



1/4" Extension Point

Code: [88-4150](#)



3" Extension Point

Code: [88-4156](#)



Dial Indicator Holder

Code: [88-4194](#)



Mechanical Dial Indicator - 25 mm Range Clockwise Movement

Code: [88-4110](#)



Unconfined Compression Assembly Only

Code: [25-3999](#)

Spares/Consumables



Electronic Digital Indicator, 0.600"/15 mm range

Code: [88-4210](#)

Alternatives



Electronic Digital Indicator, 0.600"/15 mm range

Code: [88-4210](#)



Stock Solution 1 gallon

Code: [24-4938](#)

Product Group: [Sand Equivalent Test Set](#)

Standards

ASTM D2419, AASHTO T176