



IF IT'S WORTH BUILDING, IT'S WORTH TESTING

This wishlist was generated on 07/08/2017, and contains the following Products:

36-4165/01

ADR-Auto V2.0 3000 BS EN Compression Machine

34-6250/01

Vibrating Table 600 X 400mm Table Top. 220-240V 50Hz 1Ph. Supplied with clamping assembly

34-4520

100mm Cube Mould 4-Part Clamp Type. Cast Iron Construction. BS EN Compliant.

34-4570

150mm Cube Mould 4-Part Clamp Type. Cast Iron Construction. BS EN Compliant.

24-0417/01

Motorised Liquid Limit Device W/ Counter BS 220-240V 50Hz 1Ph.

24-0461

Casagrande Grooving Tool Aashto

24-0453

ASTM Metal Grooving Tool.

34-6575/01

Large Curing Tank C/W with Circulating Pump Heater/Thermostat Unit and Lower Rack



ADR-Auto V2.0 3000 BS EN Compression Machine

Code: [36-4165/01](#)

Product Group: [BS EN Compression Machines](#)

The ADR-Auto V2.0 3000 BS EN is supplied complete with self-centring lower platen and safety gates fitted with interlock switches ready for testing 300 x 150 mm diameter cylinders. When used for cube testing Distance pieces (EN) of the appropriate size must be ordered separately.

Standards

EN 12350-6, NF P18-411

Further Information

****Not available for sale in the USA****

Whilst delivering all of the features and reputation of the established ADR-Auto V2.0 range with its 20 year design history, the new and improved user interface provides a high quality platform for testing that will enhance the performance of our compression machines. New, sophisticated electronics further the benefits of a closed-loop operation in testing concrete and cement/ mortar samples, satisfying the requirements of Quality Control Managers, Lab Managers and Technicians alike.

ACCURACY & SAVINGS

The NEW ADR-Auto V2.0 range, with 145mm (5.7") touch screen interface and intuitive menu driven operation reduces the time taken to set up the machine and perform tests, reducing the time to train staff by up to 25%. Most testing errors produce lower strength results. Noncompliant loading rates can generate errors in measured strength. With the latest closed-loop technology used in the ADR-Auto V2.0, the most effective cement ratios can be used with confidence.

TRACEABILITY & DATA QUALITY

The ADR-Auto V2.0 now provides improved data quality and traceability in due diligence cases - it is now possible to display traceability all the way from the machine/user to the accreditation body, increasing your reputation and peace of mind - all test results now come complete with the machine serial number attached. Prove your service quality - the ADR-Auto V2.0 now plots load vs time in real-time, proving full compliance to the testing standard. This data can be stored for later use or for detailed analysis of the concrete production.

USER SAFETY

Full safety gates as standard, total systems diagnostics, ram run-out switches and overload warnings ensure the safety of your employees and the reliability of your machine.

Specification

Testing Standards

BS EN 12390, BS EN 12390-3,
BS EN 12390-4, BS EN
12390-5, EN 12504-1, EN
1354, EN 1521, EN 3161, EN
1338, EN 772-6, EN 13286-41,
BS 3892-3, BS 187, BS 6717,
BS EN ISO 7500-1, ASTM E4

Capacity

3000 kN

Cubes (Concrete)

Up to 200 mm

Cylinders (Concrete)

Up to 160 x 320 mm

Blocks

Via optional Platen Handling
System

TFV and ACV

Yes

Voltage Supply

220-240 V 50 Hz 1 Ph

Frame Type

Welded

Max vert. Clearance

340 mm

Max hor. Clearance

355 mm

Platen Sizes

Lower 220mm sq,
Upper 300mm dia

Max Ram Travel

50 mm

Accessories



100 kN Flexural Fitting Kit ADR Auto for 220 - 240 V AC, 50 Hz, 1 ph

Code: [37-6135/01](#)



100 kN Flexural Fitting Kit ADR Auto for 220 - 240 V AC, 60 Hz, 1 ph

Code: [37-6135/06](#)



3000 kN Load Calibration Device Complete with Hand Held Readout Unit

Code: [37-8400](#)



300mm Lower Brick Platen

Code: [37-4842](#)



BS Block Platens & Platen Handling Assembly for 2000kN & 3000kN BS Frames.

Code: [37-4830](#)



BS/EN Standard Rectangular Platen

Code: [37-4860](#)



EN 12390-3/4 Distance Piece - 100 mm Depth

Code: [37-5180](#)




EN 12390-3/4 Distance Piece - 20 mm Depth

Code: [37-5110](#)



EN 12390-3/4 Distance Piece - 50 mm Depth

Code: [37-5120](#)



EN 12390-3/4 Distance Piece - 60 mm Depth

Code: [37-5140](#)



Flexible Hose

Code: [5038B0027](#)



Impact Printer Rs232 Serial Connection. Supplied Complete with 1 Paper Roll.

Code: [37-4859/01](#)

Spares/Consumables



Pressure transducer, 0-700bar, 0.05 to 10v DC Output

Code: [6014A0062](#)

Alternatives



ADR-Auto V2.0 2000 BS Compression Machine

Code: [36-4150/01](#)



ADR-Auto V2.0 2000 BS Compression Machine

Code: [36-4150/06](#)



ADR-Auto V2.0 3000 BS EN Compression Machine

Code: [36-4165/06](#)



Vibrating Table 600 X 400mm Table Top. 220-240V 50Hz 1Ph. Supplied with clamping assembly

Code: [34-6250/01](#)

Product Group: [Vibrating Table](#)

Vibrating table mounted on a steel stand, supplied with clamp assembly.

Standards

EN 12390-2, EN 12350-6, EN 12350-7

Further Information

****NOT AVAILABLE FOR SALE IN THE USA****

3000 cycles per minute. For 220 - 240 V AC, 50 Hz, 1 ph.

Specification


Dimensions (table top)	600 x 400 mm
Maximum no. Cube moulds	2 x 150 mm ²
Clamp Assembly	Single
Weight	60 kg

Accessories



Compacting Bar 25mm Sq X 380mm

Code: [34-2910](#)



Wire Brush

Code: [81-0705](#)

Alternatives



100 X 100 X 500mm Beam Mould.

Code: [34-5003](#)



100mm Cube Mould 2-Part Clamp Type. Cast Iron Construction. BS EN Compliant.

Code: [34-4650](#)



100mm Cube Mould 4-Part Clamp Type. Cast Iron Construction. BS EN Compliant.

Code: [34-4520](#)



100mm Dia Cylinder Mould 200mm Long.

Code: [34-5210](#)



150 X 150 X 750mm Beam Mould.

Code: 34-5053



150mm Cube Mould 2-Part Clamp Type. Cast Iron Construction. BS EN Compliant.

Code: 34-4670



150mm Cube Mould 4-Part Clamp Type. Cast Iron Construction. BS EN Compliant.

Code: 34-4570



150mm Dia Cylinder Mould 150mm Long.

Code: 34-5230



150mm Dia Cylinder Mould 300mm Long.

Code: 34-5260



**200mm Cube Mould Clamp Type. Cast Iron Construction.
Stamped Mould Sections. EN Compliant.**

Code: [34-4620](#)



100mm Cube Mould 4-Part Clamp Type. Cast Iron Construction. BS EN Compliant.

Code: [34-4520](#)

Product Group: [Cube Moulds](#), [Cube Moulds](#)

4-part with clamp attached base plate.

Standards

EN 12390-1, EN 12390-2

Specification

Construction	Bolted sides and clamped base plate
Finish	Painted
Weight	20 lb (9.1 kg)

Accessories



Aluminium Scoop Large

Code: [81-0220](#)



Compacting Bar 25mm Sq X 380mm

Code: [34-2910](#)



Float - Plasterer's type

Code: [81-0340](#)



Mould Oil (25 Litre Drum)

Code: [82-7341](#)



Wire Brush

Code: [81-0705](#)

Spares/Consumables



Soft Headed Mallet.

Code: [29-5020](#)

Alternatives



Vibrating Table 600 X 400mm Table Top. 220-240V 50Hz 1Ph. Supplied with clamping assembly

Code: [34-6250/01](#)



150mm Cube Mould 4-Part Clamp Type. Cast Iron Construction. BS EN Compliant.

Code: [34-4570](#)

Product Group: [Cube Moulds](#), [Cube Moulds](#)

4-part with clamp attached base plate.

Standards

BS 1881-108, EN 12390-1, EN 12390-2

Specification

Construction	Bolted sides and clamped base plate
Finish	Painted
Weight	42 lb (19.1 kg)

Accessories



Aluminium Scoop Large

Code: [81-0220](#)



Compacting Bar 25mm Sq X 380mm

Code: [34-2910](#)



Float - Plasterer's type

Code: [81-0340](#)



Mould Oil (25 Litre Drum)

Code: [82-7341](#)



Wire Brush

Code: [81-0705](#)

Spares/Consumables



Soft Headed Mallet.

Code: [29-5020](#)

Alternatives



Vibrating Table 600 X 400mm Table Top. 220-240V 50Hz 1Ph. Supplied with clamping assembly

Code: [34-6250/01](#)



Motorised Liquid Limit Device W/ Counter BS 220-240V 50Hz 1Ph.

Code: [24-0417/01](#)

Product Group: [Casagrande Method](#)

Complete with revolution counter and motor.

Standards

BS 1377-2

Accessories



Glass Plate.

Code: [24-0430](#)



Grooving Tool and Gauge B.S.

Code: [24-0425](#)

Alternatives



Liquid Limit Device BS with Counter. C/W Metal Grooving Tool & Test Gauge.

Code: [24-0410](#)



Casagrande Grooving Tool Aashto

Code: [24-0461](#)

Product Group: [Casagrande Method, Motorized Liquid Limit Device, AASHTO Grooving Tool](#)

- Rust resistant brass construction.
- 1 cm gage block located at end of handle.

The AASHTO Grooving Tool is used to control the width of the soil groove in the liquid limit cup, in accordance with AASHTO specifications.

Standards

AASHTO T89

Further Information

Brass construction with a gauge height of 1 cm.

Specification

Construction	Brass.
Gauge Height	1 cm.
Weight	Net 3 oz. (85 g).

Spares/Consumables



ASTM Plastic Grooving Tools

Code: [24-0451](#)



ASTM Metal Grooving Tool.

Code: [24-0453](#)

Product Group: [Casagrande Method](#)

Standards

ASTM D4318



Large Curing Tank C/W with Circulating Pump Heater/Thermostat Unit and Lower Rack

Code: [34-6575/01](#)

Product Group: [Expansion \(swell\) Test Equipment, Large Curing Tank](#)

This Large Curing Tank is supplied complete with a submersible pump, immersion heater/thermostat unit and separate control panel. The tank includes a lower rack as standard and is designed to maintain the temperature at $20 \pm 2^{\circ}\text{C}$, providing that the ambient temperature does not fall below 15°C or rise above 20°C .

Standards

EN 12390-2, ASTM C31, AASHTO T23

Further Information

****NOT AVAILABLE FOR SALE IN THE USA****

Supplied as specified. For 220 - 240 V AC, 50 - 60 Hz, 1 ph.

Specification

Internal Dimensions	1040 x 1040 x 605 mm (l x w x h)
Capacity	650 litres
Rated Power	2000 watt
Weight	60 kg

Accessories



Maximum and Minimum Thermometer

Code: [82-5310](#)

Alternatives



Jolting Table 220 - 240 V AC 60 Hz

Code: [39-1150/06](#)