



IF IT'S WORTH BUILDING, IT'S WORTH TESTING

# Contents

[www.ele.com](http://www.ele.com)  
+44 (0) 01525 249 200



This wishlist was generated on 21/09/2017, and contains the following Products:

---

505-092

**Digital Lux Meter**

---

514-126

**Soil moisture meter.**

---



## Digital Lux Meter

Code: [505-092](#)

Product Group: [Light measurement](#)

- High accuracy and wide range.
- Remote sensor head.
- Ideal for field work.

This portable lightmeter is for monitoring illuminance and gives a digital display in Lux. This simple to use instruments has only two controls; a power button and a range switch. It is ideal for field survey work and initial investigations.

## Further Information

Supplied complete with sensor head.



## Soil moisture meter.

Code: [514-126](#)

Product Group: [Soil Moisture](#)

This instrument is rugged, hand-held for field derivation of soil moisture.

Buriable soil moisture blocks allow moisture levels to be measured throughout the soil profile.

It is easy to use and battery operated.

This instrument is the ideal companion for the new, slim design moisture blocks, which are placed in the soil and leads connected in turn, to the meter. The measured resistance of the block, in ohms, is converted to a corresponding reading between 0 and 100 on an empirical scale. In practical terms this empirical range covers the soil suction range 0.2 to 15 bar and using the calibration graphs of soil moisture content (dry weight percentage) against soil suction in bars, the soil moisture content may be determined.

In practical situations, resistance blocks are often placed at various depths in the soil to monitor soil moisture content profiles across the root zone. Experience will determine the optimum depth of placement depending on the particular soil type.


The soil moisture blocks are designed for use with this particular meter and give a uniform and quick response, made possible by their slim design (20mm diameter).

## Further Information

### Specification

Measuring range	0-100 empirical range corresponds to 0.2-15 bar
Power requirements	1 x 9V battery (supplied)
Weight	0.24 kg


## Accessories



## Soil Moisture Block 0.9 m Lead

Code: [514-128](#)


---



## Soil Moisture Block 2.7 m Lead

Code: [514-130](#)

---



## Soil Moisture Block 4.5 m Lead

Code: [514-132](#)