



IF IT'S WORTH BUILDING, IT'S WORTH TESTING

Contents

www.ele.com
+44 (0) 01525 249 200



This wishlist was generated on 03/10/2017, and contains the following Products:

70-0095/01

Rock Core Drill Supplied with 2 X Nx Core Drill Bit

70-0250/01

Gsp210/250 Core Trimmer & Cut Off Machine Supplied with Coolant Pump Unit



Rock Core Drill Supplied with 2 X Nx Core Drill Bit

Code: [70-0095/01](#)

Product Group: [Sample Preparation](#)

Cores may be cut from regular or irregular samples of rock or other material for end preparation prior to strength testing. Side guards and a drain tray provide protection against water spray and a sliding front allows access to the specimen clamp. The clamp provides maximum orientation for securing irregular block samples.

Further Information

Supplied complete with 2 x NX Core Barrel. For 220-240 V AC, 50 Hz, 1ph.

Specification

Dimensions (l x w x h)	500 x 500 x 1160 mm
Drill Head Travel	630 mm
Drill Speeds	350 and 900 rpm
Weight	80 kg



Gsp210/250 Core Trimmer & Cut Off Machine Supplied with Coolant Pump Unit

Code: [70-0250/01](#)

Product Group: [Sample Preparation](#)

This unit, designed for use in Rock Mechanics, can also be used in mineralogy, ceramics and refractory sample preparation. Cores in excess of 140 mm length and cubes up to 100 mm square can also be prepared.

Further Information

Supplied complete with coolant recirculation pump/tank unit and 1 each diamond set cutting disc and double faced cup wheel. For 220 - 240 V AC, 50 Hz, 1 ph.

Specification

Dimensions (l x w x h)	406 x 915 x 760 mm
Two vices supplied	1- Regular and Irregular samples up to 70 x 125 mm 1- V-vice cores up to 57 mm diameter x 140 mm long
Blade capacity	200 mm
Rated Power	750 W
Weight	118 kg

Alternatives



Gsp210/250 Core Trimmer & Cut Off Machine Supplied with Coolant Pump Unit

Code: [70-0250/06](#)