



IF IT'S WORTH BUILDING, IT'S WORTH TESTING

This wishlist was generated on 16/10/2017, and contains the following Products:

---

23-5800

**Hand Operated Soil Lathe for 38mm Dia Specimens Up to 100mm Long.**

---

23-5802

**1.4" and 2.8" Hand Specimen Trimmer**

---

25-4261

**1.4" (35 mm) Rubber Membranes**

---



## Hand Operated Soil Lathe for 38mm Dia Specimens Up to 100mm Long.

Code: [23-5800](#)

Product Group: [Soil Lathes, Soil Trimmers \(Lathes\)](#)

For producing 38 mm diameter specimens. The lathe platen is adjustable in height and will accept specimens up to 100 mm in length.

## Standards

BS 1377-1

## Further Information

- Lightweight frame construction for both laboratory and field use.
- Sturdy plated steel uprights serve as guides for wire saw during final trimming procedure.
- Adjustable upper platen trimming for various sample heights.

Wire Saw and other trimming accessories not included; order separately.

## Accessories



### Trimming Knife

Code: [81-0710](#)

## Alternatives



## 1.4" and 2.8" Hand Specimen Trimmer

Code: 23-5802



## 1.4" and 2.8" Hand Specimen Trimmer

Code: [23-5802](#)

Product Group: [Soil Lathes, Soil Trimmers \(Lathes\)](#)

Specimen Trimmers are designed to simplify precision trimming of soil samples for triaxial, shear, unconfined compression, and other tests requiring standard cylindrical specimens. This trimming frame is supplied complete with vane type grips for both 1.4" (35 mm) and 2.8" (70 mm) diameter specimens, and a narrow wire saw.

### Further Information


- Lightweight frame construction for both laboratory and field use.
- Sturdy plated steel uprights serve as guides for wire saw during final trimming procedure.
- Samples are held securely during trimming through vane type grips.
- Adjustable upper gripper platen for various sample heights.
- Plated steel uprights and gripper assemblies for rust resistance and long life.

Includes Wire Saw.

### Specification

Sample Size.	Trims samples to either 1.4" (35 mm) or 2.8" (70 mm) diam.
Uprights.	Positioned to guide wire saw to control final sample diam; plated steel.
Sample Grips.	Vane type; hold sample during trimming; plated steel.
Overall Dimensions.	7" w. x 5" d. x 14" h. (178 x 127 x 356 mm).
Weight.	Net 16 lbs. (7.3 kg).

### Accessories



#### Trimming Knife

Code: [81-0710](#)

### Alternatives



## Hand Operated Soil Lathe for 38mm Dia Specimens Up to 100mm Long.

Code: [23-5800](#)



## 1.4" (35 mm) Rubber Membranes

Code: [25-4261](#)

Product Group: [Rubber Membranes, Tri-Flex 2](#)  
[Permeability Test Cell](#)

### Standards

ASTM D2850, ASTM D4767, ASTM D5084, AASHTO T296, AASHTO T297, ASTM D7181

### Accessories



#### Rubber Membrane 100mm/4 Inch Diameter. Pack of 10

Code: [25-7621](#)



#### Rubber Membrane 70mm/2.8 Inch Diameter. Pack of 10.

Code: [25-6441](#)

### Alternatives



#### Rubber Membrane 100mm/4 Inch Diameter. Pack of 10

Code: [25-7621](#)



#### Rubber Membrane 70mm/2.8 Inch Diameter. Pack of 10.

Code: [25-6441](#)