



IF IT'S WORTH BUILDING, IT'S WORTH TESTING

# Contents

[www.ele.com](http://www.ele.com)  
+44 (0) 01525 249 200



This wishlist was generated on 19/01/2018, and contains the following Products:

---

34-6100

**Flake Capping Compound to ASTM C617 22Kg**

---



## Flake Capping Compound to ASTM C617 22Kg

Code: 34-6100

Product Group: Sulphur Compound Method, Flake Capping Compound

Supplied in 22 kg box.


## Standards

ASTM C617, AASHTO T231

## Specification

Density	13 7 lbs./cu. ft. (2,186 kg/cu. m.).
Tensile Strength	605 psi (4.2 x 105 kg/sq m.) after 48 hrs.
Compressive Strength	5,000 psi (3.6 x 106 kg/sq m.) minimum, after 2 hrs.
Melting Range	23 0°-24 0°F (11 0°-115 °C).
Optimum Pouring Range	260°-290°F (12 6°-143 °C).
Weight	Net 50 lbs. (22 .7 kg); Shpg. 52 lbs. (23 .6 kg).

## Accessories



### 6" Retaining Caps


Code: 34-6134

## Alternatives



### 4" Compression Pads 60 Durometer

Code: 34-6132/10



## 4" Compression Pads 70 Durometer

Code: [34-6132/12](#)


---



## 4" Retaining Caps

Code: [34-6132](#)


---



## 6" Compression Pads 60 Durometer

Code: [34-6134/10](#)

---



## 6" Compression Pads 70 Durometer

Code: [34-6134/12](#)

---



## Capping Compound Warming Pots 110vAC

Code: [34-6125/02](#)

---



## Capping Compound Warming Pots 220vAC

Code: [34-6125/01](#)

---




## Cylinder Capping Frame Complete with 100mm and 150mm Dia Capping Plates.

Code: [34-6031](#)



## Cylinder Capping Set

Code: [3000/01](#)



## Cylinder Capping Set

Code: [3000/02](#)



## Melting Pot 4 Litre Capacity. 50 to 300 Deg. C. Temperature Range.

Code: [34-6122/01](#)