



IF IT'S WORTH BUILDING, IT'S WORTH TESTING

Contents

www.ele.com
+44 (0) 01525 249 200



This wishlist was generated on 29/01/2018, and contains the following Products:

35-2505

Crack Detection Microscope Magnification X 40 Measuring Range of 4mm In 0.02mm Divisions

35-1480

Standard Concrete Test Hammer



Crack Detection Microscope Magnification X 40 Measuring Range of 4mm In 0.02mm Divisions

Code: [35-2505](#)

Product Group: [Crack Detection](#), [Crack Detection Microscope](#)

Specifically designed for measuring crack width in concrete, this high definition microscope operates via an adjustable light source provided by high power batteries.

Supplied in a pocket sized carrying case.

Specification

| | |
|-----------------|--|
| Magnification | X 35 . |
| Measuring Range | 4 mm. |
| Divisions | 0.02 mm. |
| Dimensions | 1.5" x 3.5" x 6" (40 x 90 x 150 mm) in case. |
| Weight | Net 19.4 oz. (550 g). |

Alternatives



Calibrated Crack Monitor

Code: [35-2510](#)



Standard Concrete Test Hammer

Code: [35-1480](#)

Product Group: [Concrete Test Hammer, Surface Hardness](#)

The hammer is intended for testing the quality of concrete in finished structures such as buildings and bridges. Supplied complete with carrying case and carborundum stone, the hammer is suitable for testing concrete with compressive strengths of 10 to 70 N/mm².

Standards

ASTM C805

Specification

| | |
|--------------------|---|
| Body | Includes indicator scale, calibration curves. |
| Calibration Curves | Rebound number vs. compressive strength. |
| Rubbing Stone | Prepares test surface. |
| Accuracy | Within 15 %. |
| Carrying Case | Plastic. |
| Weight | Net 3 lbs. (1.4 kg). |

Accessories



Testing Anvil

Code: [35-1530](#)

Spares/Consumables



Rubbing Stone

Code: [35-1475/10](#)

Alternatives



Concrete Test Hammer - English

Code: [35-1475](#)