



IF IT'S WORTH BUILDING, IT'S WORTH TESTING

# Contents

[www.ele.com](http://www.ele.com)  
+44 (0) 01525 249 200



This wishlist was generated on 10/07/2018, and contains the following Products:

---

36-0720/01

**ADR Touch 1500 Compression Machine with Digital Readout.**

---

47-5175

**Compact Core Drill**

---

47-5565

**Core Barrel 100 mm**

---

78-1250/01

**225 Litre Drying Oven**

---

78-5457/01

**Electronic Balance - 8 000 g x 0.1 g**

---

45-3810/01

**Rotatest 1500**

---

46-4120

**Ductility Testing Machine**

---



## ADR Touch 1500 Compression Machine with Digital Readout.

Code: 36-0720/01

Product Group: General Purpose Compression Machines

- 1560 kN/350 000 lbf capacity
- Calibration accuracy to BS EN ISO 7500-1; ASTM E4;
- Efficient hydraulic power packs
- Economic machines ideal for site use

The Compact 1500 range of compression machines has been designed to meet the need for a simple, economic and reliable means of testing concrete.

### SPECIMEN CAPACITY

The dimensions of the frame allow the testing of cylinders up to 320 mm long x 160 mm diameter, and cubes 150 or 100 mm square. Kerbs and flagstones may also be tested on the ADR machine as well as 150 mm and 100 mm square section beams to ASTM C78, using the optional 100 kN flexural frames which are connected to the power pack.

### LOAD INDICATION

The ADR digital readout is a microprocessor controlled instrument, which is fitted as standard to all digital machines in the range. Load can be displayed in kN, lbf or kgf as selected by the operator.

## Standards

BS EN ISO 7500-1, ASTM E4

## Further Information

**\*\*NOT AVAILABLE FOR SALE IN THE USA\*\***

The Standard range of compression machines has been designed to meet the need for a simple, economic and reliable means of testing concrete.

Whilst delivering all the features and reputation of the established ADR Series with its extensive design history, the new and improved user interface provides a high quality platform for testing that enhances the performance of ELE's compression machines.

New, sophisticated electronics further the benefits of simplified operation, whilst delivering the highest levels of accuracy in testing concrete and cement/mortar samples, satisfying the needs of Quality Control Managers, Lab Managers and Technicians.

### ACCURACY & SAVINGS

The new ADR Touch Series, with 145mm (5.7") high resolution QVGA touch screen interface and intuitive menu-driven operation, reduces the time taken to set up the machine and perform tests, reducing the time to train staff by up to 25%.

- Up to 6 sample types can be set as favorites, enabling one-touch set up for repeat testing.

- Full, QWERTY touch pad for input of test data.

Most testing errors produce lower strength results. Noncompliant loading rates can generate errors in measured strength. The user interface includes real-time display of load vs. time, further ensuring accurate and consistent test results and providing "goodness of test" data to improve traceability in your QC operations.

## TRACEABILITY & DATA QUALITY

The ADR range now provides improved data quality and traceability in due diligence cases - it is now possible to demonstrate traceability all the way from the machine/user to the accreditation body, increasing your reputation and peace of mind - all test results now come complete with the machine serial number attached.

- Enhanced USB data communications between PC and machine - eliminating the need for download software.
- Two gigabytes of storage memory.
- Full customization of sample sizes - stress calculations are automatically recalculated.

## USER SAFETY

With full safety gates as standard, total systems diagnostics, ram run-out switches and overload warnings ensure the safety of your employees and the reliability of your machine.

---

## Specification

Testing Standards	BS EN ISO 7500-1, ASTM E4
Capacity	1500 kN
Cubes (Concrete)	Up to 150 mm
Cylinders (Concrete)	Up to 160 x 320 mm
Blocks	n/a
Flexural Testing	Via Flexural Frame
TFV and ACV	Yes
Voltage Supply	220-240V 50/60 Hz 1Ph.
Frame Type	Welded
Max vert. Clearance	340 mm
Max hor. Clearance	325 mm
Platen Sizes	Lower, Upper 222 mm
Max Ram Travel	50 mm

---

## Accessories



### **100kN Flexural Fitting Kit (ADR) Used for Connecting Flexural Frames to ADR Compression Machines.**

Code: [37-6138](#)



## 2000 kN Load Calibration Device complete with Handheld Readout Unit & Calibration Certificate ISO376

Code: [37-8315](#)



## ADR Touch Head for Compression Machines

Code: [37-5951/09](#)



## Impact Printer Rs232 Serial Connection. Supplied Complete with 1 Paper Roll.

Code: [37-4859/01](#)



## Standard Distance Piece - 100 mm Depth

Code: [37-5100](#)



## Standard Distance Piece - 20 mm Depth

Code: [37-4980](#)





## Standard Distance Piece - 50 mm Depth

Code: [37-5000](#)



## Standard Distance Piece - 60 mm Depth

Code: [37-5020](#)



## Standard Distance Piece - 80 mm Depth

Code: [37-5050](#)

## Spares/Consumables



## Pressure transducer, 0-700bar, 0.05 to 10v DC Output

Code: [6014A0062](#)

## Alternatives



## ADR Touch 2000 Standard Compression Machine with Digital Readout.

Code: [36-3090/01](#)



## Compact Core Drill

Code: 47-5175

Product Group: Compact Core Drill Machine

This compact and portable core drilling machine is designed to cut cores up to 150 mm diameter from concrete, asphalt and similar hard construction material.

The machine comprises a vertical support column which carries the drill head/motor assembly.

An integral water swivel is built into the drill head providing a 12 mm connection to an external water supply via 12 mm flexible hose (not supplied). The motor assembly comprises a 4 hp, 2-stroke petrol engine. Speeds of 800 rpm or 1200 rpm may be selected. A ball screw mechanism enables close control over drilling pressure and rapid return when drilling is completed.

The complete assembly is supplied on a rigid metal base frame with levelling facility and is suitable for vertically down drilling applications only.

## Standards

EN 12697-32, EN 13280-4, BS 598-104

## Further Information

**\*\*NOT AVAILABLE FOR SALE IN THE USA\*\***

Special Note: Requires a continuous clean water supply via a 12 mm flexible hose (not supplied).



## Core Barrel 100 mm

Code: [47-5565](#)

Product Group: [Core Barrels](#)

## Standards

EN 12697-32, EN 13280-4, BS 598-104

## Further Information

**\*\*NOT AVAILABLE FOR SALE IN THE USA\*\***





## 225 Litre Drying Oven

Code: [78-1250/01](#)

Product Group: [Percentage Refusal Density \(PRD\)](#),  
[Oven Drying Method](#), [Oven Drying Method](#), [Oven Drying Method](#)

## Standards

EN 12697-32, EN 13280-4, BS 598-104, BS 1377

## Specification

Capacity	225 litres
External Dimensions (l x w x h)	540 x 1040 x 940
Internal Dimensions (l x w x h)	440 x 920 x 600
Fluctuation	± 0.75°C
Rated power heater elements	2000 W
Shelves supplied	3
Shelf positions	4
Weight	80 kg

## Alternatives



## 100 Litre Drying Oven

Code: [78-1225/01](#)



## 150 Litre Drying Oven

Code: [78-1235/01](#)



## 50 Litre Drying Oven

Code: [78-1215/01](#)

# Product Sheet

[www.ele.com](http://www.ele.com)  
+44 (0) 01525 249 200



## Drying Oven 425 Litre Capacity

Code: [78-0135/01](#)



## Electronic Balance - 8 000 g x 0.1 g

Code: [78-5457/01](#)

Product Group: [Electronic Balances](#)

## Further Information

**\*\*Not available for sale in the USA\*\***

## Specification

Capacity resolution	8000 g x 0.1 g
Pan size	225 x 275 mm
Mains and battery	Yes
Dimensions (w x d x h)	315 x 355 x 110 mm
Weight	4 kg
Weighing units	g, kg, lb, lb:oz, oz
Repeatability	0.1 g



## Rotatest 1500

Code: 45-3810/01

Product Group: Asphalt Centrifuge Extractors

Centrifuge extractor used to determine the quantitative amount of bitumen in bituminous paving mixtures. Variable speed control from 0 to 3600 rpm through the front panel mounted control knob and brake control included for rapid deceleration.

Precision machined aluminium removable cover with integral cup for adding solvent, with sealed cast aluminium housing. Centrifuge extractor used to determine the quantitative amount of bitumen in bituminous paving mixtures. Variable speed control from 0 to 3600 rpm through the front panel mounted control knob and brake control included for rapid deceleration.

Precision machined aluminium removable cover with integral cup for adding solvent, with sealed cast aluminium housing.

## Standards

EN 12697-1, ASTM D2172, AASHTO T164

## Further Information

**\*\*NOT AVAILABLE FOR SALE IN THE USA\*\***

1500 g capacity. Supplied with 100 Filter Discs. For 220 V AC, 50 - 60 Hz, 1ph.

## Accessories



### Bowl - 2.5 litre

Code: 81-5020



## Desiccator - Non-vacuum

Code: [82-2100](#)



## Evaporating Dish - 100 x 40 mm

Code: [82-1970](#)



## Filter Discs Pack of 100

Code: [45-3803](#)



## Hotplate

Code: [78-2950/01](#)



## Measuring Cylinder - Glass 100 ml

Code: [82-0380](#)



## Measuring Cylinder - Glass 1000 ml

Code: [82-0500](#)



## Sample Tray - 306 x 306 x 38 mm

Code: [81-4020](#)



## Silica Gel

Code: [82-7091](#)



## Volumetric Flask - 100 ml

Code: [82-1000](#)



## Volumetric Flask - 1000 ml

Code: [82-1060](#)

## Spares/Consumables





## Replacement bowl for Rotatest 1500 centrifuge extractor

Code: [45-3810/10](#)

---

### Alternatives



## Muffle Furnace

Code: [83-4170/01](#)



## Rotatest 3000

Code: [45-3815/01](#)



## Ductility Testing Machine

Code: 46-4120

Product Group: Ductility Testing

The Ductility Testing Machine is used to determine the ductility of bituminous materials in a briquette mould by measuring the breaking elongation at a constant speed of 50 mm/min. It is designed for testing 3 specimens simultaneously. The Internal tank is made of stainless steel. The bath is fitted with an immersion heater in order to obtain (in normal conditions), the 25°C test temperature.

The Ductility Testing Machine comprises of speed control and water circulator to maintain the homogenous water temperature.

Elongation measurement through the motor encoder.

3 simultaneous load measurements with 18-bit resolution.

Speed control with servo AC motor between 0.01 to 100 mm/min.

Ethernet connection for computer interface.

Has 3 load cells with an accuracy of  $\pm 0.1N$ , with a maximum capacity of 300 N.

Failure conditions can be downloaded to the unit.

Complies with EN13398, ASTM D113, ASTM D6084 and AASHTO T51 standards.

## Specification

Dimensions	300 x 1850 x 550 mm
Weight	80kg
Watts	1000 W
Power supply	220V 50-60Hz 1Ph