







## IF IT'S WORTH BUILDING, IT'S WORTH TESTING

www.ele.com

## Contents



This wishlist was generated on 09/08/2018, and contains the following Products:

### 45-6829/06 Marshall Stability Tester

45-6894 Asphalt Flow Indicator with Brake - Metric



## **Product Sheet**





#### **Marshall Stability Tester**

Code: 45-6829/06 Product Group: Marshall Stability Tester

Compact size takes up little counter space in the lab. Push-button operation controls movement of load screw. Indicator lights show when unit is running and when test limit or maximum travel is reached.

The Marshall Stability Tester quickly and accurately measures the resistance to plastic flow of bituminous mixtures, in accordance with ASTM D-6927 and AASHTO T-245 testing standards.

With operator convenience in mind, the machine features push-button operation with indicator lights to show when the unit is in operation and when the platen has reached its limit or point of maximum travel.

# Further Information 220vAC, 60Hz, 1ø

Specification	
Frame Capacity	10,000 lbf. (44 .5 kN) maximum.
Proving Ring	up to 10,000 lbf. (sold separately)
Controls	Push-button up/down/stop with running and limit indicator lights.
Motor	3/4 h.p., reversible.
Speed	2" (50.8 mm) per minute.
Travel	2.5" (64 mm) maximum.
Clearances	10" (254 mm) between uprights, 7-1/2" (191 mm) between platen and load piston.
Overall Dimensions	14 " w. x 23 " d. x 40" h. (35 6 x 584 x 1,016 mm).
Housing	14 " w. x 23 " d. x 11 " h. (35 6 x 584 x 279 mm).
Weight	Net 189 lbs. (86 kg); Shpg. 236 lbs. (107 kg).

### Accessories







### 4" Lottman Breaking Head

Code: 45-6860



## **4" Marshall Breaking Head** Code: 45-6855

Asphalt Flow Indicator with Brake - English Code: 45-6892



Asphalt Flow Indicator with Brake - Metric Code: 45-6894



## Proving Ring 10,000 lbf Capacity

Code: PR-100

## **Alternatives**









## **Marshall Test System Set**

Code: 5002/06



## **Product Sheet**





## Asphalt Flow Indicator with Brake - Metric

Code: 45-6894 Product Group: Marshall Stability Breaking Head, Asphalt Flow Indicator with Brake, Accessories for the Marshall Test

#### Standards ASTM D6927, AASHTO T245

#### Specification

Holder Dial Indicator Range

Weight

Cast aluminum. Special type with brake. 25 .4 mm x 0.254 mm divisions. Net 12 oz. (340 g).

#### Accessories



### **4" Marshall Breaking Head**


Code: 45-6855



Asphalt Flow Indicator with Brake - English

#### Code: 45-6892

Alternatives









### **4" Marshall Breaking Head**

Code: 45-6855



## Asphalt Flow Indicator with Brake - English

Code: 45-6892

