

















IF IT'S WORTH BUILDING, IT'S WORTH TESTING

Contents

www.ele.com +44 (0) 01525 249 200



This wishlist was generated on 27/02/2019, and contains the following Products:

36-5150/01

ADR Touch Control PRO 2000 Auto BS EN Compression Machine

38-1000

Blaine Air Permeability Apparatus







ADR Touch Control PRO 2000 Auto BS EN Compression Machine

Code: 36-5150/01

Product Group: BS EN Compression Machines

The ADR Touch Control PRO 2000 Auto BS EN is supplied complete with self-centring lower platen and safety gates fitted with interlock switches ready for testing 320 x 160 mm diameter cylinders. When used for cube testing distance pieces (EN) of the appropriate size must be ordered separately.

Standards

EN 12350-6, NF P18-411, EN 12390-4, EN 12390-3, EN 772-1, BS EN ISO 7500-1, ASTM E4

Further Information

Not available for sale in the USA

The ADR Touch Control PRO will deliver all the features and quality of the established ADR-Auto range, with its 20 year history, but with a new sleek design and additional capabilities. The console assembly consists of an ADR Touch Control Pro and power base which can be used with all existing concrete and cement frames

USER INTERFACE

The new ADR Touch Control PRO has an improved user interface providing a high quality platform for testing that will enhance the performance of our compression machines. It now has a larger 7-inch colour touch screen with a higher definition display, allowing easier observation of test progress. A favourites option is also available, allowing users to save the most common set-ups for immediate access, without the need for navigating through selection menus.

USER FLEXIBILITY

The ADR Touch Control PRO has a unique flexible head with rotation capabilities of 75-degrees and a 45-degree tilt, improving usability and comfort for individual users. It is available with four languages English, Spanish, Portuguese and French, making it even more user-friendly and accessible to a wider audience. The new LAN connectivity feature lets the operator use the PC based APP (ELE Logger) to download test results away from the test area. User flexibility has also increased with the new ADR Touch Control PRO as it can now be operated remotely, so tests can be initiated away from the test area. Many issues can be resolved quickly by our service team through the new remote diagnostics feature and updating to the latest version of software has never been easier.

COMPATIBILITY

www.ele.com ## +44 (0)1525 249 200 ## +1 (800) 323 1242 Page 3 of 10



The all new dual sensor capabilities allow users to test both concrete and cement samples on one frame. The ADR Touch Control PRO is compatible with all existing compression frames and upgrade kits are also available. The upgrade kits can be used to convert existing ADR-Auto consoles to the new Automatic Digital Control Readout.

TESTING TIMES

The new generation ADR Compression Machines have an increased control over the pace rate, which allows users to run the pace rate higher than average, but still within standard. This produces an average time saving of 10% for a typical 150mm cube sample.

ELECTRICAL

Reduced component count and no wire design results in increased reliability and serviceability. New low voltage interlocks and e-stop has increased safety. The ADR Touch Control PRO has the latest Arm Core Processor technology which has improved the processing power and speed.

Specification

Capacity 2000 kN
Cubes (Concrete) Up to 200 mm
Cylinders (Concrete) Up to 320 x 160 mm

Blocks Via optional Platen Handling

System

TFV and ACV Yes

Voltage Supply 220-240 V 50 Hz 1 Ph

Frame Type Welded
Max vert. Clearance 375 mm
Max hor. Clearance 355 mm

Platen Sizes Lower 220mm sq,

Upper 300mm dia

Max Ram Travel 50 mm

Accessories



100 kN Flexural Fitting Kit ADR Auto for 220 - 240 V AC, 50 Hz, 1 ph

Code: 37-6135/01



100 kN Flexural Fitting Kit ADR Auto for 220 - 240 V AC, 60 Hz, 1 ph

Code: 37-6135/06

www.ele.com +44 (0)1525 249 200

= +1 (800) 323 1242







2000 kN Load Calibration Device complete with Handheld Readout Unit & Calibration Certificate ISO376

Code: 37-8315



300mm Lower Brick Platen

Code: 37-4842




BS Block Platens & Platen Handling Assembly for 2000kN & 3000kN BS Frames.

Code: 37-4830



EN 12390-3/4 Distance Piece - 100 mm Depth

Code: 37-5180



EN 12390-3/4 Distance Piece - 20 mm Depth

Code: 37-5110



EN 12390-3/4 Distance Piece - 50 mm Depth

Code: 37-5120

www.ele.com +44 (0)1525 249 200

= +1 (800) 323 1242







EN 12390-3/4 Distance Piece - 60 mm Depth

Code: 37-5140



Flexible Hose

Code: 5038B0027



Impact Printer Rs232 Serial Connection. Supplied Complete with 1 Paper Roll.

Code: 37-4859/01

Spares/Consumables



Pressure transducer, 0-700bar, 0.05 to 10v DC Output

Code: 6014A0062



Pressure transducer, 0-70bar, 0.05 to 10v DC Output

Code: 6014A0065

Alternatives



ADR Touch Control PRO 2000 Auto BS EN Compression Machine

Code: 36-5150/06

www.ele.com # +44 (0)1525 249 200 = +1 (800) 323 1242 Page 6 of 10





ADR Touch Control PRO 3000 Auto BS EN Compression Machine

Code: 36-5165/06



ADR Touch Control PRO 3000 Auto BS EN Compression Machine

Code: 36-5165/01



Remote Head ADR Touch Control PRO 3000 BS EN **Compression Machine**

Code: 36-5265/01



Remote Head ADR Touch Control PRO 3000 BS EN **Compression Machine**

Code: 36-5265/06

= +1 (800) 323 1242 www.ele.com Page 7 of 10







Blaine Air Permeability Apparatus

Code: 38-1000

Product Group: Blaine Fineness Apparatus, Determination of Fineness Blaine Apparatus

- Designed for the determination of fineness to EN 196-6, BS 4359-2, ASTM C204
- Supplied complete with stainless stell cell perforated disc and plunger Manometer U-Tube Aspirator bottle of Manometer liquid (pure mineral 1 litre) and a box of filter papers

Standards

EN 196-6, EN 459-2, EN 13286-44, BS 4359-2, ASTM C204, AASHTO T153

Specification

Cell Stainless steel; 12.70 ±0.10

mm i.d.

Disk 0.9 ± 0.1 mm thick with 30-40

one mm diam. holes.

Plunger Stainless steel.

Manometer U-tube glass with ground joint,

stop cock and rubber

bulb assembly.

Filter Paper 12.70 mm diam.
Fluid Pure Mineral Oil.
Weight Net 7 lbs. (3.2 kg).

Accessories



Electronic Balance - 620 g x 0.001 g

Code: 78-5405/01

www.ele.com # +44 (0)1525 249 200 # +1 (800) 323 1242 Page 8 of 10







Filter Papers

Code: 38-0650



Pure Mineral Oil 1 Litre Bottle.

Code: 38-0620



Reference Cement

Code: 38-0640



Reference Cement

Code: 38-0645

Spares/Consumables



Aspirator

Code: 38-0500/11

www.ele.com +44 (0)1525 249 200

= +1 (800) 323 1242







Blaine Air Permeability Cell

Code: 38-1000/15



Filter Paper

Code: 38-0652



Manometer U-tube

Code: 38-1000/10