



IF IT'S WORTH BUILDING, IT'S WORTH TESTING

Contents

www.ele.com
+44 (0) 01525 249 200



This wishlist was generated on 25/03/2019, and contains the following Products:

[26-2261](#)

Pocket Shearmeter with 3 Vanes 0 to 1Kgf/Cm2 X 0.5Kgf/Cm2.

[26-2261/12](#)

Standard Vane

[29-3729](#)

Pocket Penetrometer.

[29-3729/10](#)

Adaptor Foot



Pocket Shearmeter with 3 Vanes 0 to 1Kgf/Cm2 X 0.5Kgf/Cm2.

Code: [26-2261](#)

Product Group: [Torvane Shear Device, Pocket Shearmeter](#)

The shearmeter can be used on tube samples, on the sides of pits, cuttings etc. It is an invaluable tool for initial site investigation work.

Further Information

Complete with sensitive vane, standard vane and high-capacity vane. Range 0 to 1 x 0.05 kgf/cm2.

Specification

Vane Driver	1.6" (41 mm) diam. x 3.2" (81 mm) l. with vane attached.
Dial Scale	1 kg/sq. cm (tons/sq. ft.) x 0.05 subdivisions.
Carrying Case	Plastic; 6" w. x 4" d. x 2" h. (152 x 102 x 51 mm).
Weight	Net 10.5 oz. (300 g).

Spares/Consumables



High-Capacity Vane

Code: [26-2261/14](#)



Sensitive Vane

Code: [26-2261/10](#)



Standard Vane

Code: [26-2261/12](#)

Alternatives



Digital Direct/Residual Shear Apparatus Complete with Lever Loading Assembly. 110-120V 50/60Hz 1Ph.

Code: [26-2114/02](#)



Digital Direct/Residual Shear Apparatus Complete with Lever Loading Assembly. 220-240V 50/60Hz 1Ph.

Code: [26-2114/01](#)



Hand Vane Tester

Code: [26-3346](#)



Standard Vane

Code: [26-2261/12](#)

Product Group: [Torvane Shear Device](#)

0-1.0 kg/sq. cm (tons/sq. ft.).



Pocket Penetrometer.

Code: [29-3729](#)

Product Group: [In-situ Testing](#), [Pocket Penetrometer](#), [Plate Bearing Apparatus](#)

- Direct-reading scale in tons/sq. ft. and kg/sq. cm.
- Ground and polished stainless steel loading piston.
- Calibrated spring and penetrometer body plated for rust resistance and long life.
- Convenient belt-loop style carrying case.
- Optional Adapter Foot for testing very soft materials.

The Pocket Penetrometer was originally developed for use by field personnel in checking visual classification of soils. Data was compiled on several thousand unconfined compressive strength tests of silty clays and clayey soils against the penetrometer readings to develop the scale.

Further Information

IMPORTANT: the readings obtained from the pocket penetrometer do not replace laboratory test results due to the fact that a small area penetration test is inherently liable to give misleading results. The instrument should not be used for obtaining foundation design data.

Specification

Range	0.25 to 4.5 tons/sq. ft. (kg/sq. cm).
Scale Divisions	0.25 tons/sq. ft. (kg/sq. cm).
Load Piston	1/4" (6 mm) diam.; stainless steel.
Carrying Case	Canvas; belt-loop style.
Dimensions	3/4" diam. x 6-3/8" l. (19 x 162 mm).
Weight	Net 7 oz. (198 g).

Accessories



Adaptor Foot

Code: [29-3729/10](#)

Alternatives



C.O.E Cone Penetrometer

Code: [29-3741](#)



Proctor & Mortar Penetrometer Set

Code: [29-3935](#)



Proving Ring Penetrometer

Code: [29-3739](#)



Adaptor Foot

Code: [29-3729/10](#)

Product Group: [Pocket Penetrometer, Plate Bearing Apparatus](#)

1" (25.4 mm) diam.

Increases piston area 16 times for testing on soft materials.

Further Information

The Pocket Penetrometer does not replace field and laboratory testing analysis