







IF IT'S WORTH BUILDING, IT'S WORTH TESTING

www.ele.com

Contents



This wishlist was generated on 06/05/2019, and contains the following Products:

23-7452

Speedy Moisture Tester D2 Large 0-20% Moisture Range. Supplied Less Calcium Carbide

23-7700 Calcium Carbide Powder 500G.



Product Sheet





Speedy Moisture Tester D2 Large 0-20% Moisture Range. Supplied Less Calcium Carbide

Code: 23-7452

Product Group: Rapid Moisture Testers, Rapid method by Speedy Moisture Tester, Rapid method by Speedy Moisture Tester

Uses a technique based on the fact that water will react with calcium carbide to form a gas and that the quantity of gas formed is directly proportional to the water present. The gas pressure is indicated on a built-in pressure gauge. The pressure gauge calibrated in percentage of moisture. Has a moisture range of 0-20% with gauge divisions every 0.2%. Holds a sample size of 20 g. Includes an electronic balance of 200 g capacity x 0.1 g readability and is supplied in plastic carrying case.

Standards BS 812, ASTM D4944, AASHTO T217

~				
S	ne	CIT	icat	inn
	$\mathbf{p}\mathbf{c}$	CIII	Juli	

D2 Large
0 to 20%
0.20%
20
8.4

Accessories



Calcium Carbide Powder 500G.

Code: 23-7700



Reagent for Speedy Moisture Testers. Pack of 12 Cans 500 G Each. (Calcium Carbide)

Code: 23-7702

Product Sheet





Speedy Calibration Unit Self Contained Unit.

Code: 23-7600

Spares/Consumables



Portable Electronic Balance

Code: 23-7452/12

Alternatives



Speedy Moisture Tester D2 Small 0-20% Moisture Range. Supplied Less Calcium Carbide

Code: 23-7502



Speedy Moisture Tester G2 Large 0-50% Moisture Range. Supplied Less Calcium Carbide

Code: 23-7462



Product Sheet





Calcium Carbide Powder 500G.

Code: 23-7700 Product Group: Accessories for the Speedy Moisture Tester, Accessories for the Speedy Moisture Tester

Supplied in 500 g container.

Standards ASTM D4944, AASHTO T217

Further Information

NOT AVAILABLE FOR SALE IN THE USA

