



IF IT'S WORTH BUILDING, IT'S WORTH TESTING

This wishlist was generated on 11/06/2019, and contains the following Products:

---

24-0430

**Glass Plate.**

---

24-0434

**Liquid Limit Device ASTM/ Aashto Hand-Operated W/ Revolution Counter.  
Supplied Less Grooving Tool.**

---

24-0453

**ASTM Metal Grooving Tool.**

---

24-0811

**Rod Comparator**

---

24-1500

**Prong Plate.**

---

24-1550

**Shrinkage Dish.**

---

24-1600

**Glass Cup.**

---

24-2885

**Pyknometer Complete with Non-Corrodable Cone and Rubber Seal 1Kg  
Capacity**

---

24-4650

**Soil Hydrometer Type 151H ASTM D422 Graduated 0.995 to 1.038 Specific  
Gravity.**

---

24-9010

**Straight Edge 300mm.**

---

24-9060

**Proctor Mould**

---

24-9063

**ASTM Compaction Rammer 2.5Kg.**

---

24-9066

**ASTM Compaction Mould 152mm.**

---

24-9070

## ASTM/Modified Proctor Compaction Rammer 4.5Kg.

---

24-9150/06

### Cbr-Test 50 Machine 50kN Capacity BS and ASTM Supplied with Stabilising Bar.

---

25-3518/10

### Adaptor kit, to perform CBR on the Tritest 50 load frame

---

78-1225/01

### 100 Litre Drying Oven

---

79-5020

### 8in Dia ASTM Sieve 4.75mm Stainless Steel Mesh.

---

79-5080

### 8in Dia ASTM Sieve 1.70mm Stainless Steel Mesh.

---

79-5120

### 8in Dia ASTM Sieve 850 Mic Stainless Steel Mesh.

---

79-5160

### 8in Dia ASTM Sieve 425 Mic Stainless Steel Mesh.

---

79-5190

### 8in Dia ASTM Sieve 250 Mic Stainless Steel Mesh.

---

79-5220

### 8in Dia ASTM Sieve 150 Mic Stainless Steel Mesh.

---

79-5260

### 8in Dia ASTM Sieve 75 Mic Stainless Steel Mesh.

---

79-5510

### 8in Dia ASTM Sieve 9.50mm Stainless Steel Mesh.

---

79-5530

### 8in Dia ASTM Sieve 12.5mm Stainless Steel Mesh.

---

79-5560

### 8in Dia ASTM Sieve 19.0mm Stainless Steel Mesh.

---

79-5580

### 8in Dia ASTM Sieve 25.0mm Stainless Steel Mesh.

---

---

79-5610

**8in Dia ASTM Sieve 37.5mm Stainless Steel Mesh.**

---

79-5630

**8in Dia ASTM Sieve 50.0mm Stainless Steel Mesh.**

---

79-5660

**8in Dia ASTM Sieve 75.0mm Stainless Steel Mesh.**

---

81-0140

**Spatula 200 mm**

---

82-0380

**Measuring Cylinder - Glass 100 ml**

---

82-2000

**Evaporating Dish - 150 x 45 mm**

---



## Glass Plate.

Code: [24-0430](#)

Product Group: [Casagrande Method, Determination of Plastic Limit](#)

500 mm square x 10 mm thick.

## Standards

BS 1377-2



## Liquid Limit Device ASTM/ Aashto Hand-Operated W/ Revolution Counter. Supplied Less Grooving Tool.

Code: [24-0434](#)

Product Group: [Casagrande Method](#)

Complete with revolution counter. Supplied less grooving tool.

## Standards

ASTM D4318, AASHTO T89

## Accessories



## ASTM Metal Grooving Tool.

Code: [24-0453](#)



## Casagrande Grooving Tool Aashto

Code: [24-0461](#)



## ASTM Metal Grooving Tool.

Code: [24-0453](#)

Product Group: [Casagrande Method](#)

## Standards

ASTM D4318



## Rod Comparator

Code: [24-0811](#)

Product Group: [Determination of Plastic Limit, Rod Comparator](#)

3mm diameter rod comparator to BS1377.

## Standards

BS 1924-2, EN 1997-2, ASTM D4318, BS 1377, AASHTO T90





## Prong Plate.

Code: [24-1500](#)

Product Group: [Volumetric Shrinkage](#), [Shrinkage](#)  
[Prong Plate](#)

Made of acrylic plastic fitted with three prongs,  
nominal 76 mm square and 2.4 mm thick.

## Standards

BS 1377, ASTM D427, AASHTO T92

## Specification

|              |                                       |
|--------------|---------------------------------------|
| Construction | Acrylic plastic with 3 metal prongs.  |
| Dimensions   | 3" square x 1/8" thick (76 x 3.2 mm). |
| Weight       | Net 1 oz. (28 g).                     |

## Accessories



### Evaporating Dish - 150 x 45 mm

Code: [82-2000](#)



### Measuring Cylinder - Glass 100 ml

Code: [82-0380](#)

## Alternatives



### Glass Cup.

Code: [24-1600](#)



### Shrinkage Dish.

Code: [24-1550](#)



## Shrinkage Dish.

Code: [24-1550](#)


Product Group: [Volumetric Shrinkage](#), [Shrinkage](#)  
[Prong Plate](#)

Nominal 42 mm diameter x 12 mm deep.

## Standards

ASTM D427, AASHTO T92

## Accessories



### Evaporating Dish - 150 x 45 mm

Code: [82-2000](#)



### Measuring Cylinder - Glass 100 ml

Code: [82-0380](#)

## Alternatives



## Glass Cup.

Code: [24-1600](#)



## Prong Plate.

Code: [24-1500](#)



## Glass Cup.

Code: [24-1600](#)

Product Group: [Volumetric Shrinkage](#), [Shrinkage](#)  
[Prong Plate](#)

Nominal 70 mm diameter x 50 mm deep.

## Standards

ASTM D427, AASHTO T92

## Accessories



## Evaporating Dish - 100 x 40 mm

Code: [82-1970](#)



## Measuring Cylinder - Glass 100 ml

Code: [82-0380](#)

## Alternatives



## Prong Plate.

Code: [24-1500](#)



## Shrinkage Dish.

Code: [24-1550](#)



## Pyknometer Complete with Non-Corrodable Cone and Rubber Seal 1Kg Capacity

Code: [24-2885](#)

Product Group: [Particle Density: Pyknometer  
Methods, Pycnometer Top and Jar](#)

Glass jar complete with noncorrodible cone.

## Standards

BS 1377, BS 812-2, EN 1097-7, EN 1997-2, ASTM D854, AASHTO T100, ASTM C128, AASHTO T84

## Accessories



### 100MI Density Bottle with Perforated Stopper.

Code: [24-2950](#)



### 50MI Density Bottle with Perforated Stopper.

Code: [24-2900](#)



### Density Bottle 25ML.

Code: [24-2890](#)



## Pyknometer Gasket

Code: [24-2885/11](#)



## Pyknometer Jar Only

Code: [24-2885/10](#)



## Pyknometer Top

Code: [24-2885/12](#)

## Alternatives



## Sand Absorption Cone.

Code: [42-1700](#)





## Soil Hydrometer Type 151H ASTM D422 Graduated 0.995 to 1.038 Specific Gravity.

Code: [24-4650](#)

Product Group: [ASTM Soil Hydrometers, Soil Hydrometers](#)

Graduated 0.995 to 1.038 g/ml.

## Standards

ASTM D422, ASTM E100, AASHTO T88

## Specification

|              |                          |
|--------------|--------------------------|
| Construction | Molded, seamless.        |
| Scale        | Bouyoucos; double scale. |
| Calibration  | At 68°F.                 |
| Weight       | Net 4 oz. (113 g).       |

## Alternatives



## Soil Hydrometer BS EN DD ENV graduated 0.995 to 1.030 g/ml

Code: [24-4620](#)



## Soil Hydrometer Type 152H ASTM/Aashto Graduated -5 to + 60G/Litre.

Code: [24-4640](#)



## Straight Edge 300mm.

Code: [24-9010](#)

Product Group: [BS/EN compaction test 4.5kg, Proctor compaction, Straightedge](#)

300 mm

## Standards

BS 1377-4, BS 1924-2, ASTM D698, ASTM D1557, AASHTO T99, EN 13286-2, EN 13286-4, ASTM D1883, AASHTO T193, ASTM D558, ASTM D559, ASTM D560, AASHTO T134, AASHTO T135, AASHTO T136, AASHTO T180

## Specification

|              |                                       |
|--------------|---------------------------------------|
| Construction | Flat ground tool steel; beveled edge. |
| Dimensions   | L x W x T (300mm x 40mm x 6mm).       |
| Weight       | 550g                                  |

## Accessories



## ASTM Compaction Rammer 2.5Kg.

Code: [24-9063](#)

## Alternatives



### ASTM Compaction Rammer 2.5Kg.

Code: [24-9063](#)



## Proctor Mould

Code: [24-9060](#)

Product Group: [Accessories for ASTM and Proctor compaction](#), [Proctor compaction](#)

## Standards

ASTM D558, ASTM D559, ASTM D560, ASTM D698, ASTM D1557, AASHTO T99, AASHTO T134, AASHTO T135, AASHTO T136, AASHTO T180

## Specification

|                     |                                                   |
|---------------------|---------------------------------------------------|
| Dimensions          | 101.6 mm dia x 116.4 mm high                      |
| Rammer Mould Volume | 1/30 ft <sup>3</sup>                              |
| Construction        | All steel, threaded studs with wing nuts, plated. |
| Weight              | 5.4 kg                                            |



## ASTM Compaction Rammer 2.5Kg.

Code: [24-9063](#)

Product Group: [Proctor compaction, Standard Compaction Hammer](#)

50.8mm diameter x 305mm deep.

## Standards

ASTM D1557, AASHTO T180, ASTM D558, ASTM D559, ASTM D560, ASTM D698, AASHTO T99, AASHTO T134, AASHTO T135, AASHTO T136

## Specification

|              |                                                       |
|--------------|-------------------------------------------------------|
| Hammer       | 2" diam. (50.8 mm); 5-1/2 lbs. (2.49 kg).             |
| Drop         | 12 " (305 mm).                                        |
| Guide Sleeve | Machined steel tubing with air pressure release holes |
| Finish       | Corrosion resistant                                   |
| Weight       | 4.1 kg (9 lbs)                                        |

## Accessories



## ASTM/Modified Proctor Compaction Rammer 4.5Kg.

Code: [24-9070](#)

# Product Sheet

www.ele.com  
+44 (0) 01525 249 200



## Straight Edge 300mm.

Code: [24-9010](#)

---

## Alternatives



## ASTM/Modified Proctor Compaction Rammer 4.5Kg.

Code: [24-9070](#)

---



## Straight Edge 300mm.

Code: [24-9010](#)



## ASTM Compaction Mould 152mm.

Code: 24-9066

Product Group: Accessories for ASTM and Proctor compaction, ASTM/Modified Proctor compaction

152mm inside diameter

## Standards

ASTM D698, ASTM D1557, AASHTO T99, AASHTO T180

## Specification

|                     |                                                   |
|---------------------|---------------------------------------------------|
| Dimensions          | 152.4 mm dia x 116.4 mm high                      |
| Rammer Mould Volume | 1/13.33 ft <sup>3</sup>                           |
| Construction        | All steel, threaded studs with wing nuts, plated. |
| Weight              | 8.2 kg                                            |



## ASTM/Modified Proctor Compaction Rammer 4.5Kg.

Code: [24-9070](#)

Product Group: [ASTM/Modified Proctor compaction, Modified Compaction Hammer](#)

50.8mm diameter x 457.2 mm drop.

## Standards

ASTM D1557, AASHTO T180

## Specification

|              |                                                                                 |
|--------------|---------------------------------------------------------------------------------|
| Hammer       | 2" diam. (50.8 mm); 10 lbs. (4.5 kg).                                           |
| Drop         | 18" (457.2 mm).                                                                 |
| Guide Sleeve | Machined steel tubing with integrally spun end cap; air pressure release holes. |
| Finish       | Corrosion resistant                                                             |
| Weight       | Net 6.3 kg (14 lbs)                                                             |

## Accessories



## ASTM Compaction Rammer 2.5Kg.

Code: [24-9063](#)

## Alternatives





### ASTM Compaction Rammer 2.5Kg.

Code: [24-9063](#)



## Cbr-Test 50 Machine 50kN Capacity BS and ASTM Supplied with Stabilising Bar.

Code: [24-9150/06](#)

Product Group: [CBR Load Frames](#)

- Single speed machine (BS/EN and ASTM)
- Rapid platen adjustment
- Complete with stabilising bar
- Compact, bench-mounting design
- Options for mechanical or electronic measurement

Designed for performing laboratory CBR tests to BS 1377, EN13286-47 and ASTM D1883, this bench mounting machine comprises a twin column frame incorporating a motorised drive system. Rapid adjustment of the platen is provided, which enables daylight to be taken up quickly and also close control of application of a seating load.

## Specification

|                        |                     |
|------------------------|---------------------|
| Dimensions (l x w x h) | 550 x 400 x 1220 mm |
| Max vertical clearance | 800 mm              |
| Horizontal clearance   | 255 mm              |
| Platen diameter        | 133 mm              |
| Platen travel          | 105 mm              |
| Weight kg              | 80                  |

## Accessories



### 50kN Clamped Boss Load Ring

Code: [78-0860](#)



### 50kN S-type Load Cell

Code: [27-1559](#)



### ASTM Cbr Mould Complete with Collar & Perforated Base

Code: [24-9228](#)




## Bracket and Adaptor. Dual Purpose Mounting Bracket for CBR Penetration Gauges EL24-9184/EL24-9186

Code: [24-9188](#)




## BS Cbr Mould Body.

Code: [24-9198](#)



## BS Extension Collar

Code: [24-9200](#)



## BS Solid Base or Top Plate

Code: [24-9204](#)



## Cbr Penetration Piston (Adjustable).

Code: [24-9183](#)



## CBR Penetration Transducer 50mm Travel Fitted with 5 Pin Din Plug.

Code: [27-1705](#)



## Clamped Boss Load Ring - 10.0 kN

Code: [78-0460](#)



## Clamped Boss Load Ring - 2.0 kN

Code: [78-0060](#)



## Clamped Boss Load Ring - 28.0 kN

Code: [78-0760](#)



## Penetration Dial Gauge BS

Code: [24-9186](#)



## Penetration Piston

Code: [24-9182](#)



## Penetration/Swell Dial Gauge ASTM.

Code: [24-9184](#)

## Alternatives



## CBR-Test 50 Machine 50 kN Capacity BS and ASTM Supplied with Stabilising Bar.

Code: [24-9150/02](#)



## Cbr-Test 50 Machine 50kN Capacity BS and ASTM Supplied with Stabilising Bar.

Code: [24-9150/06](#)



## Cbr-Test 50 Machine 50kN Capacity BS and ASTM Supplied with Stabilising Bar.

Code: [24-9150/01](#)



## MultiPlex 50 Load Frame

Code: [25-3700/01](#)



## Adaptor kit, to perform CBR on the Tritest 50 load frame

Code: [25-3518/10](#)

Product Group: [CBR Load Frames](#)

Contains a platen adaptor and a stabilising bar



## 100 Litre Drying Oven

Code: [78-1225/01](#)

Product Group: [Oven Drying Method](#), [Oven Drying Method](#), [Oven Drying Method](#)

## Standards

BS 2648, BS 598, BS 1377, BS 1924

## Further Information

**\*\*NOT AVAILABLE FOR SALE IN THE USA\*\***

## Alternatives



## 150 Litre Drying Oven

Code: [78-1235/01](#)



## 225 Litre Drying Oven

Code: [78-1250/01](#)



## 50 Litre Drying Oven

Code: [78-1215/01](#)



## Drying Oven 425 Litre Capacity

Code: [78-0135/01](#)





## 8in Dia ASTM Sieve 4.75mm Stainless Steel Mesh.

Code: 79-5020

Product Group: 8in Dia ASTM Brass Sieves, 8" Diameter ASTM Sieves, 8" Diameter ASTM Sieves, 8" Diameter ASTM Sieves

## Standards

ASTM E11

## Specification

|                                 |                                                                          |
|---------------------------------|--------------------------------------------------------------------------|
| Frames                          | Full height; 2 1/4" (51 mm) depth to mesh.                               |
| Construction                    | Polished and lacquered brass with S.S. mesh.                             |
| Nameplates                      | Show standard, alternate and Tyler Screen Scale equivalent designations. |
| Weights                         | Net 1 lb. (453 g).                                                       |
| Sieve Size or Number            | No. 4                                                                    |
| Sieve Opening Standard          | 4.75 mm                                                                  |
| Sieve Opening Alternative (in.) | 0.187                                                                    |



## 8in Dia ASTM Sieve 1.70mm Stainless Steel Mesh.

Code: 79-5080

Product Group: 8in Dia ASTM Brass Sieves, 8" Diameter ASTM Sieves, 8" Diameter ASTM Sieves, 8" Diameter ASTM Sieves

## Standards

ASTM E11

## Specification

|                                 |                                                                          |
|---------------------------------|--------------------------------------------------------------------------|
| Frames                          | Full height; 2 1/4" (51 mm) depth to mesh.                               |
| Construction                    | Polished and lacquered brass with S.S. mesh.                             |
| Nameplates                      | Show standard, alternate and Tyler Screen Scale equivalent designations. |
| Weights                         | Net 1 lb. (453 g).                                                       |
| Sieve Size or Number            | No. 12                                                                   |
| Sieve Opening Standard          | 1.70 mm                                                                  |
| Sieve Opening Alternative (in.) | 0.0661                                                                   |



## 8in Dia ASTM Sieve 850 Mic Stainless Steel Mesh.

Code: 79-5120

Product Group: 8in Dia ASTM Brass Sieves, 8" Diameter ASTM Sieves, 8" Diameter ASTM Sieves, 8" Diameter ASTM Sieves

## Standards

ASTM E11

## Specification

|                                 |                                                                          |
|---------------------------------|--------------------------------------------------------------------------|
| Frames                          | Full height; 2 1/4" (51 mm) depth to mesh.                               |
| Construction                    | Polished and lacquered brass with S.S. mesh.                             |
| Nameplates                      | Show standard, alternate and Tyler Screen Scale equivalent designations. |
| Weights                         | Net 1 lb. (453 g).                                                       |
| Sieve Size or Number            | No. 20                                                                   |
| Sieve Opening Standard          | 850 um                                                                   |
| Sieve Opening Alternative (in.) | 0.331                                                                    |



## 8in Dia ASTM Sieve 425 Mic Stainless Steel Mesh.

Code: 79-5160

Product Group: 8in Dia ASTM Brass Sieves, 8" Diameter ASTM Sieves, 8" Diameter ASTM Sieves, 8" Diameter ASTM Sieves

## Standards

ASTM E11

## Specification

|                                 |                                                                          |
|---------------------------------|--------------------------------------------------------------------------|
| Frames                          | Full height; 2 1/4" (51 mm) depth to mesh.                               |
| Construction                    | Polished and lacquered brass with S.S. mesh.                             |
| Nameplates                      | Show standard, alternate and Tyler Screen Scale equivalent designations. |
| Weights                         | Net 1 lb. (453 g).                                                       |
| Sieve Size or Number            | No. 40                                                                   |
| Sieve Opening Standard          | 425 um                                                                   |
| Sieve Opening Alternative (in.) | 0.0165                                                                   |



## 8in Dia ASTM Sieve 250 Mic Stainless Steel Mesh.

Code: 79-5190

Product Group: 8in Dia ASTM Brass Sieves, 8" Diameter ASTM Sieves, 8" Diameter ASTM Sieves, 8" Diameter ASTM Sieves

## Standards

ASTM E11

## Specification

|                                 |                                                                          |
|---------------------------------|--------------------------------------------------------------------------|
| Frames                          | Full height; 2 1/4" (51 mm) depth to mesh.                               |
| Construction                    | Polished and lacquered brass with S.S. mesh.                             |
| Nameplates                      | Show standard, alternate and Tyler Screen Scale equivalent designations. |
| Weights                         | Net 1 lb. (453 g).                                                       |
| Sieve Size or Number            | No. 60                                                                   |
| Sieve Opening Standard          | 250 um                                                                   |
| Sieve Opening Alternative (in.) | 0.0098                                                                   |



## 8in Dia ASTM Sieve 150 Mic Stainless Steel Mesh.

Code: 79-5220

Product Group: 8in Dia ASTM Brass Sieves, 8" Diameter ASTM Sieves, 8" Diameter ASTM Sieves, 8" Diameter ASTM Sieves

## Standards

ASTM E11

## Specification

|                                 |                                                                          |
|---------------------------------|--------------------------------------------------------------------------|
| Frames                          | Full height; 2 1/4" (51 mm) depth to mesh.                               |
| Construction                    | Polished and lacquered brass with S.S. mesh.                             |
| Nameplates                      | Show standard, alternate and Tyler Screen Scale equivalent designations. |
| Weights                         | Net 1 lb. (453 g).                                                       |
| Sieve Size or Number            | No. 100                                                                  |
| Sieve Opening Standard          | 150 um                                                                   |
| Sieve Opening Alternative (in.) | 0.0059                                                                   |



## 8in Dia ASTM Sieve 75 Mic Stainless Steel Mesh.

Code: 79-5260

Product Group: 8in Dia ASTM Brass Sieves, 8" Diameter ASTM Sieves, 8" Diameter ASTM Sieves, 8" Diameter ASTM Sieves

## Standards

ASTM E11

## Specification

|                                 |                                                                          |
|---------------------------------|--------------------------------------------------------------------------|
| Frames                          | Full height; 2 1/4" (51 mm) depth to mesh.                               |
| Construction                    | Polished and lacquered brass with S.S. mesh.                             |
| Nameplates                      | Show standard, alternate and Tyler Screen Scale equivalent designations. |
| Weights                         | Net 1 lb. (453 g).                                                       |
| Sieve Size or Number            | No. 200                                                                  |
| Sieve Opening Standard          | 75 um                                                                    |
| Sieve Opening Alternative (in.) | 0.0029                                                                   |



## 8in Dia ASTM Sieve 9.50mm Stainless Steel Mesh.

Code: 79-5510

Product Group: 8in Dia ASTM Brass Sieves, 8" Diameter ASTM Sieves, 8" Diameter ASTM Sieves, 8" Diameter ASTM Sieves

## Standards

ASTM E11

## Specification

|                                 |                                                                          |
|---------------------------------|--------------------------------------------------------------------------|
| Frames                          | Full height; 2 1/8" (51 mm) depth to mesh.                               |
| Construction                    | Polished and lacquered brass with S.S. mesh.                             |
| Nameplates                      | Show standard, alternate and Tyler Screen Scale equivalent designations. |
| Weights                         | Net 1 lb. (453 g).                                                       |
| Sieve Size or Number            | 3/8"                                                                     |
| Sieve Opening Standard          | 9.5 mm                                                                   |
| Sieve Opening Alternative (in.) | 0.375                                                                    |





## 8in Dia ASTM Sieve 12.5mm Stainless Steel Mesh.

Code: 79-5530

Product Group: 8in Dia ASTM Brass Sieves, 8" Diameter ASTM Sieves, 8" Diameter ASTM Sieves, 8" Diameter ASTM Sieves

## Standards

ASTM E11

## Specification

|                                 |                                                                          |
|---------------------------------|--------------------------------------------------------------------------|
| Frames                          | Full height; 2 1/4" (51 mm) depth to mesh.                               |
| Construction                    | Polished and lacquered brass with S.S. mesh.                             |
| Nameplates                      | Show standard, alternate and Tyler Screen Scale equivalent designations. |
| Weights                         | Net 1 lb. (453 g).                                                       |
| Sieve Size or Number            | 1/2"                                                                     |
| Sieve Opening Standard          | 12.5 mm                                                                  |
| Sieve Opening Alternative (in.) | 0.5                                                                      |



## 8in Dia ASTM Sieve 19.0mm Stainless Steel Mesh.

Code: 79-5560

Product Group: 8in Dia ASTM Brass Sieves, 8" Diameter ASTM Sieves, 8" Diameter ASTM Sieves, 8" Diameter ASTM Sieves

## Standards

ASTM E11

## Specification

|                                 |                                                                          |
|---------------------------------|--------------------------------------------------------------------------|
| Frames                          | Full height; 2 1/4" (51 mm) depth to mesh.                               |
| Construction                    | Polished and lacquered brass with S.S. mesh.                             |
| Nameplates                      | Show standard, alternate and Tyler Screen Scale equivalent designations. |
| Weights                         | Net 1 lb. (453 g).                                                       |
| Sieve Size or Number            | 3/4"                                                                     |
| Sieve Opening Standard          | 19.0 mm                                                                  |
| Sieve Opening Alternative (in.) | 0.75                                                                     |



## 8in Dia ASTM Sieve 25.0mm Stainless Steel Mesh.

Code: 79-5580

Product Group: 8in Dia ASTM Brass Sieves, 8" Diameter ASTM Sieves, 8" Diameter ASTM Sieves, 8" Diameter ASTM Sieves

## Standards

ASTM E11

## Specification

|                                 |                                                                          |
|---------------------------------|--------------------------------------------------------------------------|
| Frames                          | Full height; 2 1/4" (51 mm) depth to mesh.                               |
| Construction                    | Polished and lacquered brass with S.S. mesh.                             |
| Nameplates                      | Show standard, alternate and Tyler Screen Scale equivalent designations. |
| Weights                         | Net 1 lb. (453 g).                                                       |
| Sieve Size or Number            | 1"                                                                       |
| Sieve Opening Standard          | 25.0 mm                                                                  |
| Sieve Opening Alternative (in.) | 1                                                                        |



## 8in Dia ASTM Sieve 37.5mm Stainless Steel Mesh.

Code: 79-5610

Product Group: 8in Dia ASTM Brass Sieves, 8" Diameter ASTM Sieves, 8" Diameter ASTM Sieves, 8" Diameter ASTM Sieves

## Standards

ASTM E11

## Specification

|                                 |                                                                          |
|---------------------------------|--------------------------------------------------------------------------|
| Frames                          | Full height; 2 1/2" (51 mm) depth to mesh.                               |
| Construction                    | Polished and lacquered brass with S.S. mesh.                             |
| Nameplates                      | Show standard, alternate and Tyler Screen Scale equivalent designations. |
| Weights                         | Net 1 lb. (453 g).                                                       |
| Sieve Size or Number            | 1-1/2"                                                                   |
| Sieve Opening Standard          | 38.1 mm                                                                  |
| Sieve Opening Alternative (in.) | 1.5                                                                      |



## 8in Dia ASTM Sieve 50.0mm Stainless Steel Mesh.

Code: 79-5630

Product Group: 8in Dia ASTM Brass Sieves, 8" Diameter ASTM Sieves, 8" Diameter ASTM Sieves, 8" Diameter ASTM Sieves

## Standards

ASTM E11

## Specification

|                                 |                                                                          |
|---------------------------------|--------------------------------------------------------------------------|
| Frames                          | Full height; 2 1/4" (51 mm) depth to mesh.                               |
| Construction                    | Polished and lacquered brass with S.S. mesh.                             |
| Nameplates                      | Show standard, alternate and Tyler Screen Scale equivalent designations. |
| Weights                         | Net 1 lb. (453 g).                                                       |
| Sieve Size or Number            | 2"                                                                       |
| Sieve Opening Standard          | 50 mm                                                                    |
| Sieve Opening Alternative (in.) | 2                                                                        |



## 8in Dia ASTM Sieve 75.0mm Stainless Steel Mesh.

Code: 79-5660

Product Group: 8in Dia ASTM Brass Sieves, 8" Diameter ASTM Sieves, 8" Diameter ASTM Sieves, 8" Diameter ASTM Sieves

## Standards

ASTM E11

## Specification

|                                 |                                                                          |
|---------------------------------|--------------------------------------------------------------------------|
| Frames                          | Full height; 2 1/4" (51 mm) depth to mesh.                               |
| Construction                    | Polished and lacquered brass with S.S. mesh.                             |
| Nameplates                      | Show standard, alternate and Tyler Screen Scale equivalent designations. |
| Weights                         | Net 1 lb. (453 g).                                                       |
| Sieve Size or Number            | 3"                                                                       |
| Sieve Opening Standard          | 75 mm                                                                    |
| Sieve Opening Alternative (in.) | 3                                                                        |



## Spatula 200 mm

Code: [81-0140](#)

Product Group: [Determination of Plastic Limit, Spatulas](#)

## Further Information

**\*\*NOT AVAILABLE FOR SALE IN THE USA\*\***

## Accessories



## Vibrating Hammer

Code: [47-0455/01](#)

## Alternatives



## Vibrating Hammer

Code: [47-0455/01](#)



## Measuring Cylinder - Glass 100 ml

Code: [82-0380](#)

Product Group: [Measuring Cylinders, BS, Volumetric Shrinkage](#)

Soda glass, spouted, BS EN 4788.

## Further Information

**\*\*NOT AVAILABLE FOR SALE IN THE USA\*\***





## Evaporating Dish - 150 x 45 mm

Code: [82-2000](#)

Product Group: [Evaporating Dishes, Volumetric Shrinkage](#)

Shallow form with spout, porcelain 150 x 45 mm nominal diameter x height.

## Further Information

**\*\*NOT AVAILABLE FOR SALE IN THE USA\*\***