

















IF IT'S WORTH BUILDING, IT'S WORTH TESTING

# **Contents**

www.ele.com +44 (0) 01525 249 200



This wishlist was generated on 23/08/2019, and contains the following Products:

36-0695/02

Accu-Tek Touch 250 Compression Machine 110V/60Hz

37-5570

**Frame Stand** 







#### **Accu-Tek Touch 250 Compression** Machine 110V/60Hz

Code: 36-0695/02

Product Group: Accu-Tek Touch 250 Series

#### **Standards**

ASTM C39, AASHTO T22

#### **Further Information**

110vAC, 60 Hz, 1ø.

#### **Specification**

Capacity 250,000 lbf (1,112 kN)

Frame Upper and lower steel plate

sections with four steel

uprights, threaded and welded

into place; 14 .75" w.

x 12 " d. x 37" h. (375 x 305 x

940 mm).

6-1/8" (155 mm) diameter; 3" Ram

(76 mm) travel.

**Upper Platen** Swivel seat type; 6-1/4" (15 9

mm) diameter.

Lower Platen 7" (178 mm) diameter.

12 -1/2" (31 8 mm); or 14 -1/2" Vetical Clearance

(368 mm) with lower spacer removed - (Upper and Lower

platens installed).

Horizontal Clearance 9" (22 9 mm) between uprights.

1 h.p. (0.7kw) electro-hydraulic Pump

pump mounted within reservoir with overload protection.

Pump-mounted pressure

Conrols compensated flow control

www.ele.com +44 (0)1525 249 200 **= +1 (800) 323 1242** 

www.ele.com +44 (0) 01525 249 200



valve with 4-position control lever and adjustable flow valve.

Pump On/Off switch.

Display 5.7" (145 mm) touch screen

display, incorporating full key pad (QWERTY type); pace deviation bargraph; automatic stress calculation; 2 GB of internal memory for storing thousands of test results; download data to PC via USB or to printer via RS-232

interface.

Range 2,500 to 25 0,000 lbf. (11 .2 to

1,112 kN).

Accuracy Factory calibrated to within

0.5% of reading

- from 1% to 100% of machine

capacity.

Overall Dimensions 25 .5" w. x 12 " d. x 45 " h. (648

x 305 x 1,143 mm).

Weight Net 535 lbs. (243 kg).

#### **Accessories**



**6" Retaining Caps** 

Code: 34-6134



**Flexural Attachment** 

Code: 37-5528



**Frame Stand** 

Code: 37-5570

www.ele.com # +44 (0)1525 249 200 # +1 (800) 323 1242 Page 4 of 9







## Pedestal for Testing 4" x 8" Cylinders

Code: 37-5561



#### Platen Set for 2" Cube

Code: 37-5514



## Platen Set for 3" x 6" Cylinders

Code: 37-5508



### Platen set for 6" Cube

Code: 37-5516



### Platen Set for 8" x 8" x 16" blocks

Code: 37-5522







### **Portable Impact Tape Printer**

Code: 37-4862/02

## Spares/Consumables



#### **Accutek Oil**

Code: 9806-0016



#### Ram Seal Kit - Accu-Tek 250

Code: CT-992

#### **Alternatives**



### **Accu-Tek Touch 250 Series Compression Machine** 220V/50Hz

Code: 36-0690/01



### **Accu-Tek Touch 250 Series Compression Machine** 220V/60Hz

Code: 36-0690/06

**= +1 (800) 323 1242** Page 6 of 9 www.ele.com







## Accu-Tek Touch 350 Compression Machine 110V/60Hz

Code: 36-0740/02



#### Accu-Tek Touch 350 Series 110V/60Hz

Code: 36-0735/02



### Accu-Tek Touch 350 Series 220V/50Hz

Code: 36-0735/01



### Accu-Tek Touch 350 Series 220V/60Hz

Code: 36-0735/06

+44 (0)1525 249 200

**= +1 (800) 323 1242** 







#### Accu-Tek Touch 500 Series 110V/60Hz

Code: 36-3095/02



### Accu-Tek Touch 500 Series 220V/50Hz

Code: 36-3095/01



### Accu-Tek Touch 500 Series 220V/60Hz

Code: 36-3095/06

www.ele.com # +44 (0)1525 249 200 # +1 (800) 323 1242

Page 8 of 9





Page 9 of 9



### **Frame Stand**

Code: 37-5570

Product Group: Frame Stands, Accu-Tek Touch 250

**Series** 

Frame Stand for Accu-Tek 250 series compression

machines.

## **Specification**

Construction Steel; with shelf and mounting

holes for frame and floor bolting. Mounting bolts

included.

Dimensions 20-1/2" w. x 17-1/2" d. x 15 " h.

(520 x 444 x 381 mm).

Weight Net 85 lbs. (38.5 kg).

#### **Accessories**



#### **Frame Stand**

Code: 37-5575

#### **Alternatives**



#### **Frame Stand**

Code: 37-5575

www.ele.com # +44 (0)1525 249 200 # +1 (800) 323 1242