



IF IT'S WORTH BUILDING, IT'S WORTH TESTING

# Contents

[www.ele.com](http://www.ele.com)  
+44 (0) 01525 249 200



This wishlist was generated on 08/11/2019, and contains the following Products:

---

[25-3518/01](#)

**Digital Tritest 50 Load Frame**

---

[81-0240](#)

**Shovel - With flat blade**

---



## Digital Tritest 50 Load Frame

Code: 25-3518/01

Product Group: Digital Tritest 50 Load Frame, CBR Load Frames, Triaxial Load Frames

- Microprocessor control
- Large on-board LED screen display
- Direct entry via a touch sensitive keyboard
- Rapid approach and return to datum of platen
- Fully variable speed, 0.00001 to 9.99999 mm/min
- Samples up to 100 mm diameter

This 50 kN capacity machine, designed primarily for triaxial testing of soil specimens up to 100 mm diameter x 200 mm long, comprises a rigid twin column construction with an integral fully variable microprocessor controlled drive unit and LCD display with a touch sensitive keyboard. The machine is normally bench mounted for ease of installation and operation.

The use of a microprocessor controlled drive system and keyboard entry provides the Digital Tritest 50 with a wide variety of features which include pause and speed reset during test, RS 232C, operator programming of speed and control functions, self test diagnostics and many other features.

A robustly constructed steel case houses the motor drive system with careful attention being given to the prevention of ingress of water or grit. All operating controls are mounted on the front panel of the machine, which is angled and recessed to prevent physical and environmental damage.

## Standards

BS 1377-7, BS 1377-8, BS 1924-2, ASTM D1883, ASTM D2166, ASTM D2850, ASTM D4767, ASTM D7181, AASHTO T99, AASHTO T134, AASHTO T135, AASHTO T136, AASHTO T180, AASHTO T193, AASHTO T208, AASHTO T296, AASHTO T297

## Further Information

Complete with RS 232C interface.

## Specification

Capacity	50kN (11,200 lbf).
Speed Range	English mode: 0.000001 to 0.399999 in/min. Metric mode: 0.00001 to 9.99999 mm/min.
Rapid Approach Speed	1.0 in/min. (25 mm/min.).

# Product Sheet

www.ele.com  
+44 (0) 01525 249 200



Platen Travel	100mm (3.9"); limit switch protection.
Platen Diameter	133 mm (5.2")
Vertical Clearance	910 mm, (36 .8") maximum; 305mm, (12") minimum.
Horizontal Clearance	364mm, (15 .3").
Serial Interface	RS232C; programmable baud rate and protocol.
Overall Dimensions	500 x 500 x 1,470 mm, (19.7" w. x 19.7" d. x 57.8" h).
Weight	Net 100kg (220 lbs); Shpg. 136kg (300 lbs).

## Accessories



### 50kN Clamped Boss Load Ring

Code: [78-0860](#)



### Adaptor kit, to perform CBR on the Tritest 50 load frame

Code: [25-3518/10](#)



### Clamped Boss Load Ring - 10.0 kN

Code: [78-0460](#)



### Clamped Boss Load Ring - 28.0 kN

Code: [78-0760](#)



## Clamped Boss Load Ring - 3.0 kN

Code: [78-0160](#)

---



## Clamped Boss Load Ring - 4.5 kN

Code: [78-0260](#)

---

## Alternatives



## MultiPlex 50 Load Frame

Code: [25-3700/01](#)

---



## Versa-Loader

Code: [25-3525/02](#)



## Shovel - With flat blade

Code: [81-0240](#)

Product Group: [Scoops and Shovels](#)

## Further Information

**\*\*NOT AVAILABLE FOR SALE IN THE USA\*\***