



IF IT'S WORTH BUILDING, IT'S WORTH TESTING

This wishlist was generated on 01/12/2019, and contains the following Products:

24-4125/01

High Speed Stirrer Complete with Paddle Cup & Baffle. 220-240V 50/60Hz 1Ph.

24-4125/10

Mixing Paddle for 24-4125 Series High Speed Stirrer

24-4125/11

Soil Dispersion Cup & Baffle.

24-4145

Sodium Hexametaphosphate 500G.

24-4919

Sand Equivalent Apparatus ASTM Aashto with Carrying Case.

24-4925

5 Litre Syphon Assembly with Connection for 5mm Id Tubing.

24-4930

Calcium Chloride 2.5Kg.

25-0408

Set of Weights 100Kg Total Weight.

25-0429

Floor Mounting Stand.

25-0479

Consolidation Cell Complete 2.5 Inch Diameter Sample. Inc. Porous Discs and Cutting Ring.

25-0479/13

2.5 Inch Dia Upper and Lower Porous Stones for Use on EL25-0479 Series Cell.

26-2114/02

Digital Direct/Residual Shear Apparatus Complete with Lever Loading Assembly. 110-120V 50/60Hz 1Ph.

79-5230

8in Dia ASTM Sieve No.120 (125 Mic) Stainless Steel Mesh.

79-5310

Contents

www.ele.com
+44 (0) 01525 249 200



8in Dia ASTM Sieve 20 micron Stainless Steel Mesh

79-5400

8 Inch Dia Lid.

79-5410

8in Dia Receiver.



High Speed Stirrer Complete with Paddle Cup & Baffle. 220-240V 50/60Hz 1Ph.

Code: [24-4125/01](#)

Product Group: [Mechanical Analysis Stirrer](#)

Compact bench top stirrer used for dispersing soil samples in water. Supplied complete with mixing paddle and dispersion cup with baffle. Beaker position maintained by column retainer.

Standards

BS 1377, ASTM D422, AASHTO T88

Accessories



Sodium Hexametaphosphate 500G.

Code: [24-4145](#)

Spares/Consumables



Mixing Paddle for 24-4125 Series High Speed Stirrer

Code: [24-4125/10](#)



Soil Dispersion Cup & Baffle.

Code: [24-4125/11](#)



Mixing Paddle for 24-4125 Series High Speed Stirrer

Code: [24-4125/10](#)

Product Group: [Mechanical Analysis Stirrer](#)

Standards

BS 1377, ASTM D422, AASHTO T88



Soil Dispersion Cup & Baffle.

Code: [24-4125/11](#)

Product Group: [Mechanical Analysis Stirrer](#)

Standards

BS 1377, ASTM D422, AASHTO T88



Sodium Hexametaphosphate 500G.

Code: [24-4145](#)

Product Group: [Sodium Hexametaphosphate,](#)
[Mechanical Analysis Stirrer](#)

Standards

ASTM D422, AASHTO T88, ASTM E100

Spares/Consumables



Solid Rubber Stopper

Code: [4699-0881](#)



Sand Equivalent Apparatus ASTM Aashto with Carrying Case.

Code: [24-4919](#)

Product Group: [Sand Equivalent Value](#), [Sand Equivalent Value](#)

Set Includes:

- 4 Plastic measuring cylinders
- 1 Carrying case
- 1 Weighted foot assembly
- 1 Irrigator tube
- 1 Rubber tubing complete with pinch clip
- 1 Funnel.

Standards

ASTM D2419, AASHTO T176

Accessories



5 Litre Syphon Assembly with Connection for 5mm Id Tubing.

Code: [24-4925](#)



Calcium Chloride 2.5Kg.

Code: [24-4930](#)



Formaldehyde 36% Aqueous Solution 2.5 Litre.

Code: [24-4932](#)



Glycerol Analar 2.5 Litre

Code: [24-4934](#)



5 Litre Syphon Assembly with Connection for 5mm Id Tubing.

Code: [24-4925](#)

Product Group: [Sand Equivalent Value](#), [Sand Equivalent Value](#)

With 5 litre polythene bottle. Supplied without rubber tubing.

Standards

ASTM D2419, AASHTO T176

Further Information

****NOT AVAILABLE FOR SALE IN THE USA****



Calcium Chloride 2.5Kg.

Code: [24-4930](#)

Product Group: [Sand Equivalent Value](#), [Sand Equivalent Value](#)

Standards

ASTM D2419, AASHTO T176

Further Information

****NOT AVAILABLE FOR SALE IN THE USA****



Set of Weights 100Kg Total Weight.

Code: [25-0408](#)

Product Group: [Consolidation Apparatus](#)

9 x 10 kg, 1 x 5 kg, 2 x 2 kg, 1 x 1 kg.

Standards

ASTM D2435, ASTM D4546, AASHTO T216, ASTM D3877, BS 1377-5



Floor Mounting Stand.

Code: [25-0429](#)

Product Group: [Consolidation Apparatus](#), [Table Top Consolidation Apparatus](#)

A versatile modular steel stand. Holes in the shelf are provided for securing up to three EL25-0402 Consolidation Frames. Dimensions 610 x 915 x 865 mm (l x w x h).

Standards

ASTM D2435, ASTM D4546, AASHTO T216, ASTM D3877, BS 1377-5



Consolidation Cell Complete 2.5 Inch Diameter Sample. Inc. Porous Discs and Cutting Ring.

Code: [25-0479](#)

Product Group: [Table Top Consolidation Apparatus](#), [ASTM/AASHTO consolidation cells and accessories](#), [Pneumatic Consolidation Apparatus](#), [Fixed Ring Consolidation](#)

Standards

ASTM D2435, ASTM D4546, AASHTO T216, ASTM D3877

Specification

Application	ASTM
Specimen Dia	2.5 inch
Specimen area	4.909 inch ²
Beam ratio	10:1
Load kg	1.55
Stress	1000 lbf/ft ²
Typical max stress	103 200 lbf/ft ²
Stress for 1 kg m ²	645 lbf/ft ²

Accessories



2.5" Floating Ring Consolidometer

Code: [25-0530](#)



Calibration Disc 2.5 Inch Cell

Code: [25-0485](#)



Consolidation Cell Complete 50mm Diameter Sample.

Code: [25-0455](#)



Consolidation Cell/ Oedometer Complete 75mm Diameter Sample

Code: [25-0503](#)

Spares/Consumables



2.5 Inch Dia Upper and Lower Porous Stones for Use on EL25-0479 Series Cell.

Code: [25-0479/13](#)



Cutting Ring for 25-0479

Code: [25-0482](#)

Alternatives



2.5" Floating Ring Consolidometer

Code: [25-0530](#)



Calibration Disc 2.5 Inch Cell

Code: [25-0485](#)



Consolidation Cell Complete 50mm Diameter Sample.

Code: [25-0455](#)



Consolidation Cell/ Oedometer Complete 75mm Diameter Sample

Code: [25-0503](#)



2.5 Inch Dia Upper and Lower Porous Stones for Use on EL25-0479 Series Cell.

Code: [25-0479/13](#)

Product Group: [ASTM/AASHTO consolidation cells and accessories](#), [Fixed Ring Consolidation](#)

Standards

ASTM D2435, ASTM D4546, AASHTO T216, ASTM D3877

Accessories



Consolidation Cell Complete 2.5 Inch Diameter Sample. Inc. Porous Discs and Cutting Ring.

Code: [25-0479](#)



Digital Direct/Residual Shear Apparatus Complete with Lever Loading Assembly. 110-120V 50/60Hz 1Ph.

Code: 26-2114/02

Product Group: Direct/Residual Shear Apparatus,
Direct/Residual Shear Apparatus

- Microprocessor control
- Large on-board LCD screen display
- Direct entry via touch sensitive keyboard
- Rapid approach and return to start datum
- Fully variable speed, 0.00001 to 9.99999 mm/minute
- Accepts specimens up to 100 mm square

The ELE Direct Shear Apparatus accepts specimens 60 mm, 100 mm square or 2.5 inches in diameter. The use of a microprocessor controlled drive system and keyboard entry gives the apparatus a wide range of features that include pause and speed reset during test, RS 232C interface, operator programming of speed and control functions, self test diagnostics and many other features. A return to start datum provides a positive means of reversing the shearbox when either preparing for a new test or continuing with residual testing procedures.

Safety forward/reverse travel limit switches are fitted as standard and monitored through the electronics system control.

The electronics are housed in a modern moulded shroud, which includes a large LCD display and keyboard entry. The apparatus is enclosed in a robustly constructed case, has been designed for floor mounting and is supplied complete with carriage, loading hanger and 10:1 lever loading device

Standards

ASTM D3080, AASHTO T236

Further Information

for 110 - 120 V AC, 50 - 60 Hz, 1 ph.

Specification

Sample Size

Accepts either 2.42", 2.5" diam.; 60 mm square samples using accessory shear box assemblies, not included.

Speed Range

Variable in either English or Metric units between

Shear Force	0.000001"
Vertical Load	(0.00001 mm) to 0.399999" (9.99999 mm) per minute.
Dimensions	1,100lbf. (5.0 kN) maximum. 2,200 lbf. (10.0 kN) using 10:1 lever ratio.
Amps	44.7" l. x 12 .6" w. x 49.6" h. (1,135 x 320 x 1,260 mm).
Watts	1.6
Weight	26
	Net 181 lbs. (82 kg).

Accessories



Clamped Boss Load Ring - 2.0 kN

Code: [78-0060](#)



Clamped Boss Load Ring - 3.0 kN

Code: [78-0160](#)



Clamped Boss Load Ring - 4.5 kN

Code: [78-0260](#)



Counter Balance Kit Complying With ASTM D3080

Code: [26-2114/10](#)



Dial Gauge 10mm Travel X 0.002mm Divisions.

Code: [25-0440](#)



Digital Proving Ring, 1,000 lbs (4.5 kN)

Code: [78-0264](#)



Digital Proving Ring, 450 lbs (2.0 kN)

Code: [78-0064](#)



Mechanical Dial Indicator - 25 mm Range Clockwise Movement

Code: [88-4110](#)



S-Type Load Cell 5 kN.for Triaxial Tests. Fitted with 5 Pin Din Plug.

Code: [27-1551](#)



Set of Weights 50 kg Slotted.

Code: [26-2132](#)



Shear Box Assembly 100mm Sq.

Code: [26-2197](#)



Shear Box Assembly 2.5 Inch Diameter

Code: [26-2213](#)



Shear Box Assembly 60mm Sq.

Code: [26-2181](#)



Vertical Displacement Transducer Assembly 15mm Travel with 5 Pin Din Plug Bracket for Shear Box

Code: [27-1689](#)



Weight Set A

Code: [25-0535](#)



Weight Set B

Code: [25-0537](#)

Spares/Consumables



Dial Indicator - 1.0" Range

Code: [88-4100](#)



Electronic Digital Indicator, 0.600"/15 mm range

Code: [88-4210](#)



Vertical Dial Indicator, English


Code: [25-0445](#)

Alternatives



Digital Direct/Residual Shear Apparatus Complete with Lever Loading Assembly. 220-240V 50/60Hz 1Ph.

Code: [26-2114/01](#)



H60 Field Inspection Vane Tester 0-200Kpa In Carrying Case. includes calibration and certificates.

Code: [26-3335](#)



Hand Vane Tester

Code: [26-3346](#)



Laboratory Vane Apparatus with 4 Springs and 12.7mm Vane; Hand Operated.

Code: [26-2270](#)



Pocket Shearmeter with 3 Vanes 0 to 1Kgf/Cm2 X 0.5Kgf/Cm2.

Code: [26-2261](#)



8in Dia ASTM Sieve No.120 (125 Mic) Stainless Steel Mesh.

Code: 79-5230

Product Group: 8in Dia ASTM Brass Sieves, 8"
Diameter ASTM Sieves, 8" Diameter ASTM Sieves, 8"
Diameter ASTM Sieves

Standards

ASTM E11

Specification

Frames	Full height; 2" (51 mm) depth to mesh.
Construction	Polished and lacquered brass with S.S. mesh.
Nameplates	Show standard, alternate and Tyler Screen Scale equivalent designations.
Weights	Net 1 lb. (453 g).
Sieve Size or Number	No. 120
Sieve Opening Standard	125 um
Sieve Opening Alternative (in.)	0.0049



8in Dia ASTM Sieve 20 micron Stainless Steel Mesh

Code: [79-5310](#)

Product Group: [8" Diameter ASTM Sieves, 8" Diameter ASTM Sieves, 8" Diameter ASTM Sieves](#)



8 Inch Dia Lid.

Code: 79-5400

Product Group: Sieve Lids and Receivers ASTM, 8"
Diameter ASTM Sieves, 8" Diameter ASTM Sieves, 8"
Diameter ASTM Sieves

Standards

ASTM E11



8in Dia Receiver.

Code: 79-5410

Product Group: Sieve Lids and Receivers ASTM, 8"
Diameter ASTM Sieves, 8" Diameter ASTM Sieves, 8"
Diameter ASTM Sieves

Standards

ASTM E11