







# IF IT'S WORTH BUILDING, IT'S WORTH TESTING

www.ele.com

# Contents



This wishlist was generated on 17/06/2020, and contains the following Products:

### 514-021 Dial-Type Gauge Tensiometer 450 mm

514-034 Service Kit



## **Product Sheet**





### **Dial-Type Gauge Tensiometer 450 mm**

Code: 514-021 Product Group: Tensiometers

Durable weather and soil resistant tensiometer.

Designed for permanent installation.

Rapid response.

Accurate yet inexpensive, this tensiometer is ideal for long term deployment in both field and greenhouse environments. The tensiometer is easy to install via the use of the custom insertion tool (514-030), and maintain, with a full range of spares available. Rapid response is ensured by the sensitive 0-100 centibar dial gauge, having a re-calibration facility. For convenience, a range of lengths are available for monitoring at variable depths.

Note: For operating these tensiometers, a service kit (514-034) is required.

The insertion tool (514-030) is used to provide a clearance hole and also to maintain existing hole diameter for the tensiometer.

Further Information

Requires Service Kit (514-034)

#### Accessories



Insertion Tool Code: 514-030



#### Service Kit

Code: 514-034





## Spares/Consumables



Screw-top porous ceramic cup

Code: 514-020/11



Vacuum dial gauge

Code: 514-020/13

## Alternatives



Dial-Type Gauge Tensiometer 450 mm Code: 514-021



Dial-Type Gauge Tensiometer 600 mm Code: 514-022



Dial-Type Gauge Tensiometer 900 mm Code: 514-024



# **Product Sheet**





## Dial-type soil moisture gauge tensiometer 300 mm

Code: 514-020



# **Product Sheet**





### Service Kit

Code: 514-034 Product Group: Tensiometers

This kit is designed to service and maintain soil moisture tensiometers. Kit includes a vacuum hand pump, 455 ml natural colour plastic bottle, rubber washer, 3 mm outside diameter nylon tubing, spout/cap assembly, herbicide/algaecide additive and 12 monthly chart forms.

## Specification

Weight Dimensions 0.77 kgs 330 x 330 x 170 mm

