



## Hand Vane Tester

Code: [26-3346](#)

Product Group: [Hand Vane Tester](#)

- Direct-reading scale with max-reading pointer.
- Provides quick and accurate shear strength values of cohesive soils.
- Lightweight carrying case for easy transport to the field.

The Hand Vane Tester is an accurate and portable instrument used for the determination of in-situ shear strength of cohesive soils, either on-site or on undisturbed or remoulded samples in the laboratory.

The instrument consists of a torque head with a direct-reading scale which is turned by hand. A non-return type pointer retains the test reading. A 19 mm (0.75") diameter vane and 300 mm (11.8") extension rod is supplied as standard.

## Standards

ASTM D2573, ASTM D4648

## Further Information

Includes 19 mm (0.75") vane, extension rod and carrying case.

## Accessories



### 33 mm Diameter Vane and Carry Case

Code: [26-3346/10](#)



### Laboratory Vane Apparatus with 4 Springs and 12.7mm Vane; Hand Operated.

Code: [26-2270](#)

## Spares/Consumables



## Laboratory Vane Apparatus (Motorised)

Code: [26-2275/01](#)

## Alternatives



## Digital Direct/Residual Shear Apparatus Complete with Lever Loading Assembly. 110-120V 50/60Hz 1Ph.

Code: [26-2114/02](#)



## Digital Direct/Residual Shear Apparatus Complete with Lever Loading Assembly. 220-240V 50/60Hz 1Ph.

Code: [26-2114/01](#)



## Pocket Shearmeter with 3 Vanes 0 to 1Kgf/Cm<sup>2</sup> X 0.5Kgf/Cm<sup>2</sup>.

Code: [26-2261](#)