



ELE-Hoek Cell NX 54.74 mm Diameter

Code: [70-1710](#)

Product Group: [Hoek Cells](#)

- For use with pressures up to 70 mPa
- Fast and effective specimen handling
- Accessories for permeability testing

The ELE-Hoek cells in this section have been designed to accept the nominal NX core size as specified in International Standards. The basic cell comprises a steel body and two steel end caps which are screwed to the body of the cell when in use. The body incorporates two self-sealing couplings; one for connecting to the hydraulic pressure system, the other for de-airing the cell chamber and for the attachment of pressure measurement devices if required. Hardened and ground spherical steel pistons and two jackets of the same diameter as the specimen are supplied.

Supplied complete with 2 jackets and 1 pair of load spreader pads.

Specification

Weight	14.5 kg
Diameter	54.74 mm

Accessories



Nylon Tubing 6 mm OD x 4 mm ID 3500 Kpa

Code: [26-1926](#)



Specimen Extruder Bench Mounting Frame for Extruding Specimens From Hoek Cells

Code: [70-2725](#)



Standard Distance Piece - 20 mm Depth

Code: [37-4980](#)



Support Assembly

Code: [81-0094](#)

Spares/Consumables



Spare Jacket Nx Size.

Code: [70-1712](#)

Alternatives



ELE-Hoek Cell ADR Touch 2000 Compression Machine

Code: [70-2630/01](#)



Hand Operated Pressure System with Pressure Gauge & Flexible Hose

Code: 70-5000



Pair of Permeability End Caps NX supplied with Distance Block

Code: 70-1750



Pressure Test 3500 Oil/Water Constant Pressure System with Digital Pressure Gauge

Code: 70-5130/01